

Printing date 04.12.2008

Version: 2

Revision: 03.12.2008

1 Identification of the substance/preparation and of the company/undertaking

· Product details

PEROXAN BIB-40 P· Trade name:
· Application of the substance /
the preparationReaction initiator
For industrial use

· Manufacturer/Supplier:

PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50· Further information obtainable
from:Environment protection / Security of labour
Competent person:
* Kathrin Bohland (Sales) e-mail: k.bohland@pergan.com
* Christoph Wilting (Environment protection / Security of labour) e-mail: c.wilting@pergan.com· Information in case of
emergency:

- Tel: +49 2871 9902-0

2 Hazards identification

· Hazard description:

Xi Irritant
O Oxidising· Information concerning
particular hazards for human
and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 7 May cause fire.
R 36/38 Irritating to eyes and skin.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

*** 3 Composition/information on ingredients**

· Chemical characterization

· Dangerous components:

CAS: 471-34-1 EINECS: 207-439-9 Reg.nr.: 05-2117814113-58-0000	calcium carbonate		50-60%
CAS: 25155-25-3 EINECS: 246-678-3 Reg.nr.: 05-2116407671-51-0000	[(1,3 / 1,4)-phenylenebis(1-methylethylidene)]bis[tert-butyl] peroxide	Xi, O; R 7-36/38	30-40%

· Additional information:

For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· General information:

Take care of personal protection for the first aider.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Take affected persons into fresh air and keep quiet.
Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Immediately remove contaminated clothing.

· After swallowing:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
If symptoms persist consult doctor.**5 Fire-fighting measures**

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· Special hazards caused by the
substance, its products of
combustion or resulting gases:

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· Protective equipment:

Do not inhale explosion gases or combustion gases.


· Additional information

Cool endangered receptacles with water spray.
Self-protection first!


Trade name: **PEROXAN BIB-40 P**

(Contd. of page 1)

6 Accidental release measures

- **Person-related safety precautions:** In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:** Ensure adequate ventilation. Pick up mechanically, collect in a suitable receptacle and dispose in accordance with government regulations.
- **Additional information:** In case of large spillage the environmental authority should be informed.

7 Handling and storage

- **Handling:** Pay attention to the special requirements of your local authorities for handling with dangerous goods.
- **Information for safe handling:** Keep receptacles tightly sealed. Store in cool, dry place in tightly closed receptacles. Open and handle receptacle with care. Prevent formation of dust. Wear suitable respiratory protective device when decanting larger quantities without extractor facilities. Before break and at the end of work hands should be thoroughly washed. Oxidizing because of releasing oxygene. While using do not eat, drink or smoke. Avoid shock and friction.
- **Information about fire - and explosion protection:** Prevent impact and friction.  Avoid open flames, sparks, direct sunlight and other sources of ignition.
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store in a cool location. Store only in the original receptacle. Prevent any seepage into the ground. Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Protect from contamination. Store in a cool place.
- **Recommended storage temperature (To maintain quality):** max.: +30°C
- **Storage class:** 5.2 "Organic Peroxides" (VCI Guideline)




8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin.

(Contd. on page 3)

Trade name: **PEROXAN BIB-40 P**

(Contd. of page 2)

<ul style="list-style-type: none"> · Respiratory protection: · Protection of hands: · Material of gloves · Penetration time of glove material · Eye protection: · Body protection: 	<p>Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation.</p> <p> Filter P2</p> <p>Only use chemical-protective gloves with CE-labelling of category III.  Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</p> <p>Protective gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene</p> <p>The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.</p> <p> Tightly sealed goggles</p> <p>Protective work clothing</p>
--	---

9 Physical and chemical properties

· General Information	
· Form:	Solid Powder
· Colour:	Whitish
· Odour:	Characteristic
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	May cause fire.
· Decomposition temperature:	> +90°C (SADT)
· Self-igniting:	Product is not selfigniting.
· Density:	Not determined.
· Bulk density at 20°C:	480 kg/m ³
· Solubility in / Miscibility with water:	Insoluble.
· Segregation coefficient (n-octanol/water): not determined	

10 Stability and reactivity

<ul style="list-style-type: none"> · Thermal decomposition / conditions to be avoided: · Materials to be avoided: · Dangerous reactions · Dangerous decomposition products: 	<p>SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications.</p> <p>Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines). Self-accelerating decomposition at SADT.</p> <p>Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.</p>
---	---

(Contd. on page 4)

Trade name: **PEROXAN BIB-40 P**

(Contd. of page 3)

· **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

471-34-1 calcium carbonate

Oral LD50 >2000 mg/kg (rattus)

25155-25-3 [(1,3 / 1,4)-phenylenebis(1-methylethylidene)]bis[tert-butyl] peroxide

Oral LD50 >2000 mg/kg (-)

Inhalative LC50 >20 mg/l (-)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Low irritant effect

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· **Product:**

· **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key:**

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· **Uncleaned packaging:**

· **Recommendation:**

This material and its container must be disposed of as hazardous waste.

14 Transport information

· **Transport/Additional information:**

Not subject to the requirement for Class 5.2. (exempt)

*** 15 Regulatory information**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant
O Oxidising

· **Hazard-determining components of labelling:**

[(1,3 / 1,4)-phenylenebis(1-methylethylidene)]bis[tert-butyl] peroxide

· **Risk phrases:**

7 May cause fire.
36/38 Irritating to eyes and skin.

· **Safety phrases:**

3/7 Keep container tightly closed in a cool place.
14 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 5)

Printing date 04.12.2008

Version: 2

Revision: 03.12.2008

Trade name: **PEROXAN BIB-40 P**

(Contd. of page 4)

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Please note:** Take care of the respective local regulations.

· **Substance of High Concern = SVHC**

None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

36/38 Irritating to eyes and skin.

7 May cause fire.

· **Department issuing MSDS:**

Environment protection / Security of labour

· **Contact:**

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· * **Data compared to the previous version altered.**