

PEROXAN BIB-40 PE-G

Dialkyl peroxide / Crosslinking

Description Di-(2-tert.-butyl-peroxyisopropyl)-benzene

40%, Granules mit polyethylene

PEROXAN BIB-40 PE-G is used for the crosslinking of polyethylene.

 Molecular weight:
 338.5

 CAS No.:
 25155-25-3

Technical data Appearance: off-white granules

Peroxide assay: appx. 40%
Active oxygen assay: appx. 3.78%
Bulk density at 20°C: 390 kg/m³

Half life time in an EPDM compound:

t ½	10h	1h	0,1h
bei	117°C	146°C	169°C

StorageMaximum storage temperature (Ts max):30°CStorage stability as from date of delivery:6 months

Hazardous reactionsOrganic Peroxides are more or less stable products but will decompose under the influence of heat. To minimize a loss of quality during storage, it is important that the recommended maximum storage temperature is not

exceeded. If a minimum storage temperature is given, an undesirable process such as a solidification or phase

separation, is known to occur below this temperature.

Safety characteristics SADT: 80°C

The SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which a self accelerating decomposition may occur.





PEROXAN BIB-40 PE-G

Dialkyl peroxide / Crosslinking

Application PEROXAN BIB-40 PE-G is recommended for the crosslinking of polyethylene. Compounds

containing PEROXAN BIB-40 PE-G have excellent scorch safety.

Safe processing temperature (t2): 135°C Typical crosslinking temperature (t90): 175°C

The safe processing temperature t2 is defined as the temperature, at which the scorch time is longer than 20 minutes. The typical crosslinking temperature t90 is defined as the temperature at

which 90% of the crosslinks in the compound are formed within about 12 minutes.

Packaging 20kg cardboard box

Major decomposition products Acetone, Acetyl-2-hydroxyisopropylbenzene, Di(2-hydroxyisopropyl)benzene,

Diacetylbenzene, Methane, tert-Butanol

Safety and handling

Please refer to the material safety data sheet (MSDS) for information concerning safe storage, use and handling
of PEROXAN BIB-40 PE-G. This information should be thoroughly reviewed prior to acceptance of this product.

The MSDS is available for downloading at www.pergan.com or through contacting Pergan directly.

The information presented herein is true and accurate and to the best of our knowledge, but without any guarantee. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestions.



Schlavenhorst 71 Phone: +49 (0)2871 / 99 02-0
D-46395 Bocholt Fax: +49 (0)2871 / 99 02-50
Germany www.pergan.com