

PEROXAN PM-25 S

Peroxyester / Curing

Description tert-Butyl peroxymaleate

25%, Suspension with plasticizer

PEROXAN PM-25 S is used for the curing of MMA resins.

CAS No.: 1931-62-0

Technical data Appearance: white suspension

Active oxygen assay: appx. 2.13%
Density at 20°C: 1.2 g/cm³

Solubility Insoluble in water, soluble in various organic solvents

Storage Maximum storage temperature (Ts max): 30°C

Storage stability as from date of delivery: 6 months

Hazardous reactions Keep packaging tightly closed in a well ventilated place at indicated storage temperature. Keep away from

reducing agents e.g. amines, acids, alkalis, heavy metal compounds (e.g. accelerators, driers, metal soaps).

Never weigh out in storage room.

Oxidizing agent. Decomposes violently under the influence of heat or by contact with reducing agent. Never mix

with accelerators.

Safety characteristics Flash point: >SADT°C

SADT: 60°C

The SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which a self accelerating decomposition may occur.





PEROXAN PM-25 S

Peroxyester / Curing

Application

PEROXAN PM-25 S is used for the ambient temperature curing of MMA resins.

Without the addition of an accelerator, the cure of the acrylic resin starts only above the activation temperature of 90°C.

For the cure at ambient temperature, PEROXAN PM-25 S must be accelerated with a combination of special accelerators.

Together with the accelerator PERGAQUICK CA and PROMOTOR MA, a reasonable geltime is obtained with a fast cure at ambient temperature.

The most important advantage of a cure system basedon PEROXAN PM-25 S is the absence of yellow discolouration and a lower residual monomer content compared to results obtained with a BPO/amine curing system.

Depending on application and working conditions, the following peroxide and when applicable accelerator dosage levels are recommended:

PEROXAN PM-25 S: 2,0 to 5,0 phr PERGAQUICK CA: 0,3 to 1,5 phr PROMOTOR MA: 0,1 to 0,5 phr

Packaging 25kg container

Major decomposition products Unknown

Safety and handling

Please refer to the material safety data sheet (MSDS) for information concerning safe storage, use and handling of PEROXAN PM-25 S. This information should be thoroughly reviewed prior to acceptance of this product. The MSDS is available for downloading at www.pergan.com or through contacting Pergan directly.

The information presented herein is true and accurate and to the best of our knowledge, but without any guarantee. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestions.

