


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - Trade name: **PEROXAN BP-Paste 50 BM**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 - No further relevant information available.
- **Application of the substance / the mixture**
 - Reaction initiator
 - For industrial use
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:**
 - Environment protection / Security of labour
 - Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:**
 - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**
 - Org. Perox. E H242 Heating may cause a fire.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Aquatic Acute 1 H400 Very toxic to aquatic life.
 - Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
 - **Hazard pictograms**

GHS02 GHS07 GHS09
 - **Signal word**
Warning
 - **Hazard-determining components of labelling:**
dibenzoyl peroxide
 - **Hazard statements**
H242 Heating may cause a fire.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.
 - **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234 Keep only in original packaging.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410 Protect from sunlight.
P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
P420 Store separately.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
 - **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 94-36-0	dibenzoyl peroxide	40-50%
EINECS: 202-327-6	Org. Perox. B, H241; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Eye Irrit. 2, H319; Skin Sens. 1, H317	
Index number: 617-008-00-0		
Reg-No.: 01-2119511472-50		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:



Take care of personal protection for the first aider.

After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbon dioxide and -monoxid.

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 2)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
While using do not eat, drink or smoke.
Do not generate flames or sparks.
Keep product and emptied container away from heat and sources of ignition.
Avoid shock and friction.
Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.
Protect against electrostatic charges.
Prevent impact and friction.
Use explosion-proof apparatus / fittings and spark-proof tools.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Pay attention to the special requirements of your local authorities for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed.
Protect from heat and direct sunlight.
Protect from contamination.
Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

+5 +30 °C

Storage class:

5.2

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

WEL (Great Britain) Long-term value: 5 mg/m³

DNELs





94-36-0 dibenzoyl peroxide

Oral	DNEL Longterm System	2 mg/kg bw/day (General population)
Dermal	DNEL Longterm System	13.3 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	39 mg/m ³ (Worker)

(Contd. on page 4)

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 3)

· PNECs	
94-36-0 dibenzoyl peroxide	
PNEC Marinewater sed	0.001 mg/kg sed dw
PNEC Freshwater	0.00002 mg/l (AF 50)
PNEC Freshwater sed	0.013 mg/kg sed dw
PNEC STP	0.35 mg/l
PNEC Marinewater	0.000002 mg/l (AF 500)
· Additional information:	The lists valid during the making were used as basis.
· 8.2 Exposure controls	
· Appropriate engineering controls	No further data; see section 7.
· Individual protection measures, such as personal protective equipment	
· General protective and hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.
· Respiratory protection:	Not necessary if room is well-ventilated.
	 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	Filter A2
· Hand protection	Only use chemical-protective gloves with CE-labelling of category III.
	 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	Protective gloves
· Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene
· Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· Eye/face protection	 Tightly sealed goggles
· Body protection:	 Protective work clothing

* **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not determined.
· Decomposition temperature:	+50 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.

(Contd. on page 5)
GB

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 4)

· Dynamic at 20 °C:	15.000 - 30.000 mPas
· Solubility	
· water:	Undetermined.
· Partition coefficient n-octanol/water (log value)	not determined
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.1 - 1.3 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	No further relevant information available.
· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbon dioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· Acute toxicity	Based on available data, the classification criteria are not met.

(Contd. on page 6)

Trade name: **PEROXAN BP-Paste 50 BM**


(Contd. of page 5)

· LD/LC50 values relevant for classification:	
94-36-0 dibenzoyl peroxide	
Oral	LD50 >5,000 mg/kg (rattus)
· Skin corrosion/irritation	Based on available data, the classification criteria are not met.
· Serious eye damage/irritation	Causes serious eye irritation.
· Respiratory or skin sensitisation	May cause an allergic skin reaction.
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.
· Carcinogenicity	Based on available data, the classification criteria are not met.
· Reproductive toxicity	Based on available data, the classification criteria are not met.
· STOT-single exposure	Based on available data, the classification criteria are not met.
· STOT-repeated exposure	Based on available data, the classification criteria are not met.
· Aspiration hazard	Based on available data, the classification criteria are not met.
· 11.2 Information on other hazards	
· Endocrine disrupting properties	
None of the ingredients is listed.	

* **SECTION 12: Ecological information**

· 12.1 Toxicity	
· Aquatic toxicity:	
94-36-0 dibenzoyl peroxide	
EC50 / 72h	0.0711 mg/l (pseudokirchneriella subcapitata)
LC50 / 96h	0.0602 mg/l (oncorhynchus mykiss)
EC50 / 48h	110 mg/l (daphnia)
· 12.2 Persistence and degradability	
· Degree of elimination:	
· Classification:	
94-36-0 dibenzoyl peroxide	
Degradation	(Readily biodegradable) (OECD 301 D)
· 12.3 Bioaccumulative potential	
· Partition coefficient: nOctanol/water: [Log Kow]	
94-36-0 dibenzoyl peroxide	3,2 (20 °C)
· 12.4 Mobility in soil	No further relevant information available.
· 12.5 Results of PBT and vPvB assessment	
· PBT:	The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
· 12.6 Endocrine disrupting properties	The product does not contain substances with endocrine disrupting properties.
· 12.7 Other adverse effects	No further relevant information available.
· Remark:	Very toxic for fish
· Additional ecological information:	
· General notes:	Very toxic for aquatic organisms Also poisonous for fish and plankton in water bodies. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods	
· Recommendation	 <p>After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.</p> <p>Must not be disposed together with household garbage. Do not allow product to reach sewage system.</p>
· Waste disposal key:	Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

(Contd. on page 7)






GB

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	UN3108
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	UN3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE), MARINE POLLUTANT ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	5.2 (P1) Organic peroxides. 5.2
<ul style="list-style-type: none"> · IMDG <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> · IATA <div style="display: flex; align-items: center; gap: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label 	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	Void
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	Product contains environmentally hazardous substances: DIBENZOYL PEROXIDE Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code 	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	500 g Code: E0 Not permitted as Excepted Quantity 2 D
<ul style="list-style-type: none"> · RID / GGVSEB: 	like ADR
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 	500 g

(Contd. on page 8)
GB

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 7)

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

* SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for
the application of lower-tier
requirements

50 t

· Qualifying quantity (tonnes) for
the application of upper-tier
requirements

200 t

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Please note: Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS:

Environment protection / Security of labour

· Contact:

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B

Org. Perox. E: Organic peroxides – Type E/F

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 9)

GB

Trade name: **PEROXAN BP-Paste 50 BM**

(Contd. of page 8)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· * Data compared to the
previous version altered.