

Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN CU-90 L · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

Further information obtainable

Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. F H242 Heating may cause a fire. Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to Hazard pictograms

Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.









GHS02 GHS05 GHS06 GHS08 GHS09

· Signal word Danger

Hazard-determining

components of labelling:

 $\alpha,\!\alpha$  -dimethylbenzyl hydroperoxide

Cumene

2-Phenyl-2-propanol

· Hazard statements H242 Heating may cause a fire.

H302+H312 Harmful if swallowed or in contact with skin. H331 Toxic if inhaled. Causes severe skin burns and eye damage.

H314 H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No · Precautionary statements P210

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e.g. heavy metal compounds and amines).

P234 Keep only in original packaging. P264 Wash thoroughly after handling. P273 Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection/hearing P280

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

(Contd. on page 2)



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

Trade name: PEROXAN CU-90 L

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up. P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Dangerous components:		
	α,α -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: $3\%$ ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: $1\%$ ≤ C < 3 % STOT SE 3; H335: C < 10 %	80-90%
CAS: 98-82-8 EINECS: 202-704-5 Index number: 601-024-00-X Reg-No.: 01-2119473983-24	Cumene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335	5-10%
CAS: 617-94-7 EINECS: 210-539-5	2-Phenyl-2-propanol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-5%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take care of personal protection for the first aider.

After inhalation: Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate

No further relevant information available.

medical attention and special treatment needed

No further relevant information available

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

# Trade name: PEROXAN CU-90 L

(Contd. of page 2)

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: · Additional information Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.

Self-protection first!

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Inform respective authorities in case of seepage into water course or sewage system.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

(Contd. on page 4)



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

Trade name: PEROXAN CU-90 L

Keep ignition sources away - Do not smoke.

(Contd. of page 3)

 $\cdot$  7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in

one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about

storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination.

Store under lock and key and out of the reach of children.

· Recommended storage temperature (To maintain

quality):

0 .... +30 °C

7.3 Specific end use(s)

No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters				
Ingredients with limit values that require monitoring at the workplace:				
98-82-8 C	98-82-8 Cumene			
WEL (Gre			le: 250 mg/m³, 50 ppm	
	SI	0	e: 125 mg/m³, 25 ppm	
IOELV (E	IOELV (EU) Short-term value: 250 mg/m³, 50 ppm Long-term value: 50 mg/m³, 10 ppm Skin			
·DNELs	DNELs			
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide			
Inhalative DNEL Longterm System 6 mg/m3 (Worker)				
98-82-8 C	98-82-8 Cumene			
Dermal	DNEL Longt	erm System	15.4 mg/kg bw/day (Worker)	
Inhalative	DNEL Longi	erm System	100 mg/m3 (Worker)	
PNECs				
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide			
PNEC Ma	rinewater sec	0.002 mg/k	g sed dw (-)	
PNEC Fre	PNEC Freshwater 0.003 mg/l (AF 1.000)			

 PNEC Marinewater sed
 0.002 mg/kg sed dw (-)

 PNEC Freshwater
 0.003 mg/l (AF 1.000)

 PNEC Freshwater sed
 0.023 mg/kg sed dw (-)

 PNEC Soil
 0.003 mg/kg sed dw (-)

 PNEC STP
 0.35 mg/l (-)

 PNEC Marinewater
 0 mg/l (AF 10.000)

#### 98-82-8 Cumene

PNEC Marinewater sed PNEC Freshwater PNEC Freshwater Sed PNEC Soil PNEC STP PNEC STP PNEC Marinewater PNEC Marinewater Sed PNEC Marinewater 0.032 mg/kg sed dw (-) 0.624 mg/kg soil dw (-) 200 mg/l (AF 10) 0.004 mg/l (AF 100)

· Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

· Appropriate engineering

**controls** No further data; see section 7.

Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

(Contd. on page 5)



(Contd. of page 4)

Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

## Trade name: PEROXAN CU-90 L

Store protective clothing separately. Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

colourless - yellowish

observed.

Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:

· Odour: Characteristic Odour threshold: Not determined.

· Melting point/freezing point: Not applicable. Boiling point or initial boiling point and boiling range Not applicable. Not applicable.

· Flammability

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. > SADT · Flash point:

Decomposition temperature: +70 °C (SADT) Ha · Not determined.

Viscosity:

· Kinematic viscosity

Not determined. Dynamic at 20 °C: 11 mPas

· Solubility

· water: Undetermined. · Partition coefficient n-octanol/water (log value) not determined

· Vapour pressure:

· Density and/or relative density

Density at 20 °C: 1.06 g/cm<sup>3</sup> Not determined. Relative density · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form:

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour

Fluid

mixtures are possible.

Not determined.

(Contd. on page 6)



Version: 11 (replaces version 10) Printing date 02.01.2024 Revision: 27.11.2023

# Trade name: PEROXAN CU-90 L

(Contd. of page 5)

Change in condition  Evaporation rate	Not determined.	
Information with regard to physical hazard classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammable gases	in	
contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Heating may cause a fire.	
Corrosive to metals	Void	
Desensitised explosives	Void	

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT.

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

10.6 Hazardous decomposition

· Additional information:

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Harmful if swallowed or in contact with skin. Acute toxicity Toxic if inhaled

	Toxic ii iiinialea.			
· LD/LC50	· LD/LC50 values relevant for classification: 80-15-9 α,α -dimethylbenzyl hydroperoxide			
80-15-9 α,				
Oral	Oral LD50 200-2,000 mg/kg (rattus)			
Dermal	LD50	400-2,000 mg/kg (rattus)		
Inhalative	LC50 / 4h	0.5-2 mg/l (rattus)		
98-82-8 C	98-82-8 Cumene			
Oral	Oral LD50 2,260 mg/kg (rattus)			
Dermal	LD50	12,300 mg/kg (cuniculosus)		
Inhalative	halative LC50 / 4h 24.7 mg/l (mus)			
617-94-7 2	617-94-7 2-Phenyl-2-propanol			
Oral	LD50	1,300 mg/kg (rattus)		
Dermal	LD50	4,300 mg/kg (cuniculosus)		

Skin corrosion/irritation

Causes severe skin burns and eye damage.

(Contd. on page 7)



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

Trade name: PEROXAN CU-90 L

 Serious eye damage/irritation Causes serious eye damage. (Contd. of page 6)

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. May cause respiratory irritation.

· STOT-single exposure

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard May be fatal if swallowed and enters airways.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

#### 80-15-9 α,α -dimethylbenzyl hydroperoxide

LC50 10-100 mg/l (leuciscus idus)

- 12.2 Persistence and degradability
- · Degree of elimination:

· Classification:

#### 80-15-9 $\alpha$ , $\alpha$ -dimethylbenzyl hydroperoxide

Degradation (Not readily biodegradable) (OECD 301 B)

98-82-8 Cumene

Degradation (Readily biodegradable)

12.3 Bioaccumulative potential

· Partitio	n coefficient: nOctanol/water: [Log Kow]	
80-15-9	α,α -dimethylbenzyl hydroperoxide	1,6 (25°C)
98-82-8	Cumene	3,55 (20°C)
617-94-7	2-Phenyl-2-propanol	1,89 (25°C)
98-86-2	acetophenone	1,65 (20°C)

· 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

· 12.6 Endocrine disrupting properties

· 12.7 Other adverse effects

The product does not contain substances with endocrine disrupting properties.

· Remark:

Toxic for fish · Additional ecological information:

General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Must not reach sewage water or drainage ditch undiluted or unneutralised. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-· Waste disposal key:

number.

• Uncleaned packaging:

· Recommendation: This material and its container must be disposed of as hazardous waste.

GB



Version: 11 (replaces version 10) Printing date 02.01.2024 Revision: 27.11.2023

# Trade name: PEROXAN CU-90 L

(Contd. of page 7)

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3109
· 14.2 UN proper shipping name · ADR	UN3109 ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE), ENVIRONMENTALLY HAZARDOUS
·IMDG	ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE), MARINE POLLUTANT ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE)
· 14.3 Transport hazard class(es)	CROANCT EROXIDE THE ET, EIGOID (CONTENTION EROXIDE)
· ADR	
· Class · Label	5.2 (P1) Organic peroxides. 5.2+8
· IMDG	
· Class · Label	5.2 Organic peroxides. 5.2/8
· IATA	
· Class · Label	<ul><li>5.2 Organic peroxides.</li><li>5.2 (8)</li></ul>
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: CUMYLHYDROPEROXIDE, Cumene
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Organic peroxides.
· Stowage Category · Stowage Code	D SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.
· 14.7 Maritime transport in bulk according to IMO	) instruments Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ) · Excepted quantities (EQ)	125 ml Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· RID / GGVSEB:	like ADR
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	125 ml Code: E0 Not permitted as Excepted Quantity



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

Trade name: PEROXAN CU-90 L

(Contd. of page 8)

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier

requirements 200 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- Other regulations, limitations and prohibitive regulations
- · Please note: Take care of the respective local regulations

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.

> H242 Heating may cause a fire. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

 Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation / ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)



Printing date 02.01.2024 Version: 11 (replaces version 10) Revision: 27.11.2023

Trade name: PEROXAN CU-90 L

(Contd. of page 9)

Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. E: Organic peroxides – Type E/F
Org. Perox. F: Organic peroxides – Type E/F
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

·\* Data compared to the previous version altered.

GB