





## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN ME-50 LM4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour  
Competent person:  
\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wiltung, e-mail: c.wiltung@pergan.com  
Security of labour
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## \* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
  - Org. Perox. D H242 Heating may cause a fire.
  - Acute Tox. 4 H332 Harmful if inhaled.
  - Skin Corr. 1B H314 Causes severe skin burns and eye damage.
  - Eye Dam. 1 H318 Causes serious eye damage.
  - Skin Sens. 1 H317 May cause an allergic skin reaction.
  - Muta. 2 H341 Suspected of causing genetic defects.
  - Carc. 2 H351 Suspected of causing cancer.
  - Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**

GHS02 GHS05 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane  
tert-butyl hydroperoxide  
hydrogen peroxide solution
- **Hazard statements**
  - H242 Heating may cause a fire.
  - H332 Harmful if inhaled.
  - H314 Causes severe skin burns and eye damage.
  - H317 May cause an allergic skin reaction.
  - H341 Suspected of causing genetic defects.
  - H351 Suspected of causing cancer.
  - H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
  - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P234 Keep only in original packaging.
  - P264 Wash thoroughly after handling.
  - P273 Avoid release to the environment.
  - P280 Wear protective gloves/protective clothing/eye protection/face protection.
  - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P310 Immediately call a POISON CENTER/doctor.
  - P405 Store locked up.
  - P410 Protect from sunlight.

Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 1)

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.  
P420 Store separately.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

· **Dangerous components:**

CAS: 1338-23-4 EC number: 700-954-4 Reg-No.: 01-2119514691-43	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane Org. Perox. D, H242; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	30-40%
CAS: 75-91-2 EINECS: 200-915-7 Reg-No.: 01-2119446670-40	tert-butyl hydroperoxide Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 2, H351; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limits: Eye Dam. 1; H318: C ≥ 1 % Skin Sens. 1; H317: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	2.5-5%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 % Skin Corr. 1B; H314: 50 % ≤ C < 70 % Skin Irrit. 2; H315: 35 % ≤ C < 50 % Eye Dam. 1; H318: C ≥ 8 % Eye Irrit. 2; H319: 5 % ≤ C < 8 % STOT SE 3; C ≥ 35 % Ox. Liq. 1; H271: C ≥ 70 % Ox. Liq. 2; H272: 50 % ≤ C < 70 %	1-2.5%
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg-No.: 01-2119539582-35	2-methylpentane-2,4-diol Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

- **After inhalation:** Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.


Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 2)




### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.  
Self-protection first!

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.  
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Open and handle receptacle with care.  
Prevent formation of aerosols.  
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
Do not refill residue into storage receptacles.  
Restrict the quantity stored at the work place.  
Before break and at the end of work hands should be thoroughly washed.  
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
While using do not eat, drink or smoke.  
Do not generate flames or sparks.  
Keep product and emptied container away from heat and sources of ignition.  
Avoid shock and friction.  
Take precautionary measures against static discharges.
- **Information about fire - and explosion protection:**  Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.  
Prevent impact and friction.  
Use explosion-proof apparatus / fittings and spark-proof tools.  
Fumes can combine with air to form an explosive mixture.
-  Wear shoes with conductive soles.  
Formation of flammable or explosive gas/air-mixtures is possible.
-  Avoid open flames, sparks, direct sunlight and other sources of ignition.

(Contd. on page 4)  
GB

Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
Prevent any seepage into the ground.  
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.  
Protect from heat and direct sunlight.  
Protect from contamination.  
Store under lock and key and out of the reach of children.  
Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** 0 .... +30 °C
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### 7722-84-1 hydrogen peroxide solution

WEL (Great Britain)	Short-term value: 2.8 mg/m <sup>3</sup> , 2 ppm Long-term value: 1.4 mg/m <sup>3</sup> , 1 ppm
---------------------	---

##### 107-41-5 2-methylpentane-2,4-diol

WEL (Great Britain)	Short-term value: 123 mg/m <sup>3</sup> , 25 ppm Long-term value: 123 mg/m <sup>3</sup> , 25 ppm
---------------------	---

#### · DNELs

##### 1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

Dermal	DNEL Longterm System	1.43 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	7.55 mg/m <sup>3</sup>
	DNEL Longterm System	2.52 mg/m <sup>3</sup> (Worker)

##### 75-91-2 tert-butyl hydroperoxide

Dermal	DNEL Longterm System	0.21 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	85.2 mg/m <sup>3</sup> (Worker)
	DNEL Acute Local	28.4 mg/m <sup>3</sup> (Worker)
	DNEL Longterm System	2.2 mg/m <sup>3</sup> (Worker)
	DNEL Longterm Local	0.58 mg/m <sup>3</sup> (Worker)

##### 7722-84-1 hydrogen peroxide solution

Inhalative	DNEL Longterm Local	1.4 mg/m <sup>3</sup> (Worker)
------------	---------------------	--------------------------------

##### 107-41-5 2-methylpentane-2,4-diol

Dermal	DNEL Longterm System	42 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	44.4 mg/m <sup>3</sup> (Worker)

#### · PNECs

##### 1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

PNEC Marinewater sed	0.009 mg/kg sed dw
PNEC Freshwater	0.006 mg/l (AF 1.000)
PNEC Freshwater sed	0.088 mg/kg sed dw
PNEC Soil	0.014 mg/kg soil dw
PNEC STP	1.2 mg/l (AF 10)
PNEC Marinewater	0.001 mg/l (AF 10.000)

##### 75-91-2 tert-butyl hydroperoxide

PNEC Marinewater sed	0.001 mg/kg sed dw
PNEC Freshwater	0.002 mg/l (AF 1.000)
PNEC Seawater	0 mg/l (AF 10.000)

(Contd. on page 5)

**Trade name: PEROXAN ME-50 LM4**


(Contd. of page 4)

PNEC Freshwater sed	0.006 mg/kg sed dw (-)
PNEC Soil	0.166 mg/kg soil dw (AF 1.000)
PNEC STP	0.17 mg/l (AF 100)
<b>7722-84-1 hydrogen peroxide solution</b>	
PNEC Marinewater sed	0.047 mg/kg sed dw
PNEC Freshwater	0.013 mg/l (AF 50)
PNEC Freshwater sed	0.047 mg/kg sed dw
PNEC Soil	0.002 mg/kg soil dw
PNEC STP	4.66 mg/l (AF 100)
PNEC Marinewater	0.013 mg/l (AF 50)
<b>107-41-5 2-methylpentane-2,4-diol</b>	
PNEC Marinewater sed	0.159 mg/kg sed dw (-)
PNEC Freshwater	0.429 mg/l (AF 1.000)
PNEC Freshwater sed	1.59 mg/kg sed dw (-)
PNEC Soil	0.066 mg/kg soil dw (-)
PNEC STP	20 mg/l (AF 10)
PNEC Marinewater	0.043 mg/l (AF 10.000)


- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid close or long term contact with the skin.  
 Avoid contact with the eyes and skin.  
 Do not eat, drink, smoke or sniff while working.  
 Use skin protection cream for skin protection.  
 Be sure to clean skin thoroughly after work and before breaks.
- **Respiratory protection:**

Not necessary if room is well-ventilated.  
 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.


 Filter A2
- **Hand protection**


Only use chemical-protective gloves with CE-labelling of category III.

 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**

Protective gloves  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.  
 Butyl rubber, BR  
 Fluorocarbon rubber (Viton)  
 Nitrile rubber, NBR  
 Neoprene
- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**

 Tightly sealed goggles
- **Body protection:**

 Protective work clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Colourless

(Contd. on page 6)

Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· <b>Odour:</b></li> <li>· <b>Odour threshold:</b></li> <li>· <b>Melting point/freezing point:</b></li> <li>· <b>Boiling point or initial boiling point and boiling range</b></li> <li>· <b>Flammability</b></li> <li>· <b>Lower and upper explosion limit</b></li> <li>· <b>Lower:</b></li> <li>· <b>Upper:</b></li> <li>· <b>Flash point:</b></li> <li>· <b>Decomposition temperature:</b></li> <li>· <b>pH</b></li> <li>· <b>Viscosity:</b></li> <li>· <b>Kinematic viscosity</b></li> <li>· <b>Dynamic at 20 °C:</b></li> <li>· <b>Solubility</b></li> <li>· <b>water:</b></li> <li>· <b>Partition coefficient n-octanol/water (log value)</b></li> <li>· <b>Vapour pressure:</b></li> <li>· <b>Density and/or relative density</b></li> <li>· <b>Density at 20 °C:</b></li> <li>· <b>Relative density</b></li> <li>· <b>Vapour density</b></li> </ul>	<ul style="list-style-type: none"> <li>Characteristic</li> <li>Not determined.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not determined.</li> <li>Not determined.</li> <li>&gt; SADT</li> <li>Not determined.</li> <li>+60 °C (SADT)</li> <li>Not determined.</li> <li>Not determined.</li> <li>24 mPas</li> <li>Undetermined.</li> <li>not determined</li> <li>Not determined.</li> <li>1.12 g/cm<sup>3</sup></li> <li>Not determined.</li> <li>Not determined.</li> </ul>
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b></li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b></li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b></li> <li>· <b>Explosive properties:</b></li> <li>· <b>Change in condition</b></li> <li>· <b>Evaporation rate</b></li> </ul>	<ul style="list-style-type: none"> <li>Fluid</li> <li>Product is not selfigniting.</li> <li>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</li> <li>Not determined.</li> </ul>
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b></li> <li>· <b>Flammable gases</b></li> <li>· <b>Aerosols</b></li> <li>· <b>Oxidising gases</b></li> <li>· <b>Gases under pressure</b></li> <li>· <b>Flammable liquids</b></li> <li>· <b>Flammable solids</b></li> <li>· <b>Self-reactive substances and mixtures</b></li> <li>· <b>Pyrophoric liquids</b></li> <li>· <b>Pyrophoric solids</b></li> <li>· <b>Self-heating substances and mixtures</b></li> <li>· <b>Substances and mixtures, which emit flammable gases in contact with water</b></li> <li>· <b>Oxidising liquids</b></li> <li>· <b>Oxidising solids</b></li> <li>· <b>Organic peroxides</b></li> <li>· <b>Corrosive to metals</b></li> <li>· <b>Desensitised explosives</b></li> <li>· <b>Other safety characteristics</b></li> <li>· <b>Active oxygen</b></li> </ul>	<ul style="list-style-type: none"> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Heating may cause a fire.</li> <li>Void</li> <li>Void</li> <li>8.9 - 9.4 %</li> </ul>

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

(Contd. on page 7)

Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 6)

- **10.3 Possibility of hazardous reactions** To avoid thermal decomposition do not overheat.
- **10.4 Conditions to avoid** Self-accelerating decomposition at SADT.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **Additional information:** Hydrocarbons, carbon dioxide and -monoxid.  
No hazardous decomposition products if used and stored according to specifications.  
Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

**SECTION 11: Toxicological information**

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

Oral	LD50	1,017 mg/kg (rattus)
------	------	----------------------

**75-91-2 tert-butyl hydroperoxide**

Oral	LD50	805 mg/kg / (70%) (rattus)
Dermal	LD50	633 mg/kg / (70%) (cuniculosus)
Inhalative	LC50 / 4h	1.2 mg/l / (70%) (rattus)

**107-41-5 2-methylpentane-2,4-diol**

Oral	LD50	>2,000 mg/kg (rattus)
Dermal	LD50	>2,000 mg/kg (cuniculosus)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Suspected of causing genetic defects.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

- **Aquatic toxicity:**

**1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

LC50 / 96h	44.2 mg/l (-)
------------	---------------

**75-91-2 tert-butyl hydroperoxide**

EC50 / 72h	2.1 mg/l / (70%) (selenastrum capricornutum)
LC50 / 96h	42.3 mg/l / (70%) (pimephales promelas)
EC50	24.3 mg/l / (70%) (activa sludge)
EC50 / 48h	20 mg/l / (70%) (daphnia magna)

**107-41-5 2-methylpentane-2,4-diol**

LC50 / 96h	8,510 mg/l (gambusia affinis)
------------	-------------------------------

- **12.2 Persistence and degradability**

- **Degree of elimination:**

- **Classification:**

**1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

Degradation	(Readily biodegradable) (OECD 301 B)
-------------	--------------------------------------

**75-91-2 tert-butyl hydroperoxide**

Degradation	(Not readily biodegradable) (OECD 301 D)
-------------	--

(Contd. on page 8)



Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 7)

<b>7722-84-1 hydrogen peroxide solution</b>		
Degradation	(Readily biodegradable)	
<b>107-41-5 2-methylpentane-2,4-diol</b>		
Degradation	(Readily biodegradable) (OECD 301 F)	
<b>12.3 Bioaccumulative potential</b>		
<b>Partition coefficient: nOctanol/water: [Log Kow]</b>		
1338-23-4	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane	2,04 (25°C)
75-91-2	tert-butyl hydroperoxide	0,85 (30 °C)
7722-84-1	hydrogen peroxide solution	-1,57 (20°C)
107-41-5	2-methylpentane-2,4-diol	< 1
110-05-4	di-tert-butyl peroxide	3,2 (22°C)
<b>12.4 Mobility in soil</b> No further relevant information available.		
<b>12.5 Results of PBT and vPvB assessment</b>		
<b>PBT:</b> The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.		
<b>vPvB:</b> The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.		
<b>12.6 Endocrine disrupting properties</b> The product does not contain substances with endocrine disrupting properties.		
<b>12.7 Other adverse effects</b>		
<b>Additional ecological information:</b>		
<b>General notes:</b> Must not reach sewage water or drainage ditch undiluted or unneutralised. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.		

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

**Recommendation**



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Waste disposal key:**

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

**Uncleaned packaging:**

**Recommendation:**

This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

<b>14.1 UN number or ID number</b>	
<b>ADR, IMDG, IATA</b>	UN3105
<b>14.2 UN proper shipping name</b>	
<b>ADR</b>	UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S))
<b>IMDG, IATA</b>	ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S))
<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
<b>Class</b>	5.2 (P1) Organic peroxides.
<b>Label</b>	5.2
<b>IMDG, IATA</b>	
<b>Class</b>	5.2 Organic peroxides.
<b>Label</b>	5.2

(Contd. on page 9)



Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 8)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>Stowage Category</b> · <b>Stowage Code</b> · <b>Segregation Code</b>	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>  · <b>Transport category</b> · <b>Tunnel restriction code</b>	125 ml Code: E0 Not permitted as Excepted Quantity 2 D
· <b>RID / GGVSEB:</b>	like ADR
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	125 ml Code: E0 Not permitted as Excepted Quantity

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances**
  - **ANNEX I** None of the ingredients is listed.
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

#### · **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

#### · **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

#### · **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

#### · **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

#### · **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

#### · **National regulations:**

- **Other regulations, limitations and prohibitive regulations**
- **Please note:** Take care of the respective local regulations.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases** H226 Flammable liquid and vapour.  
H242 Heating may cause a fire.

(Contd. on page 10)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 29.06.2023

Version: 4 (replaces version 3)

Revision: 26.06.2023

Trade name: **PEROXAN ME-50 LM4**

(Contd. of page 9)

H271 May cause fire or explosion; strong oxidiser.  
 H302 Harmful if swallowed.  
 H311 Toxic in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H330 Fatal if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H341 Suspected of causing genetic defects.  
 H351 Suspected of causing cancer.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:**

Environment protection / Security of labour

· **Contact:**

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Ox. Liq. 1: Oxidizing liquids – Category 1  
 Org. Perox. D: Organic peroxides – Type C/D  
 Org. Perox. F: Organic peroxides – Type E/F  
 Acute Tox. 4: Acute toxicity – Category 4  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 2: Acute toxicity – Category 2  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Muta. 2: Germ cell mutagenicity – Category 2  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**