

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PB-50 P · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire. Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

 Labelling according to Hazard pictograms

Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.



· Signal word

· Hazard-determining

components of labelling:

tert-butyl perbenzoate **Hazard statements** H242 Heating may cause a fire.

H315 Causes skin irritation.

Danger

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging. P264 Wash thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

(Contd. on page 2)

GB



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:

CAS: 614-45-9 tert-butyl perbenzoate

Org. Perox. C, H242; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412 EINECS: 210-382-2 Reg-No.: 01-2119513317-46

40-50%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment:

Mouth respiratory protective device. Do not inhale explosion gases or combustion gases.

· Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Pick up mechanically, collect in a suitable receptacle and dispose in accordance with government

regulations.

See Section 7 for information on safe handling. 6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 2)

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).


Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Dust can combine with air to form an explosive mixture.

Substance/product is oxidising when dry.

Product is not explosive. However, formation of explosive air/dust mixtures are possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage: Requirements to be met by Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight.

Protect from contamination.

· Recommended storage temperature (To maintain quality):

+10 +30 °C

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs 614-45-9 tert-butyl perbenzoate DNEL Longterm System 17.5 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 24.7 mg/m3 (Worker)

(Contd. on page 4)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 3)

· PNFCs

614-45-9 tert-butyl perbenzoate

PNEC Marinewater sed | 0.028 mg/kg sed dw 0.01 mg/l (AF 10) PNFC Freshwater 0.28 mg/kg sed dw PNEC Freshwater sed PNEC Soil 0.049 mg/kg soil dw 0.6 mg/l (AF 10) PNEC STP 0.00101 mg/l (AF 100) **PNEC Marinewater**

· Additional information: The lists valid during the making were used as basis.

 8.2 Exposure controls Appropriate engineering

controls No further data: see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter P2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information · Colour:

· Odour: · Odour threshold: · Melting point/freezing point:

Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit

· Lower: · Upper: · Flash point: white - yellowish Characteristic

Not determined. Not applicable. Not applicable. May cause fire.

Not determined. Not determined. Not applicable.

(Contd. on page 5)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 4)

· Decomposition temperature:	> +60 °C (SADT)
pH	Not applicable.
\/:it	

Viscosity:

Kinematic viscosity Not applicable. · Dynamic: Not applicable.

Solubility

· water: Undetermined · Partition coefficient n-octanol/water (log value) not determined Not applicable. Vapour pressure:

Density and/or relative density

· Density: Not determined. Relative density Not determined. Bulk density at 20 °C: 340 kg/m³ · Vapour density Not applicable.

· 9.2 Other information No further relevant information available.

· Appearance:

· Form: Powder · Important information on protection of health and environment,

and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/dust

Void

Void

mixtures are possible.

· Change in condition · Evaporation rate Not applicable.

· Information with regard to physical hazard classes · Explosives Flammable gases

· Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void

· Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void Other safety characteristics

Active oxygen 4.0 - 4.2 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous reactions

· 10.4 Conditions to avoid

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

(Contd. on page 6)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 5)

• Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity
 Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

614-45-9 tert-butyl perbenzoate

 Oral
 LD50
 4,838 mg/kg (rattus)

 Dermal
 LD50
 3,817 mg/kg (rattus)

 Inhalative
 LC100 4h
 4.9 mg/l (rattus)

 LC0 / 4h
 1.01 mg/l (rattus)

Skin corrosion/irritation Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability

Degree of elimination:

· Classification:

614-45-9 tert-butyl perbenzoate

Degradation (Readily biodegradable) (OECD 301 D)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

614-45-9 tert-butyl perbenzoate

• 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
 vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

· 12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

· Remark: Very toxic for fish

· Additional ecological information:

• **General notes:** Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable inert solid material to 10 %, the product must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

3 (25°C)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 6) · Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: I	ransport in	formation
---------------	-------------	-----------

· 14.1 UN number or ID number · ADR, IMDG, IATA UN3106

· 14.2 UN proper shipping name

· ADR UN3106 ORGANIC PEROXIDE TYPE D, SOLID (tert-BUTYL

PEROXYBENZOATE), ENVIRONMENTALLY HAZARDOUS ·IMDG

ORGANIC PEROXIDE TYPE D, SOLID (tert-BUTYL PEROXYBENZOATE), MARINE POLLUTANT

· IATA ORGANIC PEROXIDE TYPE D, SOLID (tert-BUTYL PEROXYBENZOATE)

· 14.3 Transport hazard class(es)

· ADR



· Class 5.2 (P1) Organic peroxides. 5.2

Label

· IMDG





· Class 5.2 Organic peroxides. Label

· IATA



5.2 Organic peroxides. Class · Label

5.2

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards: Product contains environmentally hazardous substances: tert-BUTYL **PEROXYBENZOATE**

· Marine pollutant: Yes

Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR):

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code): D · Stowage Category

· Stowage Code SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids · Segregation Code SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable

· Transport/Additional information:

 Limited quantities (LQ) 500 g Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category · Tunnel restriction code

· RID / GGVSEB: like ADR

· IMDG

· Limited quantities (LQ) 500 g

(Contd. on page 8)



(Contd. of page 7)

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier
- requirements 200 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations

· Please note: Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H242 Heating may cause a fire.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled. H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS: Environment protection / Security of labour

Tel: +49 2871 9902-0 · Contact: E-mail: mail@pergan.com

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

(Contd. on page 9)

Page 9/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PB-50 P

(Contd. of page 8)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Org. Perox. C: Organic peroxides – Type C/D
Org. Perox. D: Organic peroxides – Type C/D
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

·* Data compared to the previous version altered.

GB -