

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**

PEROXAN PK295 V-75
- **Trade name:**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
- **Application of the substance / the mixture**

Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:**

Environment protection / Security of labour
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:**



- Tel: +49 2871 9902-0

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.
Org. Perox. C H242 Heating may cause a fire.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS08
- **Signal word**

Danger
- **Hazard-determining components of labelling:**

Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide
- **Hazard statements**

H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234 Keep only in original packaging.
P243 Take action to prevent static discharges.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.
P410 Protect from sunlight.
P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
P420 Store separately.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
- **vPvB:**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

Trade name: **PEROXAN PK295 V-75**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 6731-36-8 EINECS: 229-782-3 Reg-No.: 01-2119735694-30	di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide Org. Perox. B, H241	70-80%
CAS: 93685-81-5 EINECS: 297-629-8 Reg-No.: 01-2119490725-29	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Alternative CAS number: 13475-82-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	20-25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:



Take care of personal protection for the first aider.

After inhalation:

Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.
Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

— GB —

Trade name: **PEROXAN PK295 V-75**

(Contd. of page 2)

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Handle with care. Avoid jolting, friction and impact.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
While using do not eat, drink or smoke.
Do not generate flames or sparks.
Keep product and emptied container away from heat and sources of ignition.
Avoid shock and friction.
Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.
Protect against electrostatic charges.
Prevent impact and friction.
Use explosion-proof apparatus / fittings and spark-proof tools.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
Protect from contamination.
Store under lock and key and with access restricted to technical experts or their assistants only.
- **Recommended storage temperature (To maintain quality):** max.: +30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.





· DNELs		
6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide		
Dermal	DNEL Longterm System	2 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	1.4 mg/m3 (Worker)

(Contd. on page 4)

GB

Trade name: PEROXAN PK295 V-75

(Contd. of page 3)

· PNECs	
6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide	
PNEC Marinewater sed	0.01 mg/kg sed dw (AF 500)
PNEC Freshwater sed	0.102 mg/kg sed dw (AF 50)
PNEC Soil	5.29 mg/kg soil dw (AF 10)
PNEC STP	100 mg/l (AF 10)
· Additional information:	The lists valid during the making were used as basis.
· 8.2 Exposure controls	
· Appropriate engineering controls	No further data; see section 7.
· Individual protection measures, such as personal protective equipment	
· General protective and hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.
· Respiratory protection:	Not necessary if room is well-ventilated.
	 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	Filter A2
· Hand protection	Only use chemical-protective gloves with CE-labelling of category III.
	 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	Protective gloves
· Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene
· Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· Eye/face protection	 Tightly sealed goggles
· Body protection:	 Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	53 °C
· Decomposition temperature:	+60 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	8 mPas
· Solubility	
· water:	Undetermined.

(Contd. on page 5)
GB

Trade name: **PEROXAN PK295 V-75**

(Contd. of page 4)

<ul style="list-style-type: none"> · Partition coefficient n-octanol/water (log value) · Vapour pressure: · Density and/or relative density · Density at 20 °C: · Relative density · Vapour density 	<ul style="list-style-type: none"> not determined Not determined. 0.88 g/cm³ Not determined. Not determined.
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: · Explosive properties: · Change in condition · Evaporation rate 	<ul style="list-style-type: none"> No further relevant information available. Fluid Product is not selfigniting. Risk of explosion by shock, friction, fire or other sources of ignition. Not determined.
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids · Organic peroxides · Corrosive to metals · Desensitised explosives · Other safety characteristics · Active oxygen 	<ul style="list-style-type: none"> Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void Void Heating may cause a fire. Void Void 7.8 - 8.1 %

SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> · 10.1 Reactivity · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: 	<ul style="list-style-type: none"> No further relevant information available. SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
<ul style="list-style-type: none"> · 10.3 Possibility of hazardous reactions · 10.4 Conditions to avoid · 10.5 Incompatible materials: · 10.6 Hazardous decomposition products: · Additional information: 	<ul style="list-style-type: none"> Self-accelerating decomposition at SADT. No further relevant information available. Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines). Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications. Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

<ul style="list-style-type: none"> · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity 	<ul style="list-style-type: none"> Based on available data, the classification criteria are not met.
---	---

(Contd. on page 6)

GB

Trade name: PEROXAN PK295 V-75


(Contd. of page 5)

· LD/LC50 values relevant for classification:	
6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide	
Oral	LD50 >2,000 mg/kg (rattus)
Dermal	LD50 >2,000 mg/kg (rattus)
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	
Oral	LD50 >5,000 mg/kg (rattus)
· Skin corrosion/irritation	Based on available data, the classification criteria are not met.
· Serious eye damage/irritation	Based on available data, the classification criteria are not met.
· Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.
· Carcinogenicity	Based on available data, the classification criteria are not met.
· Reproductive toxicity	Based on available data, the classification criteria are not met.
· STOT-single exposure	Based on available data, the classification criteria are not met.
· STOT-repeated exposure	Based on available data, the classification criteria are not met.
· Aspiration hazard	May be fatal if swallowed and enters airways.
· 11.2 Information on other hazards	
· Endocrine disrupting properties	
None of the ingredients is listed.	

SECTION 12: Ecological information

· 12.1 Toxicity	
· Aquatic toxicity:	
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	
EC50 / 48h	>0.04 mg/l (daphnia)
IC50 / 72h	>0.04 mg/l (algae)
· 12.2 Persistence and degradability	
· Degree of elimination:	
· Classification:	
6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide	
Degradation	(Evidence for inherent biodegradability.) (OECD 301 D)
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	
Degradation	(Not readily biodegradable)
· 12.4 Mobility in soil	No further relevant information available.
· 12.5 Results of PBT and vPvB assessment	
· PBT:	The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.
· 12.6 Endocrine disrupting properties	The product does not contain substances with endocrine disrupting properties.
· 12.7 Other adverse effects	No further relevant information available.
· Remark:	Very toxic for fish
· Additional ecological information:	
· General notes:	Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods	
· Recommendation	 After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations. Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· Waste disposal key:	Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

(Contd. on page 7)

GB



Trade name: **PEROXAN PK295 V-75**

(Contd. of page 6)

· Uncleaned packaging:

· Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3103
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE) ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE)
· 14.3 Transport hazard class(es) · ADR  · Class · Label	5.2 (P1) Organic peroxides. 5.2
· IMDG, IATA  · Class · Label	5.2 Organic peroxides. 5.2
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	25 ml Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	1 D
· RID / GGVSEB:	like ADR
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	25 ml Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

(Contd. on page 8)

GB

Trade name: **PEROXAN PK295 V-75**

(Contd. of page 7)

· Reportable explosives precursors	
None of the ingredients is listed.	
· Reportable poisons	
None of the ingredients is listed.	
· Directive 2012/18/EU	
· Qualifying quantity (tonnes) for the application of lower-tier requirements	50 t
· Qualifying quantity (tonnes) for the application of upper-tier requirements	200 t
· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II	
None of the ingredients is listed.	
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))	
None of the ingredients is listed.	
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS	
None of the ingredients is listed.	
· Regulation (EC) No 273/2004 on drug precursors	
None of the ingredients is listed.	
· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	
None of the ingredients is listed.	
· National regulations:	
· Other regulations, limitations and prohibitive regulations	
· Please note:	Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H226 Flammable liquid and vapour.
	H241 Heating may cause a fire or explosion.
	H304 May be fatal if swallowed and enters airways.
	H413 May cause long lasting harmful effects to aquatic life.
· Department issuing SDS:	Environment protection / Security of labour
· Contact:	Tel: +49 2871 9902-0
	E-mail: mail@pergan.com
· Abbreviations and acronyms:	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
	ICAO: International Civil Aviation Organisation
	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	DNEL: Derived No-Effect Level (UK REACH)
	PNEC: Predicted No-Effect Concentration (UK REACH)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	Flam. Liq. 3: Flammable liquids – Category 3
	Org. Perox. B: Organic peroxides – Type B
	Org. Perox. C: Organic peroxides – Type C/D
	Asp. Tox. 1: Aspiration hazard – Category 1
	Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· *** Data compared to the previous version altered.**