

Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN PK295 V-90

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

 \cdot 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from:

Environment protection / Security of labour Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. C H242 Heating may cause a fire.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



innal ...and Dan

· Signal word Danger · Hazard statements H242 Heatin

Hazard statements H242 Heating may cause a fire.

• **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P401 Store in accordance with local/regional/national/international regulations.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 6731-36-8 EINECS: 229-782-3 Reg-No.: 01-2119735694-30	di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide Org. Perox. B, H241	80-90%
EINECS: 297-629-8	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Alternative CAS number: 13475-82-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	5-10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

GB — (Contd. on page 2)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

(Contd. of page 1)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet. After skin contact: Immediately remove contaminated clothing.

Rinse opened eye for several minutes under running water. After eye contact:

After swallowing: If symptoms persist consult doctor.

 4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special

No further relevant information available.

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: · Additional information Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions. protective equipment and emergency procedures

Remove persons from danger area. Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Handle with care. Avoid jolting, friction and impact. Do not refill residue into storage receptacles.

Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

(Contd. on page 3)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

(Contd. of page 2)

While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by

storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in

one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about

storage conditions:

Protect from heat and direct sunlight.

Protect from contamination.

Store under lock and key and with access restricted to technical experts or their assistants only.

Recommended storage temperature (To maintain

quality):

max.: +30 °C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

·DNELs

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

DNEL Longterm System 2 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 1.4 mg/m3 (Worker)

·PNECs

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

PNEC Marinewater sed | 0.01 mg/kg sed dw (AF 500) PNEC Freshwater sed 0.102 mg/kg sed dw (AF 50) PNEC Soil 5.29 mg/kg soil dw (AF 10) PNEC STP 100 mg/l (AF 10)

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 4)



(Contd. of page 3)

Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

• Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

Tightly sealed goggles

· Body protection:

· Eye/face protection



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Colour:
Colouriess
Odour:
Characteristic
Odour threshold:
Not determined.
Melting point/freezing point:
Not applicable.

Boiling point or initial boiling point and boiling range
Flammability
Not applicable.

Lower and upper explosion limit

Lower:

Not determined.

Upper:

Flash point:

Decomposition temperature:

PH

Not determined.

> SADT

+60 °C (SADT)

Not determined.

Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Not determined.

Solubility

water: Undetermined.
 Partition coefficient n-octanol/water (log value) not determined.
 Vapour pressure: Not determined.

· Density and/or relative density

Pensity and/or relative density

Density:
Relative density
Not determined.
Vapour density
Not determined.

9.2 Other information

No further relevant information available.

· Appearance:

· Form:

Fluid

Important information on protection of health and environment,

and on safety.
Ignition temperature:

Product is not selfigniting.

Explosive properties:

Risk of explosion by shock, friction, fire or other sources of ignition.

Change in condition

Not determined.

· Evaporation rate

(Contd. on page 5)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

	(Contd. of page 4	.)
Information with regard to physical hazard classes		7
Explosives	Void	
Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable gases in		
contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Heating may cause a fire.	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause

decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

· 10.4 Conditions to avoid

· 10.5 Incompatible materials:

products:

Self-accelerating decomposition at SADT. No further relevant information available. Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

LD50 >2,000 mg/kg (rattus) Dermal LD50 >2,000 mg/kg (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

LD50 >5,000 mg/kg (rattus)

Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

Based on available data, the classification criteria are not met. sensitisation Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

(Contd. of page 5)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h |>0.04 mg/l (daphnia) IC50 / 72h >0.04 mg/l (alga)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

Degradation (Evidence for inherent biodegradability.) (OECD 301 D)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB:

· 12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Very toxic for fish · Remark:

· Additional ecological information:

Also poisonous for fish and plankton in water bodies. General notes:

Very toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e.g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

· Uncleaned packaging:

· IMDG, IATA

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3103

· 14.2 UN proper shipping name

UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE)

ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-

3,3,5-TRIMETHYLCYCLOHEXANE)

(Contd. on page 7)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR



5.2 (P1) Organic peroxides. · Label

· IMDG, IATA



Class 5.2 Organic peroxides.

· Label 5.2

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

D Stowage Category

· Stowage Code SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. · Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 25 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category · Tunnel restriction code D

· RID / GGVSEB: like ADR

· IMDG

· Limited quantities (LQ) 25 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements

Qualifying quantity (tonnes) for

the application of upper-tier requirements 200 t

(Contd. on page 8)



Printing date 05.01.2024 Version: 9 (replaces version 8) Revision: 16.02.2023

Trade name: PEROXAN PK295 V-90

(Contd. of page 7)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Other regulations, limitations and prohibitive regulations

· Please note: Take care of the respective local regulations

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.

H241 Heating may cause a fire or explosion. H304 May be fatal if swallowed and enters airways. H413 May cause long lasting harmful effects to aquatic life.

Environment protection / Security of labour Department issuing SDS:

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PBT. Persistent, Bloaccumulative and Voxic VPVB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids — Category 3 Org. Perox. B: Organic peroxides — Type B Org. Perox. C: Organic peroxides — Type C/D

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· * Data compared to the previous version altered.

GB -