

Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PMB-Paste 50 SI · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number:

- Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

H242 Heating may cause a fire. Org. Perox. D H400 Very toxic to aquatic life. Aquatic Acute 1

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining

components of labelling: **Hazard statements**

bis(4-methylbenzoyl)peroxide H242 Heating may cause a fire.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P234 Keep only in original packaging.

P240 Ground and bond container and receiving equipment.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

Protect from sunlight. P410

P411+F 235 Store at temperatures not exceeding +25°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PRT· The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components: CAS: 895-85-2 49-52% bis(4-methylbenzoyl)peroxide ELINCS: 407-950-9 Org. Perox. B, H241; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Index number: 617-015-00-9 Reg-No.: 01-0000015733-70

· Additional information: For the wording of the listed hazard phrases refer to section 16.

GB



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 1)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet.

 After skin contact: Immediately remove contaminated clothing.

Rinse opened eye for several minutes under running water. After eye contact: After swallowing: If symptoms persist consult doctor.

 4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: · Additional information Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area. Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities. Handle with care. Avoid jolting, friction and impact.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

(Contd. on page 3)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 2)

While using do not eat, drink or smoke. Avoid shock and friction.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Prevent impact and friction.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground. Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about

storage conditions:

Protect from heat and direct sunlight.

Protect from contamination.

Store under lock and key and with access restricted to technical experts or their assistants only.

Recommended storage

temperature (To maintain quality):

+5 +25 °C Storage class: 5.2

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· DNFI s

895-85-2 bis(4-methylbenzoyl)peroxide

Dermal DNEL Longterm System 33.33 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 23.49 mg/m3 (Worker)

· PNECs

895-85-2 bis(4-methylbenzoyl)peroxide

PNEC Marinewater sed | 0.061 mg/kg sed dw (-) 0.064 mg/l (AF 50) PNEC Freshwater 0.61 mg/kg sed dw (-) PNEC Freshwater sed PNEC Soil 0.084 mg/kg soil dw (-) PNEC STP 497 mg/l (AF 1) **PNEC Marinewater** 0.0064 mg/l (AF 500)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 4)



(Contd. of page 3)

Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

White

Characteristic

Not applicable.

Not applicable.

Not applicable.

Not determined.

Not determined.

Not determined.

Not determined.

Not determined.

Undetermined.

not determined Not determined.

Not determined.

> SADT +80 °C (SADT)

Not determined.

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour:

· Odour: · Odour threshold:

· Melting point/freezing point:

Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit · Lower:

· Upper: · Flash point:

Decomposition temperature:

· pH

Viscosity:

Kinematic viscosity

· Dynamic:

Solubility

· water:

· Partition coefficient n-octanol/water (log value)

· Vapour pressure:

Relative density

Density and/or relative density Density at 20 °C:

· Vapour density

1.1 g/cm³ Not determined. Not determined.

· 9.2 Other information

Appearance:

Pasty

· Important information on protection of health and environment,

and on safety.

Ignition temperature:

Explosive properties:

Product is not selfigniting.

Product does not present an explosion hazard.

· Change in condition **Evaporation rate**

Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

(Contd. on page 5)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 4) · Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void Organic peroxides Heating may cause a fire. Corrosive to metals Void · Desensitised explosives Void Other safety characteristics

2.9 - 3.1 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity

Active oxygen

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

· 10.4 Conditions to avoid

· 10.5 Incompatible materials:

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

Self-accelerating decomposition at SADT.

No further relevant information available.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

895-85-2 bis(4-methylbenzoyl)peroxide

LD50 >2,000 mg/kg (rattus) Dermal LD50 >2,000 mg/kg (rattus)

Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Carcinogenicity

· Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 5)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

895-85-2 bis(4-methylbenzoyl)peroxide

EC50 / 72h | 74 mg/l (pseudokirchneriella subcapitata)

LC50 / 96h 64 mg/l (oryzias latipes) EC50 / 48h | 42 mg/l (daphnia)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

895-85-2 bis(4-methylbenzoyl)peroxide

Degradation (Readily biodegradable) (OECD 301 D)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

895-85-2 bis(4-methylbenzoyl)peroxide

4,7 (20°C)

· 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects · Remark:

Very toxic for fish

· Additional ecological information:

· General notes: Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

· 14.1 UN number or ID number

· Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· ADR, IMDG, IATA UN3106

14.2 UN proper shipping name · ADR

UN3106 ORGANIC PEROXIDE TYPE D, SOLID (Di-(4-methylbenzoyl) peroxide), ENVIRONMENTALLY HAZARDOUS

·IMDG ORGANIC PEROXIDE TYPE D, SOLID (Di-(4-methylbenzoyl) peroxide),

MARINE POLLUTANT ORGANIC PEROXIDE TYPE D, SOLID (Di-(4-methylbenzoyl) peroxide) ·IATA

(Contd. on page 7)



Version: 6 (replaces version 5) Printing date 04.04.2024 Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR





Class 5.2 (P1) Organic peroxides. · Label

· IMDG





Class 5.2 Organic peroxides. · Label

5.2

· IATA



Class 5.2 Organic peroxides.

Label 5.2

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

500 g · Limited quantities (LQ) Code: E0 Excepted quantities (EQ)

Not permitted as Excepted Quantity

· Transport category D · Tunnel restriction code

· RID / GGVSEB: like ADR

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements

50 t

(Contd. on page 8)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PMB-Paste 50 SI

(Contd. of page 7)

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Other regulations, limitations and prohibitive regulations

· Please note: Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H241 Heating may cause a fire or explosion.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International · Abbreviations and acronyms:

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. B: Organic peroxides – Type B Org. Perox. D: Organic peroxides – Type C/D

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

 * Data compared to the previous version altered.

GB -