

Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PO-70 · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Org. Perox. C H242 Heating may cause a fire.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

H304 May be fatal if swallowed and enters airways. Asp. Tox. 1

H400 Very toxic to aquatic life. Aquatic Acute 1

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Hazard pictograms

Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.









· Signal word Danger

· Hazard-determining

components of labelling:

tert-butyl 2-ethylperoxyhexanoate

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

· Hazard statements H226 Flammable liquid and vapour. Heating may cause a fire. H242

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines). P234 Keep only in original packaging.

P243 Take action to prevent static discharges. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up. P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +20°C. Keep cool.

P420 Store separately

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

· Additional information: Restricted to professional users. (Contd. of page 1)

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture: consisting of the following components.

| Dangerous components: | | |
|---------------------------|--|--------|
| CAS: 3006-82-4 | tert-butyl 2-ethylperoxyhexanoate | 60-70% |
| EINECS: 221-110-7 | Org. Perox. C, H242; Repr. 1B, H360F; Aquatic Chronic 2, H411; Skin Sens. 1, H317 | |
| Reg-No.: 01-2119498310-40 | | |
| CAS: 93685-81-5 | Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated | 25-30% |
| EINECS: 297-629-8 | Alternative CAS number: 13475-82-6 | |
| Reg-No.: 01-2119490725-29 | Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413 | |

 Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

No further relevant information available.

· After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters · Protective equipment:

· Additional information

Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away

· 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 2)

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

 Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination. Storage in a collecting room is required.

· Recommended storage temperature (To maintain

quality): max.: +15 °C Control temperature: +20 °C **Emergency temperature:** +25 °C

7.3 Specific end use(s) No further relevant information available.

GB



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· DNELs

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Dermal DNEL Longterm System 5.6 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 9.8 mg/m3 (Worker)

· PNECs

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

PNEC Marinewater sed | 0.0622 mg/kg sed dw **PNEC Freshwater** 0.002 mg/l (AF 50) PNEC Freshwater sed 0.622 mg/kg sed dw PNEC STP 0.64 mg/I (AF 100) **PNEC Marinewater** 0 mg/l (AF 500)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Not necessary if room is well-ventilated. · Respiratory protection:

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information

Colour: Colourless · Odour: Characteristic

(Contd. on page 5)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 4)

| | (Contd. of page 4) |
|---|--|
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Not applicable. |
| Boiling point or initial boiling point and boiling range | Not applicable. |
| · Flammability | Not applicable. |
| Lower and upper explosion limit | |
| · Lower: | Not determined. |
| · Upper: | Not determined. |
| · Flash point: | > SADT |
| Decomposition temperature: | +35 °C (SADT) |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| Solubility | |
| · water: | Undetermined. |
| Partition coefficient n-octanol/water (log value) | not determined |
| Vapour pressure: | Not determined. |
| Density and/or relative density | |
| Density at 20 °C: | 0.85 g/cm ³ |
| Relative density | Not determined. |
| · Vapour density | Not determined. |
| 9.2 Other information | No further relevant information available. |
| · Appearance: | No fartificition followalt information available. |
| · Form: | Fluid |
| Important information on protection of health and environment | |
| and on safety. | , |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour |
| | mixtures are possible. |
| · Change in condition | · |
| · Evaporation rate | Not determined. |
| Information with regard to physical hazard classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Flammable liquid and vapour. |
| Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flammable gases in | |
| contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Heating may cause a fire. |
| Corrosive to metals | Void |
| · Desensitised explosives | Void |
| | |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-

accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous reactions

Self-accelerating decomposition at SADT. · 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 5) · 10.5 Incompatible materials: Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

· Additional information:

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification: 3006-82-4 tert-butyl 2-ethylperoxyhexanoate

>10,000 mg/kg (rattus) Oral LD50

14,142-20,000 mg/kg (cuniculosus) Dermal LD50

Inhalative LC50 / 4h 42.2 mg/l (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Oral >5,000 mg/kg (rattus)

Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity May damage fertility.

 STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard May be fatal if swallowed and enters airways.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

EC50 / 72h 0.44 mg/l (alga (Süsswasser)) LC50 / 96h 8.66 mg/l (poecilia reticulata)

EC50 / 48h | 7.5 mg/l (daphnia)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h > 0.04 mg/l (daphnia) IC50 / 72h | >0.04 mg/l (alga)

12.2 Persistence and degradability

· Degree of elimination:

· Classification:

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Degradation (Readily biodegradable) (OECD 301 D)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

4,79 (20°C)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH, annex XIII.

· 12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

(Contd. on page 7)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 6)

· Remark: Toxic for fish

· Additional ecological information:

· General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

system.

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

SW3 Shall be transported under temperature control.

SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.

Must not be disposed together with household garbage. Do not allow product to reach sewage

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

| · 14.1 UN number or ID number · ADR, IMDG | UN3113 |
|--|---|
| · 14.2 UN proper shipping name · ADR | UN3113 ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), ENVIRONMENTALLY HAZARDOUS |
| · IMDG | ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED |

(tert-BUTYLPEROXY-2-ETHYLHEXANOATE), MARINE POLLUTANT

· 14.3 Transport hazard class(es)

· ADR





· Class 5.2 (P2) Organic peroxides. · Label

· IMDG





· Segregation Code

| · Class | 5.2 Organic peroxides. |
|---|--|
| · Label | 5.2 |
| | J.2 |
| · IATA | |
| · Class | X |
| · Label | X |
| Label | ^ |
| 14.4 Packing group | |
| ADR, IMDG | Void |
| | Void |
| · 14.5 Environmental hazards: | Product contains environmentally hazardous substances: tert- |
| | BUTYLPEROXY-2-ETHYLHEXÁNOATE |
| · Marine pollutant: | Symbol (fish and tree) |
| Special marking (ADR): | Symbol (fish and tree) |
| Special marking (ADR). | Symbol (lish and tree) |
| · 14.6 Special precautions for user | Warning: Organic peroxides. |
| · Hazard identification number (Kemler code): | _ |
| Stowage Category | D |
| | _ |
| · Stowage Code | SW1 Protected from sources of heat. |

(Contd. on page 8)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 7)

| 14.7 Maritime transport in bulk according to IMO ins | struments Not applicable. |
|--|---------------------------|
| · Transport/Additional information: | |

· ADR

· Limited quantities (LQ)

0 Excepted quantities (EQ)

Code: E0 Not permitted as Excepted Quantity

 Transport category · Tunnel restriction code D

· RID / GGVSEB: no admission

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

·IATA

· Remarks: no admission

· Control temperature: +20 °C · Emergency temperature: +25 °C

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for

the application of lower-tier

requirements

Qualifying quantity (tonnes) for the application of upper-tier

requirements

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex
- None of the ingredients is listed.
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Please note: Take care of the respective local regulations.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)



Printing date 29.12.2023 Version: 16 (replaces version 15) Revision: 21.12.2023

Trade name: PEROXAN PO-70

(Contd. of page 8)

· Relevant phrases H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Environment protection / Security of labour

Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PBT: Persistent, Bioaccumulative and Toxic
vPVB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. C: Organic peroxides – Type C/D
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

* Data compared to the previous version altered.

GB —