



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PERGAQUICK C24 AX
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Accelerator for polymerisation / crosslinking  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:**  
Competent person:  
\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com  
Security of labour
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
Repr. 1B	H360Fd	May damage fertility. Suspected of damaging the unborn child.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate  
cobalt(II) 2-ethylhexanoate  
N,N-dimethylaniline
- **Hazard statements**

H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H360Fd May damage fertility. Suspected of damaging the unborn child.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P261 Avoid breathing mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P281 Use personal protective equipment as required.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P391 Collect spillage.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:** Restricted to professional users.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 1)

· <b>Determination of endocrine-disrupting properties</b>	
128-37-0 Butylated hydroxytoluene	List II

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

##### · **Dangerous components:**

CAS: 6846-50-0 EINECS: 229-934-9 Reg-No.: 01-2119451093-47	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2, H361d; Aquatic Chronic 3, H412	60-70%
CAS: 136-52-7 EINECS: 205-250-6 Reg-No.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate Repr. 1B, H360Fd; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-20%
CAS: 121-69-7 EINECS: 204-493-5 Index number: 612-016-00-0 Reg-No.: 01-2119950342-44	N,N-dimethylaniline Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Carc. 2, H351; Aquatic Chronic 2, H411	5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg-No.: 01-2119488216-32	xylene Consisting of: 1330-20-7 xylene; 100-41-4 ethylbenzene; 108-88-3 toluene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	5-10%
CAS: 128-37-0 EINECS: 204-881-4 Reg-No.: 01-2119555270-46 01-2119565113-46	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0,1-1%
CAS: 68084-48-0 EINECS: 268-439-2 Reg-No.: 01-2120784744-41	Copper(2+) neodecanoate Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302	0,1-1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information:**



Take care of personal protection for the first aider.

##### · **After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.

##### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.

##### · **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

##### · **After swallowing:**

If symptoms persist consult doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

#### · 5.3 Advice for firefighters

##### · **Protective equipment:**

Do not inhale explosion gases or combustion gases.

##### · **Additional information**

Self-protection first!

### SECTION 6: Accidental release measures


#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 2)

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Ensure good ventilation/exhaustion at the workplace.
  - Open and handle receptacle with care.
  - Prevent formation of aerosols.
  - Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
  - Use only in well ventilated areas.
  - Before break and at the end of work hands should be thoroughly washed.
  - Avoid contact with skin and eyes.
  - While using do not eat, drink or smoke.
- **Information about fire - and explosion protection:**
  - Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
  - Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:**
  - Prevent any seepage into the ground.
  - Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:**
  - Store away from peroxide.
  - Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:**
  - Keep container tightly sealed.
  - Store under lock and key and out of the reach of children.
  - Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):**
  - +5 .... +30 °C
- **Storage class:**
  - 6.1 C
- **7.3 Specific end use(s)**
  - No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**121-69-7 N,N-dimethylaniline**

OEL (Ireland)	Short-term value: 50 mg/m <sup>3</sup> , 10 ppm Long-term value: 25 mg/m <sup>3</sup> , 5 ppm Sk
---------------	--

WEL (Great Britain)	Short-term value: 50 mg/m <sup>3</sup> , 10 ppm Long-term value: 25 mg/m <sup>3</sup> , 5 ppm Sk
---------------------	--

**1330-20-7 xylene**

OEL (Ireland)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Sk, IOELV
---------------	---

IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
------------	--

WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
---------------------	--

(Contd. on page 4)

**Trade name: PERGAQUICK C24 AX**

(Contd. of page 3)





<b>128-37-0 Butylated hydroxytoluene</b>	
OEL (Ireland)	Long-term value: 2 mg/m <sup>3</sup>
WEL (Great Britain)	Long-term value: 10 mg/m <sup>3</sup>
<b>· DNELs</b>	
<b>6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate</b>	
Dermal	DNEL Longterm System 5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System 17,62 mg/m <sup>3</sup> (Worker)
<b>136-52-7 cobalt(II) 2-ethylhexanoate</b>	
Inhalative	DNEL Longterm Local 0,2351 mg/m <sup>3</sup> (Worker)
<b>121-69-7 N,N-dimethylaniline</b>	
Dermal	DNEL Longterm System 2,988 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System 3,406 mg/m <sup>3</sup> (Worker)
<b>1330-20-7 xylene</b>	
Dermal	DNEL Longterm System 212 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System 221 mg/m <sup>3</sup> (Worker)
<b>128-37-0 Butylated hydroxytoluene</b>	
Dermal	DNEL Longterm System 0,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System 1,76 mg/m <sup>3</sup> (Worker)
<b>· PNECs</b>	
<b>6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate</b>	
PNEC Marinewater sed	0,529 mg/kg sed dw (-)
PNEC Freshwater	0,014 mg/l (AF 50)
PNEC Freshwater sed	5,29 mg/kg sed dw
PNEC Soil	1,05 mg/kg soil dw
PNEC STP	3 mg/l (AF 10)
PNEC Marinewater	0,001 mg/l (AF 500)
<b>136-52-7 cobalt(II) 2-ethylhexanoate</b>	
PNEC Marinewater sed	69,8 mg/kg sed dw (AF 10)
PNEC Freshwater	0,0006 mg/l (-)
PNEC Freshwater sed	53,8 mg/kg sed dw (AF 10)
PNEC Soil	10,9 mg/kg soil dw (AF 2)
PNEC STP	0,37 mg/l (AF 10)
PNEC Marinewater	0,00236 mg/l (-)
<b>121-69-7 N,N-dimethylaniline</b>	
PNEC Marinewater sed	4,942 mg/kg sed dw (-)
PNEC Freshwater	0,023 mg/l (AF 100)
PNEC Freshwater sed	4,942 mg/kg sed dw (-)
PNEC Soil	1,906 mg/kg soil dw (-)
PNEC STP	5,948 mg/l (AF 10)
PNEC Marinewater	0,002 mg/l (AF 1.000)
<b>1330-20-7 xylene</b>	
PNEC Marinewater sed	12,46 mg/kg sed dw
PNEC Freshwater	0,327 mg/l (-)
PNEC Freshwater sed	12,46 mg/kg sed dw
PNEC Soil	2,31 mg/kg soil dw
PNEC STP	6,58 mg/l
PNEC Marinewater	0,327 mg/l
<b>128-37-0 Butylated hydroxytoluene</b>	
PNEC Marinewater sed	0,046 mg/kg sed dw (-)
PNEC Freshwater	0,000199 mg/l (AF 1.000)
PNEC Seawater	0,00002 mg/l (AF 10.000)
PNEC Freshwater sed	0,458 mg/kg sed dw (-)
PNEC Soil	0,054 mg/kg soil dw (-)
PNEC STP	0,017 mg/l (AF 100)

(Contd. on page 5)

IE

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 4)

· <b>Ingredients with biological limit values:</b>	
<b>1330-20-7 xylene</b>	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
· <b>Additional information:</b>	The lists valid during the making were used as basis.
· <b>8.2 Exposure controls</b>	
· <b>Appropriate engineering controls</b>	No further data; see section 7.
· <b>Individual protection measures, such as personal protective equipment</b>	
· <b>General protective and hygienic measures:</b>	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.
· <b>Respiratory protection:</b>	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	 Filter A2
· <b>Hand protection</b>	Only use chemical-protective gloves with CE-labelling of category III.
	 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	Protective gloves
· <b>Material of gloves</b>	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene
· <b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· <b>Eye/face protection</b>	 Tightly sealed goggles
· <b>Body protection:</b>	 Protective work clothing

\* **SECTION 9: Physical and chemical properties**

· <b>9.1 Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Colour:</b>	Violet
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable.
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.
· <b>Flash point:</b>	67 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.

(Contd. on page 6)

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· <b>Dynamic at 20 °C:</b> 6 mPas</li> <li>· <b>Solubility</b></li> <li>· <b>water:</b> Undetermined.</li> <li>· <b>Partition coefficient n-octanol/water (log value)</b> not determined</li> <li>· <b>Vapour pressure:</b> Not determined.</li> <li>· <b>Density and/or relative density</b> Not determined.</li> <li>· <b>Density at 20 °C:</b> 0,956 g/cm<sup>3</sup></li> <li>· <b>Relative density</b> Not determined.</li> <li>· <b>Vapour density</b> Not determined.</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b></li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b> Fluid</li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b> Product is not selfigniting.</li> <li>· <b>Explosive properties:</b> Product does not present an explosion hazard.</li> <li>· <b>Change in condition</b></li> <li>· <b>Evaporation rate</b> Not determined.</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b> Void</li> <li>· <b>Flammable gases</b> Void</li> <li>· <b>Aerosols</b> Void</li> <li>· <b>Oxidising gases</b> Void</li> <li>· <b>Gases under pressure</b> Void</li> <li>· <b>Flammable liquids</b> Void</li> <li>· <b>Flammable solids</b> Void</li> <li>· <b>Self-reactive substances and mixtures</b> Void</li> <li>· <b>Pyrophoric liquids</b> Void</li> <li>· <b>Pyrophoric solids</b> Void</li> <li>· <b>Self-heating substances and mixtures</b> Void</li> <li>· <b>Substances and mixtures, which emit flammable gases in contact with water</b> Void</li> <li>· <b>Oxidising liquids</b> Void</li> <li>· <b>Oxidising solids</b> Void</li> <li>· <b>Organic peroxides</b> Void</li> <li>· <b>Corrosive to metals</b> Void</li> <li>· <b>Desensitised explosives</b> Void</li> </ul>	

### SECTION 10: Stability and reactivity

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	No hazardous decomposition products if used and stored according to specifications.
· <b>Additional information:</b>	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

### SECTION 11: Toxicological information

· <b>11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008</b>	
· <b>Acute toxicity</b>	Based on available data, the classification criteria are not met.

· <b>LD/LC50 values relevant for classification:</b>		
<b>6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate</b>		
Oral	LD50	3.200 mg/kg (rattus)
Dermal	LD50	18.900 mg/kg (caviinae)
<b>136-52-7 cobalt(II) 2-ethylhexanoate</b>		
Oral	LD50	3.129 mg/kg (rattus)
<b>121-69-7 N,N-dimethylaniline</b>		
Oral	LD50	951 mg/kg (rattus)

(Contd. on page 7)

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 6)

Dermal	LD50	1.690 mg/kg (cuniculosus)
<b>1330-20-7 xylene</b>		
Oral	LD50	3.520 mg/kg (rattus)
Dermal	LD50	12.126 mg/kg (cuniculosus)
<b>128-37-0 Butylated hydroxytoluene</b>		
Oral	LD50	>2.000 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (cuniculosus)
· Skin corrosion/irritation	Based on available data, the classification criteria are not met.	
· Serious eye damage/irritation	Causes serious eye irritation.	
· Respiratory or skin sensitisation	May cause an allergic skin reaction.	
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
· Carcinogenicity	Suspected of causing cancer.	
· Reproductive toxicity	May damage fertility. Suspected of damaging the unborn child.	
· STOT-single exposure	Based on available data, the classification criteria are not met.	
· STOT-repeated exposure	Based on available data, the classification criteria are not met.	
· Aspiration hazard	Based on available data, the classification criteria are not met.	
<b>11.2 Information on other hazards</b>		
· Endocrine disrupting properties		
128-37-0	Butylated hydroxytoluene	List II

## SECTION 12: Ecological information

### 12.1 Toxicity

#### · Aquatic toxicity:

##### 136-52-7 cobalt(II) 2-ethylhexanoate

LC50 / 96h | 1,5 mg/l (piscis)

##### 121-69-7 N,N-dimethylaniline

EC50 / 72h | 22 mg/l (alga)

LC50 / 96h | 53,7 mg/l (piscis)

##### 128-37-0 Butylated hydroxytoluene

LC0 /96h | &gt;0,57 mg/l (piscis)

EC50 / 48h | 0,61 mg/l (daphnia magna)

IC50 / 72h | &gt;0,4 mg/l (alga)

### 12.2 Persistence and degradability

#### · Degree of elimination:

#### · Classification:

##### 6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Degradation | (Readily biodegradable, failing 10-d wind) (OECD 301 B)

##### 121-69-7 N,N-dimethylaniline

Degradation | (Readily biodegradable)

##### 1330-20-7 xylene

Degradation | (Readily biodegradable) (OECD 301 F)

##### 128-37-0 Butylated hydroxytoluene

Degradation | (Not readily biodegradable)

### 12.3 Bioaccumulative potential

#### · Partition coefficient: nOctanol/water: [Log Kow]

121-69-7	N,N-dimethylaniline	1,17 (38°C)
1330-20-7	xylene	3,16 (20°C)
128-37-0	Butylated hydroxytoluene	5,1
67-56-1	methanol	-0,77 (20°C)

#### · Bioconcentration factor (BCF)

##### 6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

BCF | 183-194 (piscis)

##### 1330-20-7 xylene

BCF | 25,9

##### 128-37-0 Butylated hydroxytoluene

BCF | 1.277


(Contd. on page 8)

Trade name: **PERGAQUICK C24 AX**

(Contd. of page 7)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
  - **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
  - **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:** Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

· <b>14.1 UN number or ID number</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.2 UN proper shipping name</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, IMDG, IATA</b>	
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	No dangerous good according the regulation of transport.
· <b>ADR</b>	
· <b>RID / GGVSEB:</b>	like ADR

### \* SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances**
  - **ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

(Contd. on page 9)



Trade name: **PERGAQUICK C24 AX**

(Contd. of page 8)

· <b>Annex II - REPORTABLE EXPLOSIVES PRECURSORS</b>
None of the ingredients is listed.
· <b>Regulation (EC) No 273/2004 on drug precursors</b>
None of the ingredients is listed.
· <b>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</b>
None of the ingredients is listed.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.  
 H301 Toxic if swallowed.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H311 Toxic in contact with skin.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.  
 H360Fd May damage fertility. Suspected of damaging the unborn child.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

· **Contact:**

Tel: +49 2871 9902-0  
 E-mail: mail@pergan.com

· **Version number of previous version:**

11

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 2: Carcinogenicity – Category 2  
 Repr. 1B: Reproductive toxicity – Category 1B  
 Repr. 2: Reproductive toxicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**