

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN AHP · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Org. Perox. E H242 Heating may cause a fire. Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



· Signal word Danger

· Hazard-determining

components of labelling: tert-pentyl hydroperoxide

2-methylbutan-2-ol

hydrogen peroxide solution

Flammable liquid and vapour. · Hazard statements H226

H242 Heating may cause a fire.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

H314 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 · Precautionary statements

smokina. P220

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).

Keep only in original packaging. P234

Take action to prevent static discharges. P243

P264 Wash thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up. P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

(Contd. on page 2)



(Contd. of page 1)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

· 2.3 Other hazards · Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Determination of endocrine-

disrupting properties The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· PBT:

Dangerous components:		00.000/
CAS: 3425-61-4 EINECS: 222-321-7	tert-pentyl hydroperoxide	80-90%
	Org. Perox. E, H242; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 75-85-4	2-methylbutan-2-ol	1-2,5%
EINECS: 200-908-9 Index number: 603-007-00-2	Flam. Liq. 2, H225; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 3052-70-8	2,2-bis (t-amyl peroxy) propane	0,1-1%
	Org. Perox. C, H242	_
CAS: 7722-84-1	hydrogen peroxide solution	0,1-1%
EINECS: 231-765-0 Index number: 008-003-00-9	Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412	
Reg-No.: 01-2119485845-22	Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 %	
_	Skin Corr. 1B; H314: 50 % ≤ C < 70 %	
	Skin Irrit. 2; H315: 35 % ≤ C < 50 %	
	Eye Dam. 1; H318: C ≥ 8 %	
	Eye Irrit. 2; H319: 5 % ≤ C < 8 %	
	STOT SE 3; H335: C ≥ 35 %	
	Ox. Liq. 1; H271: C ≥ 70 %	
	Ox. Liq. 2; H272: 50 % ≤ C < 70 %	

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

persist.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delaved

4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

(Contd. on page 3)



(Contd. of page 2)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

5.3 Advice for firefighters• **Protective equipment:**Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

• Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage: Pay attention to the special requirements of your local autorithies for storing dangerous goods.

(Contd. on page 4)



(Contd. of page 3)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in

one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about

storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination.

Store under lock and key and out of the reach of children.

· Recommended storage temperature (To maintain

quality): +5 +30 °C Storage class:

5.2

· 7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values the	at require moni	itoring at the	workplace:
-----------------------------------	-----------------	----------------	------------

7722-84-1 hydrogen peroxide solution

OEL (Ireland) Short-term value: 3 mg/m³, 2 ppm

Long-term value: 1,5 mg/m³, 1 ppm

WEL (Great Britain) Short-term value: 2,8 mg/m³, 2 ppm Long-term value: 1,4 mg/m³, 1 ppm

7722-84-1 hydrogen peroxide solution

Inhalative DNEL Longterm Local 1,4 mg/m3 (Worker)

· PNECs

7722-84-1 hydrogen peroxide solution

PNEC Marinewater sed 0,047 mg/kg sed dw **PNEC Freshwater** 0,013 mg/l (AF 50) PNEC Freshwater sed 0,047 mg/kg sed dw PNEC Soil 0,002 mg/kg soil dw PNEC STP 4,66 mg/l (AF 100) **PNEC Marinewater** 0,013 mg/l (AF 50)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

The usual precautionary measures are to be adhered to when handling chemicals. hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

(Contd. on page 5)



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

(Contd. of page 4)

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

Not applicable.

Not determined

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

· Eye/face protection

Tightly sealed goggles

· Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Boiling point or initial boiling point and boiling range
 Colourless
 Characteristic
 Not determined.
 Not applicable.
 Not applicable.

Flammability

· Lower and upper explosion limit · Lower:

· Upper: Not determined.
· Flash point: 41 °C

Decomposition temperature: +80 °C (SADT)

• pH Not determined.

Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 6 mPas

Solubility water:

water: Undetermined.
 Partition coefficient n-octanol/water (log value) not determined
 Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 0,91 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

• **9.2 Other information** No further relevant information available.

Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour

Change in condition mixtures are possible.

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void
Void

Gases under pressure
 Flammable liquids
 Flammable liquid and vapour.

Flammable solids Void
Self-reactive substances and mixtures Void
Pyrophoric liquids Void
Pyrophoric solids Void
Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable gases in contact with water V

Void

(Contd. on page 6)



(Contd. of page 5)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

· Oxidising liquids Void Oxidising solids Void

Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void Other safety characteristics

Active oxygen 12,0 - 13,5 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating

decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT.

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if swallowed, in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

75-85-4 2-methylbutan-2-ol

Oral LD50 1.000 mg/kg (rattus)

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin

Germ cell mutagenicity

Reproductive toxicity

sensitisation

Carcinogenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· STOT-single exposure STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

 Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability

Degree of elimination:

· Classification:

3425-61-4 tert-pentyl hydroperoxide

Degradation (Not readily biodegradable) (OECD 301 D)

7722-84-1 hydrogen peroxide solution

Degradation (Readily biodegradable)

(Contd. on page 7)



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

· 12.3 Bioaccumulative potential

(Contd. of page 6)

Partition coefficient: nOctanol/water: [Log Kow] 7722-84-1 hydrogen peroxide solution -1,57 (20°C) 10508-09-5 di-tert-pentyl peroxide 4,7 (25 °C)

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties. 12.7 Other adverse effects No further relevant information available.

· Additional ecological information:

· General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

system.

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

· Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

4441111 1 15 1	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3107
14.2 UN proper shipping name	
· ADR	UN3107 ORGANIC PEROXIDE TYPE E, LIQUID (tert-AMYL
	HYDROPEROXIDE)
· IMDG, IATA	ORGANIC PEROXIDE TYPE E, LIQUID (tert-AMYL HYDROPEROXIDE)

D

· 14.3 Transport hazard class(es)

· ADR



· Class 5.2 (P1) Organic peroxides. Label 5.2

IMDG, IATA



· Class 5.2 Organic peroxides Label 5.2

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards: · Marine pollutant: No

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

Stowage Category

· Stowage Code SW1 Protected from sources of heat.

(Contd. on page 8)



(Contd. of page 7)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

Segregation Code SG35 Stow "separated from" SGG1-acids

SG36 Stow "separated from" SGG18-alkalis.

SG72 See 7.2.6.3.2.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 125 ml · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

7. Transport category

Transport category
Tunnel restriction code

· RID / GGVSEB: like ADR

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E0

Not permitted as Excepted Quantity

• Additional provisions for organic peroxides of Class 5.2 "Carriage in accordance with ADR 2.2.52.1.8."

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

• Seveso category P6b SELF-REĂCTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· Qualifying quantity (tonnes) for the application of lower-tier

requirements 50 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

Ш

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug

precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases H225 Highly flammable liquid and vapour.

H242 Heating may cause a fire.

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser. H302 Harmful if swallowed. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation.

(Contd. on page 9)



(Contd. of page 8)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 10.02.2023

Trade name: PEROXAN AHP

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

Environment protection / Security of labour Tel: +49 2871 9902-0

· Contact:

E-mail: mail@pergan.com · Version number of previous

version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Soniia (divisions of the American Chemical Chemical Control Contr

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
VPVB: very Persistent and very Bioaccumulative vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Ox. Liq. 1: Oxidizing liquids – Category 1
Org. Perox. C: Organic peroxides – Type C/D
Org. Perox. E: Organic peroxides – Type E/F
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.