


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN BU M2
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- Flam. Liq. 3 H226 Flammable liquid and vapour.
- Org. Perox. E H242 Heating may cause a fire.
- Skin Irrit. 2 H315 Causes skin irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** 
GHS02 GHS07 GHS08 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:** Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide
tert-butyl alpha, alpha-dimethylbenzyl peroxide
- **Hazard statements**
H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
- P234 Keep only in original packaging.
- P243 Take action to prevent static discharges.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P405 Store locked up.
- P410 Protect from sunlight.
- P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
- P420 Store separately.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Trade name: PEROXAN BU M2

(Contd. of page 1)

2.3 Other hazards

Results of PBT and vPvB assessment

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 3457-61-2 EINECS: 222-389-8 Index number: 617-007-00-5 Reg-No.: 01-2119969063-35	tert-butyl alpha,alpha-dimethylbenzyl peroxide Org. Perox. E, H242; Aquatic Chronic 2, H411; Skin Irrit. 2, H315	40-50%
CAS: 6731-36-8 EINECS: 229-782-3 Reg-No.: 01-2119735694-30	di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide Org. Perox. B, H241	20-25%
CAS: 93685-81-5 EINECS: 297-629-8 Reg-No.: 01-2119490725-29	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Alternative CAS number: 13475-82-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	20-25%
CAS: 98-83-9 EINECS: 202-705-0 Index number: 601-027-00-6	2-phenylpropene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 25 %	0,1-2,5%
CAS: 98-86-2 EINECS: 202-708-7 Index number: 606-042-00-1	acetophenone Acute Tox. 4, H302; Eye Irrit. 2, H319	0,1-2,5%
CAS: 75-91-2 EINECS: 200-915-7 Reg-No.: 01-2119446670-40	tert-butyl hydroperoxide Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 2, H351; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Eye Dam. 1; H318: C ≥ 1 % Skin Sens. 1; H317: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	0-1%
CAS: 80-43-3 EINECS: 201-279-3 Index number: 617-006-00-X Reg-No.: 01-2119541688-27	bis(a,a-dimethylbenzyl) peroxide Org. Perox. F, H242; Repr. 1B, H360D; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	0-1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:



Take care of personal protection for the first aider.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

(Contd. on page 3)

Safety data sheet
 according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version: 14 (replaces version 13)

Revision: 14.12.2023

Trade name: **PEROXAN BU M2**

(Contd. of page 2)

- **5.3 Advice for firefighters**
 - **Protective equipment:**
 - **Additional information**
- Hydrocarbons, carbon dioxide and -monoxid.
- Do not inhale explosion gases or combustion gases.
- Cool endangered receptacles with water spray.
- Self-protection first!

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**


Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles.

Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).


While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.

 Do not smoke.
- **Information about fire - and explosion protection:**


Protect from heat.

Protect against electrostatic charges.


Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.

 Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.

 Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**

Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

(Contd. on page 4)

— IE —

Trade name: **PEROXAN BU M2**

(Contd. of page 3)

- Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines. Store away from foodstuffs, drinks and feeding stuffs.
 - **Further information about storage conditions:** Protect from heat and direct sunlight.
Protect from contamination.
Storage in a collecting room is required.
 - **Recommended storage temperature (To maintain quality):** +5 +30 °C
 - **Storage class:** 5.2
 - **7.3 Specific end use(s):** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

98-83-9 2-phenylpropene

OEL (Ireland)	Short-term value: 492 mg/m ³ , 100 ppm Long-term value: 246 mg/m ³ , 50 ppm IOELV
IOELV (EU)	Short-term value: 492 mg/m ³ , 100 ppm Long-term value: 246 mg/m ³ , 50 ppm
WEL (Great Britain)	Short-term value: 491 mg/m ³ , 100 ppm Long-term value: 246 mg/m ³ , 50 ppm

98-86-2 acetophenone

OEL (Ireland)	Long-term value: 49 mg/m ³ , 10 ppm
---------------	--

· DNELs

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

Dermal	DNEL Longterm System	2 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	1,4 mg/m ³ (Worker)

98-86-2 acetophenone

Dermal	DNEL Longterm System	0,35 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	1,23 mg/m ³ (Worker)

75-91-2 tert-butyl hydroperoxide

Dermal	DNEL Longterm System	0,21 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	85,2 mg/m ³ (Worker)
	DNEL Acute Local	28,4 mg/m ³ (Worker)
	DNEL Longterm System	2,2 mg/m ³ (Worker)
	DNEL Longterm Local	0,58 mg/m ³ (Worker)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

Oral	DNEL Longterm System	0,4 mg/kg bw/day (General population)
Dermal	DNEL Longterm System	0,8 mg/kg bw/day (Worker)
		0,4 mg/kg bw/day (General population)
Inhalative	DNEL Longterm System	5,6 mg/m ³ (Worker)
		1,4 mg/m ³ (General population)

· PNECs

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

PNEC Marinewater sed	0,01 mg/kg sed dw (AF 500)
PNEC Freshwater sed	0,102 mg/kg sed dw (AF 50)
PNEC Soil	5,29 mg/kg soil dw (AF 10)
PNEC STP	100 mg/l (AF 10)

98-86-2 acetophenone

PNEC Marinewater sed	0,113 mg/kg sed dw (-)
PNEC Freshwater	0,086 mg/l (AF 1.000)
PNEC Freshwater sed	1,13 mg/kg sed dw (-)
PNEC Soil	0,175 mg/kg soil dw (-)
PNEC STP	34,6 mg/l (AF 10)

(Contd. on page 5)

Trade name: **PEROXAN BU M2**

(Contd. of page 4)

PNEC Marinewater	0,009 mg/l (AF 10.000)
75-91-2 tert-butyl hydroperoxide	
PNEC Marinewater sed	0,001 mg/kg sed dw
PNEC Freshwater	0,002 mg/l (AF 1.000)
PNEC Seawater	0 mg/l (AF 10.000)
PNEC Freshwater sed	0,006 mg/kg sed dw (-)
PNEC Soil	0,166 mg/kg soil dw (AF 1.000)
PNEC STP	0,17 mg/l (AF 100)
80-43-3 bis(a,a-dimethylbenzyl) peroxide	
PNEC Freshwater	0,00234 mg/l (AF 50)
PNEC Freshwater sed	2,24 mg/kg sed dw (-)
PNEC Soil	0,447 mg/kg soil dw (-)
PNEC STP	100 mg/l (AF 10)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

Not necessary if room is well-ventilated.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· **Hand protection**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Colour:	Yellowish
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.

(Contd. on page 6)

Trade name: **PEROXAN BU M2**

(Contd. of page 5)

<ul style="list-style-type: none"> · Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. · Flash point: 60 °C · Decomposition temperature: ≥ 55 (SADT) °C · pH: Not determined. · Viscosity: · Kinematic viscosity: Not determined. · Dynamic at 20 °C: 10 mPas · Solubility · water: Undetermined. · Partition coefficient n-octanol/water (log value): not determined · Vapour pressure: Not determined. · Density and/or relative density · Density at 20 °C: 0,875 g/cm³ · Relative density: Not determined. · Vapour density: Not determined. 	
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: · VOC (EC): 207,2 g/l · Change in condition · Evaporation rate: Not determined. 	
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives: Void · Flammable gases: Void · Aerosols: Void · Oxidising gases: Void · Gases under pressure: Void · Flammable liquids: Flammable liquid and vapour. · Flammable solids: Void · Self-reactive substances and mixtures: Void · Pyrophoric liquids: Void · Pyrophoric solids: Void · Self-heating substances and mixtures: Void · Substances and mixtures, which emit flammable gases in contact with water: Void · Oxidising liquids: Void · Oxidising solids: Void · Organic peroxides: Heating may cause a fire. · Corrosive to metals: Void · Desensitised explosives: Void · Other safety characteristics · Active oxygen: 6,2 - 6,4 % 	

SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> · 10.1 Reactivity 	No further relevant information available.
<ul style="list-style-type: none"> · 10.2 Chemical stability · Thermal decomposition / conditions to be avoided: 	<p>SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.</p> <p>No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.</p>
<ul style="list-style-type: none"> · 10.3 Possibility of hazardous reactions 	Self-accelerating decomposition at SADT.
<ul style="list-style-type: none"> · 10.4 Conditions to avoid 	No further relevant information available.

(Contd. on page 7)

Trade name: **PEROXAN BU M2**

(Contd. of page 6)

- **10.5 Incompatible materials:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **10.6 Hazardous decomposition products:** Hydrocarbons, carbon dioxide and -monoxid.
No hazardous decomposition products if used and stored according to specifications.
- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

3457-61-2 tert-butyl alpha,alpha-dimethylbenzyl peroxide

Oral	LD50	4.700 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (rattus)
Inhalative	LC50	>1,2 mg/l (rattus)

6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide

Oral	LD50	>2.000 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated

Oral	LD50	>5.000 mg/kg (rattus)
------	------	-----------------------

98-83-9 2-phenylpropene

Oral	LD50	4.900 mg/kg (rattus)
------	------	----------------------

98-86-2 acetophenone

Oral	LD50	2.081 mg/kg (rattus)
------	------	----------------------

75-91-2 tert-butyl hydroperoxide

Oral	LD50	805 mg/kg /(70%) (rattus)
Dermal	LD50	633 mg/kg /(70%) (rabbit)
Inhalative	LC50 / 4h	1,2 mg/l /(70%) (rattus)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

Oral	LD50	>2.000 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (rattus)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated

EC50 / 48h	>0,04 mg/l (daphnia)
IC50 / 72h	>0,04 mg/l (algae)

75-91-2 tert-butyl hydroperoxide

EC50 / 72h	2,1 mg/l /(70%) (selenastrum capricornutum)
LC50 / 96h	42,3 mg/l /(70%) (pimephales promelas)
EC50	24,3 mg/l /(70%) (activa sludge)
EC50 / 48h	20 mg/l /(70%) (daphnia)

(Contd. on page 8)

Trade name: **PEROXAN BU M2**

(Contd. of page 7)

80-43-3 bis(a,a-dimethylbenzyl) peroxide		
EC50 / 72h	>20 mg/l (algae)	
EC50	>1.000 mg/l (activa sludge)	
· 12.2 Persistence and degradability		
· Degree of elimination:		
· Classification:		
3457-61-2 tert-butyl alpha,alpha-dimethylbenzyl peroxide		
Degradation	(Not readily biodegradable) (OECD 301 F)	
6731-36-8 di-tert-butyl 3,3,5-trimethylcyclohexylidene diperoxide		
Degradation	(Evidence for inherent biodegradability.) (OECD 301 D)	
93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polyimd., triisobutylene fraction, hydrogenated		
Degradation	(Not readily biodegradable)	
98-86-2 acetophenone		
Degradation	(Readily biodegradable) (OECD 301 C)	
75-91-2 tert-butyl hydroperoxide		
Degradation	(Not readily biodegradable) (OECD 301 D)	
80-43-3 bis(a,a-dimethylbenzyl) peroxide		
Degradation	(Not readily biodegradable) (OECD 301 F)	
· 12.3 Bioaccumulative potential		
· Partition coefficient: nOctanol/water: [Log Kow]		
3457-61-2	tert-butyl alpha,alpha-dimethylbenzyl peroxide	4,4 (25°C)
98-86-2	acetophenone	1,65 (20°C)
75-91-2	tert-butyl hydroperoxide	0,85 (30 °C)
80-43-3	bis(a,a-dimethylbenzyl) peroxide	5,6 (25°C)
· Bioconcentration factor (BCF)		
80-43-3 bis(a,a-dimethylbenzyl) peroxide		
BCF	747	
· 12.4 Mobility in soil		
No further relevant information available.		
· 12.5 Results of PBT and vPvB assessment		
· PBT:		
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· vPvB:		
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· 12.6 Endocrine disrupting properties		
The product does not contain substances with endocrine disrupting properties.		
· 12.7 Other adverse effects		
· Remark:		
Very toxic for fish		
· Additional ecological information:		
· General notes:		
Also poisonous for fish and plankton in water bodies.		
Very toxic for aquatic organisms		
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water		
Do not allow product to reach ground water, water course or sewage system.		
Danger to drinking water if even small quantities leak into the ground.		

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key:**

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· **Uncleaned packaging:**

· **Recommendation:**

This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· **14.1 UN number or ID number**






· **ADR, IMDG, IATA**

UN3107

(Contd. on page 9)

Trade name: **PEROXAN BU M2**

(Contd. of page 8)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	<p>UN3107 ORGANIC PEROXIDE TYPE E, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE, tert-BUTYL CUMYL PEROXIDE), ENVIRONMENTALLY HAZARDOUS</p> <p>ORGANIC PEROXIDE TYPE E, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE, tert-BUTYL CUMYL PEROXIDE), MARINE POLLUTANT</p> <p>ORGANIC PEROXIDE TYPE E, LIQUID (1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE, tert-BUTYL CUMYL PEROXIDE)</p>
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	<div style="display: flex; align-items: center;">   </div> <p>· Class · Label</p> <p>5.2 (P1) Organic peroxides. 5.2</p>
<ul style="list-style-type: none"> · IMDG 	<div style="display: flex; align-items: center;">   </div> <p>· Class · Label</p> <p>5.2 Organic peroxides. 5.2</p>
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; align-items: center;">  </div> <p>· Class · Label</p> <p>5.2 Organic peroxides. 5.2</p>
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p>Void</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	<p>Product contains environmentally hazardous substances: tert-BUTYL CUMYL PEROXIDE</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code · Segregation Code 	<p>Warning: Organic peroxides.</p> <p>-</p> <p>F-J,S-R</p> <p>D</p> <p>SW1 Protected from sources of heat.</p> <p>SG35 Stow "separated from" SGG1-acids</p> <p>SG36 Stow "separated from" SGG18-alkalis.</p> <p>SG72 See 7.2.6.3.2.</p>
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>125 ml</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p>
<ul style="list-style-type: none"> · RID / GGVSEB: 	<p>like ADR</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>125 ml</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>

IE —

(Contd. on page 10)

Trade name: **PEROXAN BU M2**

(Contd. of page 9)

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances**- **ANNEX I**

None of the ingredients is listed.

· **Seveso category**P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
E2 Hazardous to the Aquatic Environment· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

50 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements**

200 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3, 30, 40, 75

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H241 Heating may cause a fire or explosion.
H242 Heating may cause a fire.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H360D May damage the unborn child.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

· **Department issuing SDS:**

Environment protection / Security of labour

· **Contact:**

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· **Version number of previous version:**

13

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version: 14 (replaces version 13)

Revision: 14.12.2023

Trade name: **PEROXAN BU M2**

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. B: Organic peroxides – Type B
Org. Perox. E: Organic peroxides – Type E/F
Org. Perox. F: Organic peroxides – Type E/F
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

* Data compared to the
previous version altered.

IE —