

SECTION 1: Identification of the substance/mixture and of the company/undertaking






- **1.1 Product identifier**
- **Trade name:** PEROXAN MI-60 KPX
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Org. Perox. C	H242	Heating may cause a fire.
Acute Tox. 3	H331	Toxic if inhaled.
Skin Corr. 1C	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
Repr. 2	H361d	Suspected of damaging the unborn child.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

				
GHS02	GHS05	GHS06	GHS08	GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:** Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate
4-methylpentan-2-one
tert-butyl perbenzoate
- **Hazard statements**

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H331	Toxic if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H410	Very toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P243	Take action to prevent static discharges.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.

Trade name: PEROXAN MI-60 KPX

(Contd. of page 1)

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +25°C. Keep cool.
P420	Store separately.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

EC number: 942-932-9 Reg-No.: 01-2120103792-63	Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide Alternative CAS number: 37206-20-5 Flam. Liq. 3, H226; Org. Perox. D, H242; Asp. Tox. 1, H304; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	25-40%
CAS: 614-45-9 EINECS: 210-382-2 Reg-No.: 01-2119513317-46	tert-butyl perbenzoate Org. Perox. C, H242; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-30%
CAS: 6846-50-0 EINECS: 229-934-9 Reg-No.: 01-2119451093-47	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2, H361d; Aquatic Chronic 3, H412	10-25%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg-No.: 01-2119473980-30	4-methylpentan-2-one Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50 / 4h inhalative: 11 mg/l	5-10%
CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Repr. 2, H361d; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	5-10%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 % Skin Corr. 1B; H314: 50 % ≤ C < 70 % Skin Irrit. 2; H315: 35 % ≤ C < 50 % Eye Dam. 1; H318: C ≥ 8 % Eye Irrit. 2; H319: 5 % ≤ C < 8 % STOT SE 3; C ≥ 35 % Ox. Liq. 1; H271: C ≥ 70 % Ox. Liq. 2; H272: 50 % ≤ C < 70 %	0,1-2,5%
CAS: 102-82-9 EINECS: 203-058-7 Reg-No.: 01-2119474898-14	tributylamine Acute Tox. 3, H311; Acute Tox. 1, H330; Acute Tox. 4, H302; Skin Irrit. 2, H315	0-1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

(Contd. on page 3)

IE

Trade name: **PEROXAN MI-60 KPX**


(Contd. of page 2)

- **After inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
Avoid contact with skin and eyes.
While using do not eat, drink or smoke.

(Contd. on page 4)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 3)

Avoid shock and friction.



Do not smoke.

· **Information about fire - and explosion protection:**

Protect from heat.
Prevent impact and friction.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.

· **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.

· **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.

· **Further information about storage conditions:** Keep container tightly sealed.
Protect from heat and direct sunlight.
Protect from contamination.
Store under lock and key and out of the reach of children.
Storage in a collecting room is required.

· **Recommended storage temperature (To maintain quality):** +5 +25 °C

· **Storage class:** 5.2

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

108-10-1 4-methylpentan-2-one

OEL (Ireland)	Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm Sk, IOELV
IOELV (EU)	Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm
WEL (Great Britain)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV

123-42-2 4-hydroxy-4-methylpentan-2-one

OEL (Ireland)	Long-term value: 240 mg/m ³ , 50 ppm
WEL (Great Britain)	Short-term value: 362 mg/m ³ , 75 ppm Long-term value: 241 mg/m ³ , 50 ppm

7722-84-1 hydrogen peroxide solution

OEL (Ireland)	Short-term value: 3 mg/m ³ , 2 ppm Long-term value: 1,5 mg/m ³ , 1 ppm
WEL (Great Britain)	Short-term value: 2,8 mg/m ³ , 2 ppm Long-term value: 1,4 mg/m ³ , 1 ppm

· **DNELs**

Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide

Dermal	DNEL Longterm System	1,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	2,64 mg/m ³ (Worker)

614-45-9 tert-butyl perbenzoate

Dermal	DNEL Longterm System	17,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	24,7 mg/m ³ (Worker)

(Contd. on page 5)

Trade name: PEROXAN MI-60 KPX

(Contd. of page 4)

6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	17,62 mg/m ³ (Worker)
108-10-1 4-methylpentan-2-one		
Dermal	DNEL Longterm System	11,8 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	208 mg/m ³ (Worker)
	DNEL Longterm System	83 mg/m ³ (Worker)
123-42-2 4-hydroxy-4-methylpentan-2-one		
Dermal	DNEL Longterm System	467 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	32,6 mg/m ³ (Worker)
7722-84-1 hydrogen peroxide solution		
Inhalative	DNEL Longterm Local	1,4 mg/m ³ (Worker)
102-82-9 tributylamine		
Inhalative	DNEL Acute Systemic	10,6 mg/m ³ (Worker)
	DNEL Longterm System	5,3 mg/m ³ (Worker)
	DNEL Longterm Local	15,2 mg/m ³ (Worker)
· PNECs		
Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide		
PNEC Marinewater sed	0,06 mg/kg sed dw (-)	
PNEC Freshwater	0,00133 mg/l (AF 1.000)	
PNEC Freshwater sed	0,59 mg/kg sed dw (-)	
PNEC Soil	0,118 mg/kg soil dw (-)	
PNEC STP	1,28 mg/l (AF 10)	
PNEC Marinewater	0,000133 mg/l (AF 10.000)	
614-45-9 tert-butyl perbenzoate		
PNEC Marinewater sed	0,028 mg/kg sed dw	
PNEC Freshwater	0,01 mg/l (AF 10)	
PNEC Freshwater sed	0,28 mg/kg sed dw	
PNEC Soil	0,049 mg/kg soil dw	
PNEC STP	0,6 mg/l (AF 10)	
PNEC Marinewater	0,00101 mg/l (AF 100)	
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
PNEC Marinewater sed	0,529 mg/kg sed dw (-)	
PNEC Freshwater	0,014 mg/l (AF 50)	
PNEC Freshwater sed	5,29 mg/kg sed dw	
PNEC Soil	1,05 mg/kg soil dw	
PNEC STP	3 mg/l (AF 10)	
PNEC Marinewater	0,001 mg/l (AF 500)	
108-10-1 4-methylpentan-2-one		
PNEC Marinewater sed	0,83 mg/kg sed dw (-)	
PNEC Freshwater	0,6 mg/l (AF 50)	
PNEC Seawater	0,06 mg/l (AF 500)	
PNEC Freshwater sed	8,27 mg/kg sed dw (-)	
PNEC Soil	1,3 mg/kg soil dw (-)	
PNEC STP	27,5 mg/l (AF 10)	
123-42-2 4-hydroxy-4-methylpentan-2-one		
PNEC Marinewater sed	0,74 mg/kg sed dw	
PNEC Freshwater	2 mg/l (AF 50)	
PNEC Freshwater sed	7,4 mg/kg sed dw	
PNEC Soil	0,31 mg/kg soil dw	
PNEC STP	100 mg/l (AF 10)	
PNEC Marinewater	0,2 mg/l (AF 500)	
7722-84-1 hydrogen peroxide solution		
PNEC Marinewater sed	0,047 mg/kg sed dw	
PNEC Freshwater	0,013 mg/l (AF 50)	
PNEC Freshwater sed	0,047 mg/kg sed dw	

(Contd. on page 6)

Trade name: PEROXAN MI-60 KPX


(Contd. of page 5)


PNEC Soil	0,002 mg/kg soil dw
PNEC STP	4,66 mg/l (AF 100)
PNEC Marinewater	0,013 mg/l (AF 50)
102-82-9 tributylamine	
PNEC Marinewater sed	3,59 mg/kg sed dw
PNEC Freshwater	0,008 mg/l (AF 1.000)
PNEC Freshwater sed	35,85 mg/kg sed dw
PNEC Soil	7,17 mg/kg soil dw
PNEC STP	100 mg/l (AF 1)
PNEC Marinewater	0,0008 mg/l (AF 10.000)
Ingredients with biological limit values:	
108-10-1 4-methylpentan-2-one	
BMGV (Great Britain)	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.
- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.


 Filter A2
- **Hand protection**


Only use chemical-protective gloves with CE-labelling of category III.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves
- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Butyl rubber, BR
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Neoprene
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**

 Tightly sealed goggles
- **Body protection:**

 Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Colourless

(Contd. on page 7)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 6)

<ul style="list-style-type: none"> · Odour: · Odour threshold: · Melting point/freezing point: · Boiling point or initial boiling point and boiling range · Flammability · Lower and upper explosion limit · Lower: · Upper: · Flash point: · Decomposition temperature: · pH · Viscosity: · Kinematic viscosity · Dynamic: · Solubility · water: · Partition coefficient n-octanol/water (log value) · Vapour pressure: · Density and/or relative density · Density at 20 °C: · Relative density · Vapour density 	<ul style="list-style-type: none"> Characteristic Not determined. Not applicable. Not applicable. May cause fire. Not determined. Not determined. 59 °C > +60 °C (SADT) Mixture is non-soluble (in water). Not determined. Not determined. Undetermined. not determined Not determined. Not determined. 0,995 g/cm³ Not determined. Not determined.
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: · Explosive properties: · Change in condition · Evaporation rate 	<ul style="list-style-type: none"> Fluid Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids · Organic peroxides · Corrosive to metals · Desensitised explosives · Other safety characteristics · Active oxygen 	<ul style="list-style-type: none"> Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void Void Heating may cause a fire. Void Void 8,5 - 8,8 %

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

(Contd. on page 8)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 7)

- **10.3 Possibility of hazardous reactions** To avoid thermal decomposition do not overheat.
- **10.4 Conditions to avoid** Self-accelerating decomposition at SADT.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **Additional information:** Hydrocarbons, carbon dioxide and -monoxid.
No hazardous decomposition products if used and stored according to specifications.
Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Toxic if inhaled.

- **LD/LC50 values relevant for classification:**

Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide

Oral	LD50	1.575 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (rattus)
Inhalative	LC50 / 4h	1,5 mg/l (rattus)

614-45-9 tert-butyl perbenzoate

Oral	LD50	4.838 mg/kg (rattus)
Dermal	LD50	3.817 mg/kg (rattus)
Inhalative	LC100 4h	4,9 mg/l (rattus)
	LC0 / 4h	1,01 mg/l (rattus)

6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Oral	LD50	3.200 mg/kg (rattus)
Dermal	LD50	18.900 mg/kg (caviinae)

108-10-1 4-methylpentan-2-one

Oral	LD50	>2.080 mg/kg (rattus)
Dermal	LD50	>16.000 mg/kg (cuniculosus)
Inhalative	LC50 / 4h	11 mg/l (ATE)
	LC50 / 4h	11 mg/l

123-42-2 4-hydroxy-4-methylpentan-2-one

Oral	LD50	3.002 mg/kg (rattus)
------	------	----------------------

102-82-9 tributylamine

Oral	LD50	540 mg/kg (rattus)
Dermal	LD50	250 mg/kg (cuniculosus)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

Aquatic toxicity:

Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide

EC50 / 72h	1,33 mg/l (alga (Süßwasser))
------------	------------------------------

(Contd. on page 9)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 8)

LC50 / 96h	1,89 mg/l (piscis)	
EC50 / 48h	4,48 mg/l (daphnia magna)	
108-10-1 4-methylpentan-2-one		
EC50 / 72h	146 mg/l (alga (Süßwasser))	
LC50 / 96h	179 mg/l (brachydanio rerio)	
EC50 / 48h	200 mg/l (daphnia magna)	
· 12.2 Persistence and degradability		
· Degree of elimination:		
· Classification:		
614-45-9 tert-butyl perbenzoate		
Degradation	(Readily biodegradable) (OECD 301 D)	
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
Degradation	(Readily biodegradable, failing 10-d wind) (OECD 301 B)	
108-10-1 4-methylpentan-2-one		
Degradation	(Readily biodegradable) (OECD 301 F)	
123-42-2 4-hydroxy-4-methylpentan-2-one		
Degradation	(Readily biodegradable) (OECD 301 A)	
7722-84-1 hydrogen peroxide solution		
Degradation	(Readily biodegradable)	
102-82-9 tributylamine		
Degradation	(Readily biodegradable) (OECD 301 B)	
· 12.3 Bioaccumulative potential		
· Partition coefficient: nOctanol/water: [Log Kow]		
614-45-9	tert-butyl perbenzoate	3 (25°C)
108-10-1	4-methylpentan-2-one	1,9
123-42-2	4-hydroxy-4-methylpentan-2-one	-0,09 (20°C)
7722-84-1	hydrogen peroxide solution	-1,57 (20°C)
102-82-9	tributylamine	3,34 (25 °C)
· Bioconcentration factor (BCF)		
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
BCF	183-194 (piscis)	
102-82-9 tributylamine		
BCF	7,3	
· 12.4 Mobility in soil No further relevant information available.		
· 12.5 Results of PBT and vPvB assessment		
· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.		
· 12.7 Other adverse effects		
· Remark: Very toxic for fish		
· Additional ecological information:		
· General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.		

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key:**

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.






(Contd. on page 10)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 9)

- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	UN3103
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE), MARINE POLLUTANT ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYBENZOATE)
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	5.2 (P1) Organic peroxides. 5.2
<ul style="list-style-type: none"> · IMDG <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label 	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> · IATA <div style="display: flex; align-items: center; gap: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label 	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	Void
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	Product contains environmentally hazardous substances: tert-BUTYL PEROXYBENZOATE Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code 	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	25 ml Code: E0 Not permitted as Excepted Quantity 1 D
<ul style="list-style-type: none"> · RID / GGVSEB: 	like ADR
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 	25 ml

(Contd. on page 11)

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 10)

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I

None of the ingredients is listed.

· Seveso category

H2 ACUTE TOXIC

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements

50 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H271 May cause fire or explosion; strong oxidiser.
H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact:

Tel: +49 2871 9902-0
E-mail: mail@pergan.com

· Version number of previous version:

6

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.01.2024

Version: 7 (replaces version 6)

Revision: 16.02.2023

Trade name: **PEROXAN MI-60 KPX**

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Ox. Liq. 1: Oxidizing liquids – Category 1
Org. Perox. C: Organic peroxides – Type C/D
Org. Perox. D: Organic peroxides – Type C/D
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the
previous version altered.