

Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PK122 V-80 · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

Further information obtainable

Environment protection / Security of labour from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Org. Perox. C H242 Heating may cause a fire.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS08 GHS09

· Signal word Danger

· Hazard-determining

components of labelling:

cyclohexylidenebis[tert-butyl] peroxide

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

· Hazard statements H226 Flammable liquid and vapour. H242 Heating may cause a fire.

P405

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking

Keep only in original packaging.

P234 P243 Take action to prevent static discharges. P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Do NOT induce vomiting. P331

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower]. Store locked up.

P410 Protect from sunlight. P411+P235 Store at temperatures not exceeding +25°C. Keep cool.

P420 Store separately

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Determination of endocrine-

disrupting properties The product does not contain substances with endocrine disrupting properties.

(Contd. on page 2)

IE.



Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 3006-86-8	cyclohexylidenebis[tert-butyl] peroxide	70-80%
EINECS: 221-111-2	Org. Perox. C, H242; Asp. Tox. 1, H304; Aquatic Chronic 1, H410	
Reg-No.: 01-2119967008-33		
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	10-20%
EINECS: 297-629-8	Alternative CAS number: 13475-82-6	
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately remove contaminated clothing.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delaved

4.3 Indication of any immediate

medical attention and special treatment needed

No further relevant information available

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· For safety reasons unsuitable

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

extinguishing agents:

5.2 Special hazards arising from

the substance or mixture

Water with full jet

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters · Protective equipment:

Do not inhale explosion gases or combustion gases. Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)



Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 2)

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities · Storage:

Requirements to be met by

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination. Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

max.: +25 °C

Storage class: 5.2

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· PNECs

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

PNEC Marinewater sed | 0,01 mg/kg sed dw (AF 500)

(Contd. on page 4)



Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 3)

PNEC Freshwater 0,00645 mg/l (AF 10) 0,102 mg/kg sed dw (AF 50) PNFC Freshwater sed PNEC Soil 5,29 mg/kg soil dw (AF 10) PNEC STP 2 mg/l (AF 10)

PNEC Marinewater 0,000645 mg/l (AF 100)

Additional information: The lists valid during the making were used as basis.

 8.2 Exposure controls Appropriate engineering

controls No further data: see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

> Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless · Odour: Characteristic Odour threshold: Not determined. · Melting point/freezing point: Not applicable. Boiling point or initial boiling point and boiling range Not applicable. Not applicable. · Flammability

Lower and upper explosion limit

· Lower: Not determined. Not determined. · Upper: 54 °C · Flash point: Decomposition temperature: +60 °C (SADT) · pH Not determined. Viscosity:

· Kinematic viscosity

Not determined. Not determined. · Dvnamic: Solubility

Undetermined. water: · Partition coefficient n-octanol/water (log value) not determined

(Contd. on page 5)



(Contd. of page 4)

Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

· Vapour pressure: Not determined. · Density and/or relative density

Density at 20 °C: 0,88 g/cm³ Relative density Not determined · Vapour density Not determined.

· 9.2 Other information No further relevant information available.

Appearance:

· Form: Fluid · Important information on protection of health and environment,

and on safety.

Product is not selfigniting. · Ignition temperature:

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Change in condition

· Evaporation rate Not determined

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in

contact with water Void Oxidising liquids Void · Oxidising solids Void

Organic peroxides Heating may cause a fire.

Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition /

No further relevant information available.

conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-

accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. · Acute toxicity

(Contd. on page 6)



Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 5)

LD/LC50 values relevant for classification:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

LD50 >5.000 mg/kg (rattus) Dermal LD0 >2.000 mg/kg (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

LD50 >5.000 mg/kg (rattus)

 Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met. Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure · STOT-repeated exposure Based on available data, the classification criteria are not met.

 Aspiration hazard May be fatal if swallowed and enters airways. · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

EC50 / 72h | 0,5 mg/l (algae) LC50 / 96h |>0,64 mg/l (fish) EC50 / 48h 0,598 mg/l (daphnia)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h |>0,04 mg/l (daphnia) IC50 / 72h >0,04 mg/l (algae)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

Degradation (Not readily biodegradable) (OECD 301 D)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

7,2 (25°C)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting

The product does not contain substances with endocrine disrupting properties. properties

12.7 Other adverse effects No further relevant information available.

· Additional ecological information:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

(Contd. on page 7)



Version: 9 (replaces version 8) Printing date 03.04.2024 Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 6)

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

· 14.1 UN number or ID number · ADR, IMDG, IATA UN3103

· 14.2 UN proper shipping name

UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-· ADR

BUTYLPEROXY) CYCLOHEXANE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE C, LIQUID (1,1-DI-(tert-BUTYLPEROXY)

CYCLOHEXANE)

· 14.3 Transport hazard class(es)

· ADR



· IMDG, IATA

· Class 5.2 (P1) Organic peroxides.

Label

· IMDG





5.2 Organic peroxides. · Class

Label

· IATA



Class 5.2 Organic peroxides.

· Label 5.2

· 14.4 Packing group · ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR):

· 14.6 Special precautions for user Warning: Organic peroxides.

· EMS Number: F-J,S-R D · Stowage Category

· Stowage Code SW1 Protected from sources of heat. Segregation Code SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.

Void

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 25 ml

Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity

Transport category Tunnel restriction code D

· RID / GGVSEB: like ADR

·IMDG

25 ml · Limited quantities (LQ)

(Contd. on page 8)



Printing date 03.04.2024 Version: 9 (replaces version 8) Revision: 27.04.2023

Trade name: PEROXAN PK122 V-80

(Contd. of page 7)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· Qualifying quantity (tonnes) for the application of lower-tier 50 t requirements Qualifying quantity (tonnes) for the application of upper-tier

200 t requirements

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex Ш

None of the ingredients is listed.

REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Environment protection / Security of labour

8

Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the · Abbreviations and acronyms:

International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Org. Perox. C: Organic peroxides – Type C/D Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· * Data compared to the previous version altered.

IE -