

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PK122 W · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

· Hazard pictograms

Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.







GHS02 GHS08 GHS09

· Signal word Danger

· Hazard-determining

components of labelling:

Hazard statements

cyclohexylidenebis[tert-butyl] peroxide H242 Heating may cause a fire.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Do NOT induce vomiting. P331 P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Determination of endocrine-

disrupting properties The product does not contain substances with endocrine disrupting properties.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Dangerous components: CAS: 3006-86-8 cyclohexylidenebis[tert-butyl] peroxide 40-50% EINECS: 221-111-2 Org. Perox. C, H242; Asp. Tox. 1, H304; Aquatic Chronic 1, H410 Reg-No.: 01-2119967008-33

(Contd. on page 2)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN PK122 W

(Contd. of page 1)

· Additional information: For the wording of the listed hazard phrases refer to section 16

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet. · After skin contact: Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available

# **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Additional information Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

## **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

While using do not eat, drink or smoke.

(Contd. on page 3)



(Contd. of page 2)

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK122 W

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage: Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Protect from heat and direct sunlight. Protect from contamination.

Storage in a collecting room is required.

Recommended storage temperature (To maintain

quality):

max.: +30 °C

Storage class: 5.2

· 7.3 Specific end use(s) No further relevant information available

## **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· PNECs

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

PNEC Marinewater sed | 0,01 mg/kg sed dw (AF 500) 0,00645 mg/l (AF 10) PNEC Freshwater

PNEC Freshwater sed 0,102 mg/kg sed dw (AF 50) 5,29 mg/kg soil dw (AF 10) PNEC Soil

PNEC STP 2 mg/l (AF 10) **PNEC Marinewater** 0,000645 mg/l (AF 100)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately

Do not eat, drink, smoke or sniff while working

(Contd. on page 4)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN PK122 W

Use skin protection cream for skin protection.

(Contd. of page 3)

Be sure to clean skin thoroughly after work and before breaks.

Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Protective aloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

· Penetration time of glove

· Respiratory protection:

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

· Eye/face protection



Tightly sealed goggles

· Body protection:

Protective work clothing

#### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

· General Information

· Colour:

· Odour: · Odour threshold:

· Melting point/freezing point:

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

· Lower: · Upper:

· Flash point: **Decomposition temperature:** 

· pH

· Viscosity:

Kinematic viscosity Dynamic at 20 °C:

· Solubility water:

· Partition coefficient n-octanol/water (log value) · Vapour pressure:

Density and/or relative density Density at 20 °C:

Relative density · Vapour density

not determined Not determined.

Undetermined.

Colourless

Characteristic

Not applicable.

Not applicable.

Not applicable.

Not determined.

Not determined.

> +70 °C (SADT)

Not determined.

Not determined

> SADT

22 mPas

Not determined.

0,89 g/cm<sup>3</sup> Not determined. Not determined.

9.2 Other information No further relevant information available.

Appearance:

Fluid · Form: · Important information on protection of health and environment,

and on safety.

· Ignition temperature:

**Explosive properties:** 

· Solvent content: · VOC (EC)

Change in condition · Evaporation rate

Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

0,0 g/l

Not determined.

(Contd. on page 5)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN PK122 W

(Contd. of page 4)

	<b>,</b> -	13
Information with regard to physical hazard classes		
· Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable gas	ses in	
contact with water	Void	
Oxidising liquids	Void	
· Oxidising solids	Void	
Organic peroxides	Heating may cause a fire.	
· Corrosive to metals	Void	
Desensitised explosives	Void	
Other safety characteristics	. 5.5	
· Active oxygen	6,0 - 6,3 %	

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

10.4 Conditions to avoid

· 10.5 Incompatible materials:

No further relevant information available Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

Self-accelerating decomposition at SADT.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

## **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

LD50 >5.000 mg/kg (rattus) Dermal LD0 >2.000 mg/kg (rattus)

Skin corrosion/irritation Serious eye damage/irritation

Respiratory or skin sensitisation

Germ cell mutagenicity · Carcinogenicity Reproductive toxicity STOT-single exposure · STOT-repeated exposure

Aspiration hazard

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

May be fatal if swallowed and enters airways.

(Contd. on page 6)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN PK122 W

(Contd. of page 5)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

EC50 / 72h | 0,5 mg/l (algae) LC50 / 96h | >0,64 mg/l (fish) EC50 / 48h | 0,598 mg/l (daphnia)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide

Degradation (Not readily biodegradable) (OECD 301 D)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

3006-86-8 cyclohexylidenebis[tert-butyl] peroxide 7,2 (25°C)
8042-47-5 White mineral oil, petroleum > 3,5

• 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

• 12.7 Other adverse effects No further relevant information available.

· Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system

• Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

· Uncleaned packaging:

• Recommendation: This material and its container must be disposed of as hazardous waste.

# **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3105

· 14.2 UN proper shipping name

· IMDG, IATA

ADR UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (1,1-DI-(tert-

BUTYLPEROXY) CYCLOHEXANE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE D, LIQUID (1,1-DI-(tert-BUTYLPEROXY)

CYCLOHEXANE)

(Contd. on page 7)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Void

# Trade name: PEROXAN PK122 W

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR





Class 5.2 (P1) Organic peroxides. · Label

· IMDG





· IATA



Class 5.2 Organic peroxides.

Label 5.2

· 14.4 Packing group · ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant:

Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

· Stowage Category D

· Stowage Code SW1 Protected from sources of heat. · Segregation Code SG35 Stow "separated from" SGG1-acids

SG36 Stow "separated from" SGG18-alkalis.

SG72 See 7.2.6.3.2.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 125 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category D Tunnel restriction code

RID / GGVSEB: like ADR

· IMDG

· Limited quantities (LQ) 125 ml · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

Named dangerous substances

- ANNEX I None of the ingredients is listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier

requirements 200 t

(Contd. on page 8)



(Contd. of page 7)

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK122 W

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H242 Heating may cause a fire.

H304 May be fatal if swallowed and enters airways. H410 Very toxic to aquatic life with long lasting effects.

Environment protection / Security of labour Department issuing SDS:

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

version:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

PBT: Persistent, Bloaccumulative and Toxic VPVB: very Persistent and very Bioaccumulative Org. Perox. C: Organic peroxides — Type C/D Org. Perox. D: Organic peroxides — Type C/D Asp. Tox. 1: Aspiration hazard — Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

\* \* Data compared to the previous version altered.