

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PK234 W · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. C H242 Heating may cause a fire.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 · Hazard pictograms

The product is classified and labelled according to the CLP regulation.

GHS02

· Signal word Danger

· Hazard-determining

components of labelling: di-tert-butyl sec-butylidene diperoxide **Hazard statements** H242 Heating may cause a fire.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvR· The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrine-

disrupting properties The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:			
CAS: 2167-23-9 EINECS: 218-507-2	di-tert-butyl sec-butylidene diperoxide	Org. Perox. C, H242; Aquatic Chronic 4, H413	40-50%
Reg-No.: 01-2120759172-55			

(Contd. on page 2)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 1)

· Additional information: For the wording of the listed hazard phrases refer to section 16

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet. · After skin contact: Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate

medical attention and special treatment needed

No further relevant information available.

No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Additional information Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

(Contd. on page 3)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 2)

While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

· Requirements to be met by

storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about

storage conditions:

Protect from heat and direct sunlight. Protect from contamination. Storage in a collecting room is required.

Recommended storage temperature (To maintain

quality):

max.: +30 °C

Storage class: 5.2

· 7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· DNELs

2167-23-9 di-tert-butyl sec-butylidene diperoxide

DNEL Longterm System 1,5 mg/kg bw/day (Worker) Dermal Inhalative DNEL Longterm System 2,65 mg/m3 (Worker)

· PNECs

2167-23-9 di-tert-butyl sec-butylidene diperoxide

PNEC Marinewater sed | 0,097 mg/kg sed dw (-)

PNEC Freshwater 0,083 mg/l (-) PNEC Freshwater sed 0,97 mg/kg sed dw (-) PNEC Soil 0,15 mg/kg soil dw (-) PNEC STP 2 mg/l (AF 10) **PNEC Marinewater** 0,008 mg/l (AF 10)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls

No further data; see section 7.

(Contd. on page 4)



(Contd. of page 3)

Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work. Store protective clothing separately.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Not necessary if room is well-ventilated. · Respiratory protection:

· Individual protection measures, such as personal protective equipment

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated. Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butvl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour: · Odour:

· Odour threshold: Not determined. · Melting point/freezing point: Not applicable. · Boiling point or initial boiling point and boiling range Not applicable. Not applicable.

Flammability

· Lower and upper explosion limit

· Lower: · Upper:

· Flash point:

Decomposition temperature: Hq·

· Viscosity: · Kinematic viscosity

Dynamic at 20 °C: · Solubility

water:

· Partition coefficient n-octanol/water (log value)

· Vapour pressure:

Density and/or relative density

· Density at 20 °C: Relative density Vapour density

Not determined. Not determined. No further relevant information available.

0,86 g/cm³

· 9.2 Other information

Appearance:

· Form:

Fluid

Colourless

Characteristic

Not determined. Not determined.

+70 °C (SADT) Not determined.

Not determined.

Undetermined.

not determined

Not determined.

66 °C

7 mPas

(Contd. on page 5) 1E



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 4)

	\ 1 9
Important information on protection of health and environme and on safety.	nt,
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour
Explosite proportion	mixtures are possible.
Change in condition	minus di o possible.
· Evaporation rate	Not determined.
	Tot dotominod.
Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in	
contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
Desensitised explosives	Void
· Other safety characteristics	VOIU
· Active oxygen	6.8 - 6.9 %
ACTIVE OXYGETI	0,0 - 0,3 /0

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

· Additional information:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

2167-23-9 di-tert-butyl sec-butylidene diperoxide

 Oral
 LD50
 >5.000 mg/kg (rattus)

 Dermal
 LD50
 >2.000 mg/kg (rattus)

 Inhalative
 LC0 / 4h
 2,42 mg/l (rattus)

· Serious eye damage/irritation

Skin corrosion/irritation Ba

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation

Based on available data, the classification criteria are not met.

• **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 5) Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

2167-23-9 di-tert-butyl sec-butylidene diperoxide

EC50 / 72h | 100 mg/l (algae) LC50 / 96h >10 mg/l (fish) EC50 / 48h | 150 mg/l (daphnia)

12.2 Persistence and degradability

· Degree of elimination:

· Classification:

2167-23-9 di-tert-butyl sec-butylidene diperoxide

Degradation (Not readily biodegradable) (OECD 301 B)

12.3 Bioaccumulative potential

Partition coefficient: nOctanol/water: [Log Kow]

2167-23-9 di-tert-butyl sec-butylidene diperoxide 5,4 (30°C) 8042-47-5 White mineral oil, petroleum > 3,5

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

· Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

· Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA UN3103

14.2 UN proper shipping name

· ADR UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (2,2-DI-(tert-

BUTYLPEROXY)BUTANE)

ORGANIC PEROXIDE TYPE C, LIQUID (2,2-DI-(tert-BUTYLPEROXY) · IMDG, IATA

BUTANE)

(Contd. on page 7)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR



Class 5.2 (P1) Organic peroxides.

· Label 5.

· IMDG, IATA



Class 5.2 Organic peroxides.

· Label 5.2

14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

· Stowage Category D

Stowage Code
SW1 Protected from sources of heat.
Segregation Code
SG35 Stow "separated from" SGG1-acids
SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

Transport/Additional information:

· ADR

· Limited quantities (LQ) 25 ml · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category 1
· Tunnel restriction code D

· **RID / GGVSEB**: like ADR

·IMDG

· Limited quantities (LQ) 25 ml · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

• Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· Qualifying quantity (tonnes) for the application of lower-tier

requirements 50 t Qualifying quantity (tonnes) for

the application of upper-tier requirements 200 REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

(Contd. on page 8)



Printing date 03.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PK234 W

(Contd. of page 7)

· REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H242 Heating may cause a fire.

H413 May cause long lasting harmful effects to aquatic life.

Environment protection / Security of labour Department issuing SDS:

Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the · Abbreviations and acronyms:

International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

INDEAS INTERNATIONAL MAINTINE CODE IN DAIGNESS GOODS
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

VPVB: very Persistent and very Bioaccumulative
Org. Perox. C: Organic peroxides – Type C/D
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

·* Data compared to the previous version altered.

IE -