


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PERGAQUICK CP24 A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Accelerator for polymerisation / crosslinking
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:**
Environment protection / Security of labour
Competent person:
* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com
* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com
* Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com
Security of labour
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Carc. 2 H351 Suspected of causing cancer.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** 
- **Signal word** Warning
- **Hazard-determining components of labelling:** N,N-dimethylaniline
- **Hazard statements** H351 Suspected of causing cancer.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· Dangerous components:		
CAS: 121-69-7 EINECS: 204-493-5 Index number: 612-016-00-0 Reg-No.: 01-2119950342-44	N,N-dimethylaniline Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Carc. 2, H351; Aquatic Chronic 2, H411	5-10%
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg-No.: 01-2119539582-35	2-methylpentane-2,4-diol Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-10%

Trade name: PERGAQUICK CP24 A

(Contd. of page 1)

CAS: 128-37-0 EINECS: 204-881-4 Reg-No.: 01-2119555270-46	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0,1-1%
CAS: 68084-48-0 EINECS: 268-439-2 Reg-No.: 01-2120784744-41	Copper(2+) neodecanoate Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302	0,1-1%
· Additional information: For the wording of the listed hazard phrases refer to section 16.		
· Components:		
Cobalt-Polymer		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.



Take care of personal protection for the first aider.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information** Self-protection first!

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Do not allow to enter sewers/ surface or ground water.
- **6.4 Reference to other sections** Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.



Do not allow to enter sewers/ surface or ground water.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 3)

MT

Trade name: **PERGAQUICK CP24 A**

(Contd. of page 2)

Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
While using do not eat, drink or smoke.

- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Store away from peroxide.
Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** +5 +30 °C
- **Storage class:** 10-13
- **7.3 Specific end use(s):** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

121-69-7 N,N-dimethylaniline

WEL (Great Britain)	Short-term value: 50 mg/m ³ , 10 ppm Long-term value: 25 mg/m ³ , 5 ppm Sk
---------------------	--

107-41-5 2-methylpentane-2,4-diol

WEL (Great Britain)	Short-term value: 123 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
---------------------	---

128-37-0 Butylated hydroxytoluene

WEL (Great Britain)	Long-term value: 10 mg/m ³
---------------------	---------------------------------------

· **DNELs**

121-69-7 N,N-dimethylaniline

Dermal	DNEL Longterm System	2,988 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	3,406 mg/m ³ (Worker)

107-41-5 2-methylpentane-2,4-diol

Dermal	DNEL Longterm System	42 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	44,4 mg/m ³ (Worker)

128-37-0 Butylated hydroxytoluene

Dermal	DNEL Longterm System	0,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	3,5 mg/m ³ (Worker)

· **PNECs**

121-69-7 N,N-dimethylaniline

PNEC Marinewater sed	4,942 mg/kg sed dw (-)
PNEC Freshwater	0,023 mg/l (AF 100)
PNEC Freshwater sed	4,942 mg/kg sed dw (-)
PNEC Soil	1,906 mg/kg soil dw (-)
PNEC STP	5,948 mg/l (AF 10)
PNEC Marinewater	0,002 mg/l (AF 1.000)

107-41-5 2-methylpentane-2,4-diol

PNEC Marinewater sed	0,159 mg/kg sed dw (-)
PNEC Freshwater	0,429 mg/l (AF 1.000)
PNEC Freshwater sed	1,59 mg/kg sed dw (-)
PNEC Soil	0,066 mg/kg soil dw (-)

(Contd. on page 4)

Trade name: **PERGAQUICK CP24 A**


(Contd. of page 3)

PNEC STP	20 mg/l (AF 10)
PNEC Marinewater	0,043 mg/l (AF 10.000)
128-37-0 Butylated hydroxytoluene	
PNEC Marinewater sed	0,00996 mg/kg sed dw (-)
PNEC Freshwater	0,000199 mg/l (AF 1.000)
PNEC Seawater	0,00002 mg/l (AF 10.000)
PNEC Freshwater sed	0,0996 mg/kg sed dw (-)
PNEC Soil	0,04769 mg/kg soil dw (-)
PNEC STP	0,17 mg/l (-)


- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Be sure to clean skin thoroughly after work and before breaks.
- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.


 Filter A2
- **Protection of hands:**


Only use chemical-protective gloves with CE-labelling of category III.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

 Protective gloves
- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
 Butyl rubber, BR
 Fluorocarbon rubber (Viton)
 Nitrile rubber, NBR
 Neoprene
- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**

 Tightly sealed goggles
- **Body protection:**

 Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
· Form:	Fluid
· Colour:	Red
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Not applicable.
· Flash point:	94 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.

(Contd. on page 5)

Trade name: **PERGAQUICK CP24 A**

(Contd. of page 4)

· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0,96 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Undetermined.
· Partition coefficient: n-octanol/water:	not determined
· Viscosity:	
· Dynamic at 20 °C:	73 mPas
· Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No hazardous decomposition products if used and stored according to specifications.
- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

121-69-7 N,N-dimethylaniline

Oral	LD50	951 mg/kg (rattus)
Dermal	LD50	1.690 mg/kg (cuniculosus)

107-41-5 2-methylpentane-2,4-diol

Oral	LD50	>2.000 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (cuniculosus)

128-37-0 Butylated hydroxytoluene

Oral	LD50	>5.000 mg/kg (rattus)
Dermal	LD50	>5.000 mg/kg (cuniculosus)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

Trade name: **PERGAQUICK CP24 A**

(Contd. of page 5)

SECTION 12: Ecological information**12.1 Toxicity****· Aquatic toxicity:****121-69-7 N,N-dimethylaniline**

EC50 / 72h 22 mg/l (alga)

LC50 / 96h 53,7 mg/l (piscis)

107-41-5 2-methylpentane-2,4-diol

LC50 / 96h 8.510 mg/l (gambusia affinis)

128-37-0 Butylated hydroxytoluene

LC0 / 96h >0,57 mg/l (piscis)

EC50 / 48h 0,61 mg/l (daphnia magna)

IC50 / 72h >0,4 mg/l (alga)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:**· Remark:**

Harmful to fish

· Additional ecological information:**· General notes:**

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment**· PBT:**

Not applicable.

· vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· Uncleaned packaging:**· Recommendation:**

This material and its container must be disposed of as hazardous waste.

*** SECTION 14: Transport information****· 14.1 UN-Number****· ADR, IMDG, IATA**

Void

· 14.2 UN proper shipping name**· ADR, IMDG, IATA**

Void

· 14.3 Transport hazard class(es)**· ADR, IMDG, IATA****· Class**

Void

· 14.4 Packing group**· ADR, IMDG, IATA**

Void

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Not applicable.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

No dangerous good according the regulation of transport.

· RID / GGVSEB:

like ADR

Trade name: **PERGAQUICK CP24 A**

(Contd. of page 6)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· **Directive 2012/18/EU**

· **Named dangerous substances**

- **ANNEX I**

None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:**

Environment protection / Security of labour

· **Contact:**

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**