

Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PERGAQUICK CP24 A · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance /

the mixture

Accelerator for polymerisation / crosslinking

For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

H351 Suspected of causing cancer.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS08

· Signal word Warning

· Hazard-determining

components of labelling:

N,N-dimethylaniline

Hazard statements

H351 Suspected of causing cancer. H412 Harmful to aquatic life with long lasting effects.

P201 · Precautionary statements Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P280

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrine-disrupting properties

128-37-0 Butylated hydroxytoluene

List II

5-10%

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 121-69-7 N.N-dimethylaniline EINECS: 204-493-5

Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Carc. 2, H351; Aquatic Chronic 2, H411

Index number: 612-016-00-0 Reg-No.: 01-2119950342-44

(Contd. on page 2)



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

	(C	ontd. of page 1
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg-No.: 01-2119539582-35		5-10%
CAS: 128-37-0 EINECS: 204-881-4 Reg-No.: 01-2119555270-46 01-2119565113-46		0,1-1%
CAS: 68084-48-0 EINECS: 268-439-2 Reg-No.: 01-2120784744-41	Copper(2+) neodecanoate Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302	0,1-1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

· Components: Cobalt-Polymer

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information: Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

No further relevant information available.

· After skin contact: Immediately remove contaminated clothing

· After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate

medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 2)

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed.

While using do not eat, drink or smoke.

· Information about fire - and

explosion protection:

No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage: · Requirements to be met by Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Store away from peroxide.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about

storage conditions:

Keep container tightly sealed.

Storage in a collecting room is required.

· Recommended storage temperature (To maintain

quality):

+5 +30 °C

Storage class: 10-13

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

121-69-7 N,N-dimethylaniline

WEL (Great Britain) Short-term value: 50 mg/m³, 10 ppm

Long-term value: 25 mg/m³, 5 ppm

Sk

107-41-5 2-methylpentane-2,4-diol

WEL (Great Britain) | Short-term value: 123 mg/m³, 25 ppm

Long-term value: 123 mg/m³, 25 ppm

128-37-0 Butylated hydroxytoluene

WEL (Great Britain) Long-term value: 10 mg/m³

·DNELs

121-69-7 N,N-dimethylaniline

DNEL Longterm System 2,988 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 3,406 mg/m3 (Worker)

107-41-5 2-methylpentane-2,4-diol

DNEL Longterm System | 42 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 44,4 mg/m3 (Worker)

128-37-0 Butylated hydroxytoluene

DNEL Longterm System 0,5 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 1,76 mg/m3 (Worker)

· PNECs

121-69-7 N,N-dimethylaniline

PNEC Marinewater sed 4,942 mg/kg sed dw (-) **PNEC Freshwater** 0,023 mg/l (AF 100) PNEC Freshwater sed 4,942 mg/kg sed dw (-) PNEC Soil 1,906 mg/kg soil dw (-) PNEC STP 5,948 mg/l (AF 10) **PNEC Marinewater** 0,002 mg/l (AF 1.000)

(Contd. on page 4)



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 3)

107-41-5 2-methylpentane-2,4-diol

PNEC Marinewater sed PNEC Freshwater sed PNEC Freshwater sed PNEC Soil PNEC STP 20,429 mg/l (AF 1.000) 1,59 mg/kg sed dw (-) 0,066 mg/kg soil dw (-) 20 mg/l (AF 10) PNEC Marinewater 0,043 mg/l (AF 10.000)

128-37-0 Butylated hydroxytoluene

PNEC Marinewater sed | 0,046 mg/kg sed dw (-) |
PNEC Freshwater | 0,000199 mg/l (AF 1.000) |
PNEC Seawater | 0,00002 mg/l (AF 10.000) |
PNEC Freshwater sed | 0,458 mg/kg sed dw (-) |
PNEC Soil | 0,054 mg/kg soil dw (-) |
PNEC STP | 0,017 mg/l (AF 100)

• Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

• Hand protection Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Colour:

Odour: Colour: C

Melting point/freezing point:
 Boiling point or initial boiling point and boiling range

· Boiling point or initial boiling point and boiling range · Flammability Red

Characteristic Not determined. Undetermined. Not applicable. Not applicable.

(Contd. on page 5)



Version: 4 (replaces version 3) Printing date 04.01.2024 Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 4)

· Lower and upper explosion limit	
Lower:	Not determined.
· Upper:	Not determined.
Flash point:	94 °C

Decomposition temperature: Not determined. pН Not determined.

Viscosity:

Kinematic viscosity Not determined. Dynamic at 20 °C: 73 mPas

· Solubility

· water: Undetermined. Partition coefficient n-octanol/water (log value) not determined · Vapour pressure: Not determined. Density and/or relative density Density at 20 °C: 0,96 g/cm³ Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

Appearance:

· Form: Fluid · Important information on protection of health and environment,

and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in	
contact with water	Void

Oxidising liquids Void Void · Oxidising solids · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: No hazardous decomposition products if used and stored according to specifications.

Emergency procedures will vary depending on conditions. The customer should have an emergency Additional information:

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 5) · LD/LC50 values relevant for classification: 121-69-7 N,N-dimethylaniline LD50 951 mg/kg (rattus) Dermal LD50 1.690 mg/kg (cuniculosus) 107-41-5 2-methylpentane-2,4-diol LD50 >2.000 mg/kg (rattus) Dermal LD50 >2.000 mg/kg (cuniculosus) 128-37-0 Butylated hydroxytoluene LD50 >2.000 mg/kg (rattus) Dermal LD50 >2.000 mg/kg (cuniculosus)

· Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met. Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties 128-37-0 Butylated hydroxytoluene List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	xicity:
121-69-7 N,	N-dimethylaniline
EC50 / 72h 22 mg/l (alga)	
LC50 / 96h 53,7 mg/l (piscis)	
107-41-5 2-methylpentane-2,4-diol	
LC50 / 96h 8.510 mg/l (gambusia affinis)	
128-37-0 Bu	utylated hydroxytoluene
LC0 /96h	>0,57 mg/l (piscis)
EC50 / 48h	0,61 mg/l (daphnia magna)
IC50 / 72h	>0,4 mg/l (alga)

- 12.2 Persistence and degradability
- · Degree of elimination:

20grou or	
· Classification:	
121-69-7 N,N-dimethylaniline	
Degradation (Readily biodegradable)	
107-41-5 2-methylpentane-2,4-diol	
Degradation (Readily biodegradable) (OECD 301 F)	
128-37-0 Butylated hydroxytoluene	
Degradation (Not readily biodegradable)	
40.2 Biogrammulativa matematical	

12.3 Bioaccumulative potential

Partition	coefficient: nOctanol/water: [Log Kow]	
121-69-7	N,N-dimethylaniline	1,17 (38°C)
107-41-5	2-methylpentane-2,4-diol	< 1
128-37-0	Butylated hydroxytoluene	5,1
67-56-1	methanol	-0,77 (20°C)

128-37-0 Butylated hydroxytoluene

BCF 1.277 12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

(Contd. on page 7)



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 6)

12.6 Endocrine disrupting

properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation:

This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMC	O instruments Not applicable.
· Transport/Additional information:	No dangerous good according the regulation of transport.
· ADR	
· RID / GGVSEB:	like ADR

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances

- ANNEX I None of the ingredients is listed.

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

MT -



Printing date 04.01.2024 Version: 4 (replaces version 3) Revision: 20.12.2022

Trade name: PERGAQUICK CP24 A

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

version:

· Abbreviations and acronyms:

3 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

·* Data compared to the previous version altered.

MT -