

Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN A-40 KP · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. C H242 Heating may cause a fire. H319 Causes serious eye irritation. Eve Irrit. 2 Skin Sens. 1 H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. Repr. 2 STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word

· Hazard-determining

components of labelling:

4-hydroxy-4-methylpentan-2-one

Danger

2,4-Pentadione, peroxide tert-butyl perbenzoate

· Hazard statements

H242 Heating may cause a fire. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

P210 · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines). Keep only in original packaging.

P234 Wash thoroughly after handling. P264

Wear protective gloves/protective clothing/eye protection/face protection/hearing P280

protection.

P305+P351+P338 F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +25°C. Keep cool.

P420 Store separately.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Additional information: Product contains: Reportable explosives precursors. Making available, introduction, possession and use

according to Regulation (EU) 2019/1148, Article 9.

2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

(Contd. on page 2)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 1)

Determination of endocrinedisrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3 2 Mixtures

Dangerous components:		
CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Repr. 2, H361d; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	40-60%
CAS: 13784-51-5 EINECS: 237-438-9 Reg-No.: 01-2119965139-28	2,4-Pentadione, peroxide Alternative CAS number: 37187-22-7 Org. Perox. D, H242; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-30%
CAS: 614-45-9 EINECS: 210-382-2 Reg-No.: 01-2119513317-46	tert-butyl perbenzoate Org. Perox. C, H242; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-10%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: $C \ge 70$ % Skin Corr. 1B; H314: 50 % $\le C < 70$ % Skin Irrit. 2; H315: 35 % $\le C < 50$ % Eye Dam. 1; H318: $C \ge 8$ % Eye Irrit. 2; H319: 5 % $\le C < 8$ % STOT SE 3; H335: $C \ge 35$ % Ox. Liq. 1; H271: $C \ge 70$ % Ox. Liq. 2; H272: 50 % $\le C < 70$ %	1-5%
CAS: 123-54-6 EINECS: 204-634-0 Index number: 606-029-00-0 Reg-No.: 01-2119458968-15	pentane-2,4-dione Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302	1-2,5%
CAS: 102-82-9 EINECS: 203-058-7 Reg-No.: 01-2119474898-14	tributylamine Acute Tox. 3, H311; Acute Tox. 1, H330; Acute Tox. 4, H302; Skin Irrit. 2, H315	≤0,1%

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

· After eye contact:

Additional information:

Take care of personal protection for the first aider.

For the wording of the listed hazard phrases refer to section 16.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After swallowing: 4.2 Most important symptoms Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. If symptoms persist consult doctor.

and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases.

(Contd. on page 3)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

Additional information Cool endangered receptacles with water spray.
 Self-protection first!

(Contd. of page 2)

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

 $\dot{\text{Soak}}$ up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

Avoid contact with skin and eyes.

While using do not eat, drink or smoke.

Avoid shock and friction.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.

Prevent impact and friction.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from contamination.

(Contd. on page 4)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 3)

Storage in a collecting room is required.

· Recommended storage temperature (To maintain

quality):

+5 +25 °C 5.2

Storage class:

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

o. i control paramete	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
· Ingredients with limit values that require monitoring at the workplace:	
123-42-2 4-hydroxy-4-methylpentan-2-one	
WEL (Great Britain) S	Short-term value: 362 mg/m³, 75 ppm
`	_ong-term value: 241 mg/m³, 50 ppm
7722 94.4 hydrogon paravide colution	

7722-84-1 hydrogen peroxide solution

WEL (Great Britain) | Short-term value: 2,8 mg/m³, 2 ppm

Long-term value: 1,4 mg/m³, 1 ppm

123-42-2 4-hydroxy-4-methylpentan-2-one

Dermal	DNEL Longterm System	467 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	32,6 mg/m3 (Worker)

13784-51-5 2,4-Pentadione, peroxide

Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	4,41 mg/m3 (Worker)

614-45-9 tert-butyl perbenzoate

Dermal	DNEL Longterm System	17,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	24,7 mg/m3 (Worker)

7722-84-1 hydrogen peroxide solution

Inhalative | DNEL Longterm Local | 1,4 mg/m3 (Worker)

123-54-6 pentane-2,4-dione

Dermal	DNEL Longterm System	12 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	84 mg/m3 (Worker)

102-82-9 tributylamine

102-02-5 (Tibutyiaiiiiie	
Inhalative	DNEL Acute Systemic	10,6 mg/m3 (Worker)
	DNEL Longterm System	5,3 mg/m3 (Worker)
	DNEL Longterm Local	15,2 mg/m3 (Worker)

· PNECs

123-42-2 4-hydroxy-4-methylpentan-2-one

PNEC Marinewater sec	d 0,74 mg/kg sed dw
PNEC Freshwater	2 mg/l (AF 50)
PNEC Freshwater sed	7,4 mg/kg sed dw
PNEC Soil	0,31 mg/kg soil dw
PNEC STP	100 mg/l (AF 10)
PNFC Marinewater	0.2 mg/L (AF 500)

13784-51-5 2,4-Pentadione, peroxide

PNEC Marinewater sed	0,153 mg/kg sed dw (-)
PNEC Freshwater	0,17 mg/l (AF 10)
PNEC Freshwater sed	1,53 mg/kg sed dw (-)
PNEC Soil	0,2 mg/kg soil dw (-)
PNEC STP	6,2 mg/l (AF 10)
PNEC Marinewater	0,017 mg/l (AF 100)

614-45-9 tert-butyl perbenzoate

PNEC Marinewater sed	0,028 mg/kg sed dw
PNEC Freshwater	0,01 mg/l (AF 10)
PNEC Freshwater sed	0,28 mg/kg sed dw
PNEC Soil	0,049 mg/kg soil dw
PNEC STP	0,6 mg/l (AF 10)
PNEC Marinewater	0,00101 mg/l (AF 100)

(Contd. on page 5)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 4) 7722-84-1 hydrogen peroxide solution PNEC Marinewater sed 0,047 mg/kg sed dw 0,013 mg/l (AF 50) PNEC Freshwater PNEC Freshwater sed 0,047 mg/kg sed dw PNFC Soil 0,002 mg/kg soil dw PNEC STP 4,66 mg/l (AF 100) **PNEC Marinewater** 0,013 mg/l (AF 50) 123-54-6 pentane-2,4-dione PNEC Marinewater sed 0,191 mg/kg sed dw PNFC Freshwater 0,2 mg/l (AF 50) PNFC Freshwater sed 1,909 mg/kg sed dw PNEC Soil 0,193 mg/kg soil dw (-) PNEC STP 1,32 mg/l (AF 10) **PNEC Marinewater** 0,02 mg/l (AF 500) 102-82-9 tributylamine PNEC Marinewater sed | 3,59 mg/kg sed dw PNFC Freshwater 0,008 mg/l (AF 1.000) 35,85 mg/kg sed dw PNFC Freshwater sed PNEC Soil 7,17 mg/kg soil dw PNEC STP 100 mg/l (AF 1)

· Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

PNEC Marinewater

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

0,0008 mg/l (AF 10.000)

General protective and

The usual precautionary measures are to be adhered to when handling chemicals. hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eves and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

· Eye/face protection



Tightly sealed goggles

(Contd. on page 6)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Fluid

Colourless

Characteristic

Not applicable.

Not applicable.

May cause fire.

Not determined.

Not determined.

+60 °C (SADT)

Not determined.

Undetermined.

not determined Not determined.

Not determined.

Not determined.

1,08 g/cm³

Mixture is non-soluble (in water).


> SADT

48 mPas

Not determined.

Trade name: PEROXAN A-40 KP

· Body protection:



(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information o	n basic ph	ysical and	chemical	properties
---------------------	------------	------------	----------	------------

General Information

· Physical state · Colour: · Odour:

· Odour threshold: · Melting point/freezing point:

· Boiling point or initial boiling point and boiling range

· Flammability

Lower and upper explosion limit · Lower:

· Upper: Flash point:

Decomposition temperature:

· pH

Viscosity:

· Kinematic viscosity · Dynamic at 20 °C:

Solubility

· water:

· Partition coefficient n-octanol/water (log value)

· Vapour pressure:

Density and/or relative density

Density at 20 °C: Relative density

· Vapour density

Not determined.

Fluid

· 9.2 Other information

· Appearance:

· Important information on protection of health and environment,

and on safety.

Ignition temperature:

· Explosive properties:

· Change in condition · Evaporation rate

Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

Product is not selfigniting.

Not determined.

Information with regard to physical hazard classes

· Explosives Flammable gases · Aerosols

· Oxidising gases · Gases under pressure Flammable liquids

Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids

Pyrophoric solids · Self-heating substances and mixtures

Substances and mixtures, which emit flammable gases in contact with water

· Oxidising liquids Oxidising solids · Organic peroxides

· Corrosive to metals · Desensitised explosives

Active oxygen

Other safety characteristics

Void

Void Void

Void Void

Void Void Void

Void Void Void

> Void Void Void

Heating may cause a fire.

Void Void

ca. 4,5 %

(Contd. on page 7)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 6)

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

10.4 Conditions to avoid · 10.5 Incompatible materials:

Self-accelerating decomposition at SADT. No further relevant information available.

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· LD/LC50 values relevant for classification:

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. Acute toxicity

	123-42-2 4-hydroxy-4-methylpentan-2-one			
	Oral	LD50	3.002 mg/kg (rattus)	
	13784-51-5 2,4-Pentadione, peroxide			
	Oral	LD50	>2.000 mg/kg (rattus)	
7				

614-45-9 tert-butyl perbenzoate

Orai	LDSU	4.000 mg/kg (railus)
Dermal	LD50	3.817 mg/kg (rattus)
Inhalative	LC100 4h	4,9 mg/l (rattus)
	LC0 / 4h	1,01 mg/l (rattus)

123-54-6 pentane-2,4-dione

Oral	LD50	575 mg/kg (rattus)
Dermal	LD50	790 mg/kg (rattus)
Inhalative	LC50 / 4h	5,1 mg/l (rattus)

102-82-9 tributylamine

	•	
Oral	LD50	540 mg/kg (rattus)
Dermal	LD50	250 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin

sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Suspected of damaging the unborn child. STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

 Endocrine disrupting properties None of the ingredients is listed.



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

13784-51-5 2,4-Pentadione, peroxide

EC50 / 72h 5,4 mg/l (alga (Süsswasser))

LC50 / 96h 67,7 mg/l (fish)

EC50 / 48h 7,1 mg/l (daphnia)

123-54-6 pentane-2,4-dione

LC50 / 96h | 72 mg/l (oncorhynchus mykiss)

EC50 / 48h | 75 mg/l (daphnia)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

123-42-2 4-hydroxy-4-methylpentan-2-one

Degradation (Readily biodegradable) (OECD 301 A)

13784-51-5 2,4-Pentadione, peroxide

Degradation (Readily biodegradable) (OECD 301 D)

614-45-9 tert-butyl perbenzoate

Degradation (Readily biodegradable) (OECD 301 D)

7722-84-1 hydrogen peroxide solution

Degradation (Readily biodegradable)

123-54-6 pentane-2,4-dione

Degradation (Readily biodegradable) (OECD 301 C)

102-82-9 tributylamine

Degradation (Readily biodegradable) (OECD 301 B)

12.3 Bioaccumulative potential

· Partition o	· Partition coefficient: nOctanol/water: [Log Kow]				
	4-hydroxy-4-methylpentan-2-one	-0,09 (20°C)			
13784-51-5	2,4-Pentadione, peroxide	1,1 (20°C)			
614-45-9	tert-butyl perbenzoate	3 (25°C)			
7722-84-1	hydrogen peroxide solution	-1,57 (20°C)			
123-54-6	pentane-2,4-dione	0,68 (20°C)			
102-82-9	tributylamine	3,34 (25 °C)			

· Bioconcentration factor (BCF)

102-82-9 tributylamine

BCF 7,3

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT:

· vPvB: · 12.6 Endocrine disrupting

properties

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

- 12.7 Other adverse effects
- · Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

The product does not contain substances with endocrine disrupting properties.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)number.

(Contd. on page 9)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 8)

Uncleaned packaging:

· Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3103

· 14.2 UN proper shipping name

· ADR UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL

PEROXYBENZOATE, ACETYL ACETONE PEROXIDE) ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL

PEROXYBENZOATE, ACETYL ACETONE PEROXIDE)

· 14.3 Transport hazard class(es)

· ADR



· IMDG, IATA

5.2 (P1) Organic peroxides. Class 5.2

· Label

· IMDG, IATA



· Class 5.2 Organic peroxides.

· Label 5.2

· 14.4 Packing group · ADR, IMDG, IATA Void

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Organic peroxides.

· Hazard identification number (Kemler code): · Stowage Category

· Stowage Code SW1 Protected from sources of heat. · Segregation Code SG35 Stow "separated from" SGG1-acids

SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· IMDG

· Limited quantities (LQ) 25 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category Tunnel restriction code

RID / GGVSEB: like ADR

· Limited quantities (LQ) 25 ml

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances

- ANNEX I None of the ingredients is listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

(Contd. on page 10)



Printing date 04.04.2024 Version: 7 (replaces version 6) Revision: 15.02.2023

Trade name: PEROXAN A-40 KP

(Contd. of page 9)

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for

the application of upper-tier

200 t requirements

REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

Version number of previous

version:

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Ox. Liq. 1: Oxidizing liquids – Category 1 Org. Perox. C: Organic peroxides – Type C/D Org. Perox. D: Organic peroxides – Type C/D Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Ird. 2: Skin corrosion/irritation – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

MT -