

Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN BD-Paste 50 SI · Trade name:

· CAS Number: 133-14-2 205-094-9 · EC number: Registration number: 01-2119965137-32

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire.

Skin Sens. 1 H317 May cause an allergic skin reaction. H360 May damage fertility or the unborn child. Repr. 1B

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

· Hazard pictograms

The substance is classified and labelled according to the CLP regulation.





GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining

components of labelling: di-2,4-dichlorobenzoyl peroxide Hazard statements H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child. · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines). P234

Keep only in original packaging.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P405 Store locked up. P410 Protect from sunlight.

P411 Store at temperatures not exceeding +30°C.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Restricted to professional users.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PRT· This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII. · vPvB: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Determination of endocrine-

disrupting properties The product does not contain substances with endocrine disrupting properties.

МТ



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.1 Substances

CAS No. Description 133-14-2 di-2,4-dichlorobenzoyl peroxide

Identification number(s)

· EC number: 205-094-9

· Additional information: Bis(2,4-dichlorobenzoyl) peroxide 50%ig in Siloxanes and Siliconee, dimethyl

Impurities and stabilising additives:

CAS: 63148-62-9 Siloxanes and Silicones, dimethyl

Polymer

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms

and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

polychlorinated biphenyls

furan

1,3-dichlorbenzene 2,4-dichlorobenzoic acid

5.3 Advice for firefighters

· Protective equipment: Additional information Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions. protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 2)

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). Avoid contact with skin and eyes. While using do not eat, drink or smoke.

Avoid shock and friction.

Information about fire - and explosion protection:

Protect from heat.

Prevent impact and friction.

Keep respiratory protective device available

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· 7.2 Conditions for safe storage, including any incompatibilities

 Storage: Requirements to be met by Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from contamination.

Store under lock and key and out of the reach of children.

Store in a cool place.

Storage in a collecting room is required.

Recommended storage temperature (To maintain

quality):

+5 +30 °C

Storage class:

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace: Not required.

· DNELs

133-14-2 di-2,4-dichlorobenzoyl peroxide

Dermal DNEL Longterm System 10 mg/kg bw/day (Worker)

(Contd. on page 4)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 3)

Inhalative DNEL Longterm System 3,53 mg/m3 (Worker)

· PNECs

133-14-2 di-2,4-dichlorobenzoyl peroxide

PNEC Marinewater sed 0,38 mg/kg sed dw 0,0006 mg/l (AF 50) PNEC Freshwater PNEC Freshwater sed 3,8 mg/kg sed dw PNEC Soil 0,76 mg/kg soil dw PNEC STP 50 mg/l (AF 10) 0,00006 mg/l (AF 500) **PNEC Marinewater**

The lists valid during the making were used as basis. Additional information:

8.2 Exposure controls

Appropriate engineering

controls No further data: see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

· Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information · Colour:

Odour: · Odour threshold:

· Melting point/freezing point: Boiling point or initial boiling point and boiling range · Flammability

Lower and upper explosion limit · Lower:

· Upper: · Flash point: Decomposition temperature: white - yellowish Characteristic

Not determined. Not applicable. Not applicable.

Not applicable.

Not determined. Not determined. Not determined. +60 °C (SADT)

(Contd. on page 5)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 4) · pH Not determined. · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined ·Solubility · water: Undetermined. · Partition coefficient n-octanol/water (log value) not determined · Vapour pressure: Not determined. Density and/or relative density Density at 20 °C: 1,2 g/cm³ · Relative density Not determined. Vapour density Not determined. 9.2 Other information Appearance: · Form: Pasty · Important information on protection of health and environment, and on safety. Ignition temperature: Not determined. **Explosive properties:** Product does not present an explosion hazard. Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

Void

Void

Void

Void

Void

Void

Void

2,1 - 2,2 %

SECTION 10: Stability and reactivity

Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases in

· 10.1 Reactivity

· 10.2 Chemical stability

· Pyrophoric solids

contact with water

Organic peroxides

· Corrosive to metals

· Desensitised explosives

Other safety characteristics

Oxidising liquids

· Oxidising solids

Active oxygen

No further relevant information available.

Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

Heating may cause a fire.

No decomposition if used and stored according to specifications.

Self-accelerating decomposition at SADT.

No further relevant information available.

heavy-metal compounds and amines).

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

· 10.5 Incompatible materials:

Hydrocarbons, carbondioxide and -monoxid.

· 10.6 Hazardous decomposition

products:

polychlorinated biphenyls

furan

1,3-dichlorbenzene

2,4-dichlorobenzoic acid

No hazardous decomposition products if used and stored according to specifications.

(Contd. on page 6)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 5)

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

133-14-2 di-2,4-dichlorobenzoyl peroxide

LD50 >12.000 mg/kg (rattus male)

>2.500 mg/kg (rattus female)

Dermal LD50 >8.000 mg/kg (rabbit)

· Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity May damage fertility or the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

133-14-2 di-2,4-dichlorobenzoyl peroxide

LC50 / 96h |>1.000 mg/l (poecilia reticulata)

EC50 / 48h >100 mg/l (daphnia)

- 12.2 Persistence and degradability
- Degree of elimination:
- · Classification:

133-14-2 di-2,4-dichlorobenzoyl peroxide

Degradation (Evidence for inherent biodegradability.) (OECD 301 D)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

6 (20°C)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII. · vPvB: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

(Contd. on page 7)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 6)

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3106

· 14.2 UN proper shipping name

UN3106 ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-· ADR

DICHLOROBENZOYL PEROXIDE) · IMDG, IATA

ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-DICHLOROBENZOYL

PEROXIDE)

· 14.3 Transport hazard class(es)

· ADR



· Class 5.2 (P1) Organic peroxides.

Label

· IMDG, IATA



Class 5.2 Organic peroxides.

· Label

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards: Not applicable

· 14.6 Special precautions for user Warning: Organic peroxides. Hazard identification number (Kemler code):

D Stowage Category

 Stowage Code SW1 Protected from sources of heat. · Segregation Code SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 500 g Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport category D · Tunnel restriction code

like ADR · RID / GGVSEB:

· IMDG

 Limited quantities (LQ) 500 g Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

· Named dangerous substances

ANNEX I Substance is not listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

(Contd. on page 8)



Printing date 04.04.2024 Version: 12 (replaces version 11) Revision: 14.02.2023

Trade name: PEROXAN BD-Paste 50 SI

(Contd. of page 7)

Qualifying quantity (tonnes) for the application of lower-tier

requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier

200 t requirements

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3, 30, 75

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

version:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International · Abbreviations and acronyms:

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. D: Organic peroxides – Type C/D Skin Sens. 1: Skin sensitisation – Category 1 Repr. 1B: Reproductive toxicity – Category 1B

· * Data compared to the previous version altered.

MT -