


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN BD-Paste 50 SI
- **CAS Number:** 133-14-2
- **EC number:** 205-094-9
- **Registration number:** 01-2119965137-32
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Org. Perox. D H242 Heating may cause a fire.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Repr. 1B H360 May damage fertility or the unborn child.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The substance is classified and labelled according to the CLP regulation.
- **Hazard pictograms** 
GHS02 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** di-2,4-dichlorobenzoyl peroxide
- **Hazard statements** H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
- **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234 Keep only in original packaging.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P405 Store locked up.
P410 Protect from sunlight.
P411 Store at temperatures not exceeding +30°C.
P420 Store separately.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:** Restricted to professional users.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
- **vPvB:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients**3.1 Substances**

- **CAS No. Description** 133-14-2 di-2,4-dichlorobenzoyl peroxide
- **Identification number(s)**
- **EC number:** 205-094-9
- **Additional information:** Bis(2,4-dichlorobenzoyl) peroxide 50%ig in Siloxanes and Siliconee, dimethyl


Impurities and stabilising additives:

CAS: 63148-62-9 Polymer	Siloxanes and Silicones, dimethyl
----------------------------	-----------------------------------

Dangerous components:

CAS: 133-14-2 EINECS: 205-094-9 Reg-No.: 01-2119965137-32	di-2,4-dichlorobenzoyl peroxide Org. Perox. D, H242; Repr. 1B, H360; Skin Sens. 1, H317	40-50%
CAS: 556-67-2 EINECS: 209-136-7 Index number: 014-018-00-1	octamethylcyclotetrasiloxane Flam. Liq. 3, H226; Repr. 2, H361f; Aquatic Chronic 1, H410 (M=10) PBT; vPvB	≤0,05%

SECTION 4: First aid measures**4.1 Description of first aid measures**

- **General information:**  Take care of personal protection for the first aider.

- **After inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment neededTreatment: Symptomatic treatment
No further relevant information available.**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.
polychlorinated biphenyls
furan
1,3-dichlorobenzene
2,4-dichlorobenzoic acid

5.3 Advice for firefighters

- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



— MT —

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Keep receptacles tightly sealed.
 - Store in cool, dry place in tightly closed receptacles.
 - Keep away from heat and direct sunlight.
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
 - Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
 - Do not refill residue into storage receptacles.
 - Restrict the quantity stored at the work place.
 - Use only in well ventilated areas.
 - Before break and at the end of work hands should be thoroughly washed.
 - Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
 - Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
 - Avoid contact with skin and eyes.
 - While using do not eat, drink or smoke.
 - Avoid shock and friction.
- **Information about fire - and explosion protection:**
 - Protect from heat.
 - Prevent impact and friction.
 - Keep respiratory protective device available.
 - Fumes can combine with air to form an explosive mixture.
 -  Wear shoes with conductive soles.
 -  Avoid open flames, sparks, direct sunlight and other sources of ignition.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
 - **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Store only in the original receptacle.
 - Prevent any seepage into the ground.
 - Use only receptacles specifically permitted for this substance/product.
 - **Information about storage in one common storage facility:**
 - Do not store or park organic peroxide together with heavy metal compounds and amines.
 - Store away from foodstuffs, drinks and feeding stuffs.
 - **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
 - Protect from contamination.
 - Store under lock and key and out of the reach of children.
 - Store in a cool place.
 - Storage in a collecting room is required.
 - **Recommended storage temperature (To maintain quality):** +5 +30 °C
 - **Storage class:** 5.2
 - **7.3 Specific end use(s)** No further relevant information available.

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 3)

* SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

Not required.

· DNELs

133-14-2 di-2,4-dichlorobenzoyl peroxide

Dermal	DNEL Longterm System	10 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	3,53 mg/m ³ (Worker)

· PNECs

133-14-2 di-2,4-dichlorobenzoyl peroxide

PNEC Marinewater sediment	0,38 mg/kg sed dw
PNEC Freshwater	0,0006 mg/l (AF 50)
PNEC Freshwater sediment	3,8 mg/kg sed dw
PNEC Soil	0,76 mg/kg soil dw
PNEC Sewage treatment plant	50 mg/l (AF 10)
PNEC Marinewater	0,00006 mg/l (AF 500)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber: 0,7 mm layer thickness, 480 minutes breakthrough time
Butyl rubber (II): 0,47 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (I): 0,4 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (III): 0,2 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (VI): 1,36 mm layer thickness, 480 minutes breakthrough time

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Butyl rubber: 0,7 mm layer thickness, 480 minutes breakthrough time
Butyl rubber (II): 0,47 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (I): 0,4 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (III): 0,2 mm layer thickness, 480 minutes breakthrough time
Nitrile rubber (VI): 1,36 mm layer thickness, 480 minutes breakthrough time

· Eye/face protection



Tightly sealed goggles

(Contd. on page 5)

MT

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 4)

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	white - yellowish
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not determined.
· Decomposition temperature:	+60 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Undetermined.
· Partition coefficient n-octanol/water (log value)	not determined
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1,2 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Not determined.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void
· Other safety characteristics	
· Active oxygen	2,1 - 2,2 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

MT

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.
No decomposition if used and stored according to specifications.
To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** Self-accelerating decomposition at SADT.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **10.6 Hazardous decomposition products:** Hydrocarbons, carbon dioxide and -monoxid.
polychlorinated biphenyls
furan
1,3-dichlorobenzene
2,4-dichlorobenzoic acid
No hazardous decomposition products if used and stored according to specifications.
- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

133-14-2 di-2,4-dichlorobenzoyl peroxide

Oral	LD50	>12.000 mg/kg (rattus male)
		>2.500 mg/kg (rattus female)
Dermal	LD50	>8.000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

540-97-6	Dodecamethylcyclohexasiloxane	List II
541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

- **12.1 Toxicity**

· **Aquatic toxicity:**

133-14-2 di-2,4-dichlorobenzoyl peroxide

LC50 / 96h	>1.000 mg/l (poecilia reticulata)
EC50 / 48h	>100 mg/l (daphnia)

- **12.2 Persistence and degradability**

· **Degree of elimination:**

· **Classification:**

133-14-2 di-2,4-dichlorobenzoyl peroxide

Degradation	(Evidence for inherent biodegradability.) (OECD 301 D)
-------------	--


(Contd. on page 7)

Trade name: **PEROXAN BD-Paste 50 SI**



(Contd. of page 6)

556-67-2 octamethylcyclotetrasiloxane		
Degradation	(Not readily biodegradable) (OECD 310)	
· 12.3 Bioaccumulative potential		
· Partition coefficient: nOctanol/water: [Log Kow]		
133-14-2	di-2,4-dichlorobenzoyl peroxide	6 (20°C)
540-97-6	Dodecamethylcyclohexasiloxane	8,87 (20°C)
541-02-6	Decamethylcyclopentasiloxane	8,07 (20°C)
556-67-2	octamethylcyclotetrasiloxane	6,98 (20°C)
· 12.4 Mobility in soil No further relevant information available.		
· 12.5 Results of PBT and vPvB assessment		
· PBT:	This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.	
· vPvB:	This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.	
· 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.		
· 12.7 Other adverse effects		
· Additional ecological information:		
· General notes:	Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.	

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:** Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3106
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN3106 ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-DICHLOROBENZOYL PEROXIDE) ORGANIC PEROXIDE TYPE D, SOLID (DI-2,4-DICHLOROBENZOYL PEROXIDE)
· 14.3 Transport hazard class(es) · ADR 	5.2 (P1) Organic peroxides. 5.2
· Class · Label	
· IMDG, IATA 	5.2 Organic peroxides. 5.2
· Class · Label	
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Organic peroxides.

(Contd. on page 8)

— MT —

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 7)

· Hazard identification number (Kemler code):	-
· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	500 g
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· RID / GGVSEB:	
	like ADR
· IMDG	
· Limited quantities (LQ)	500 g
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I Substance is not listed.

· Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 30, 75

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0
E-mail: mail@pergan.com

· Version number of previous version: 12

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)

Trade name: **PEROXAN BD-Paste 50 SI**

(Contd. of page 8)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. D: Organic peroxides – Type C/D
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

* Data compared to the
previous version altered.

— MT —