

Safety data sheet
 according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024


Version: 12 (replaces version 11)

Revision: 14.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **PEROXAN BU**
- **CAS Number:** 3457-61-2
- **EC number:** 222-389-8
- **Index number:** 617-007-00-5
- **Registration number:** 01-2119969063-35
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

*** SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Org. Perox. F H242 Heating may cause a fire.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The substance is classified and labelled according to the CLP regulation.
- **Hazard pictograms**


GHS02 GHS07 GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:** tert-butyl alpha,alpha-dimethylbenzyl peroxide
- **Hazard statements** H242 Heating may cause a fire.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
 - P234 Keep only in original packaging.
 - P264 Wash thoroughly after handling.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection.
 - P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
 - P410 Protect from sunlight.
 - P411+P235 Store at temperatures not exceeding +30°C. Keep cool.
 - P420 Store separately.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
- **vPvB:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

Trade name: **PEROXAN BU**

(Contd. of page 1)

* SECTION 3: Composition/information on ingredients

3.1 Substances

CAS No. Description	3457-61-2 tert-butyl alpha,alpha-dimethylbenzyl peroxide
Identification number(s)	
EC number:	222-389-8
Index number:	617-007-00-5

Dangerous components:

CAS: 3457-61-2 EINECS: 222-389-8 Index number: 617-007-00-5 Reg-No.: 01-2119969063-35	tert-butyl alpha,alpha-dimethylbenzyl peroxide Org. Perox. E, H242; Aquatic Chronic 2, H411; Skin Irrit. 2, H315	90-100%
CAS: 98-83-9 EINECS: 202-705-0 Index number: 601-027-00-6	2-phenylpropene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 25 %	1-2,5%
CAS: 98-86-2 EINECS: 202-708-7 Index number: 606-042-00-1	acetophenone Acute Tox. 4, H302; Eye Irrit. 2, H319	1-2,5%
CAS: 75-91-2 EINECS: 200-915-7 Reg-No.: 01-2119446670-40	tert-butyl hydroperoxide Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 2, H351; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Eye Dam. 1; H318: C ≥ 1 % Skin Sens. 1; H317: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	0-1%
CAS: 80-43-3 EINECS: 201-279-3 Index number: 617-006-00-X Reg-No.: 01-2119541688-27	bis(a,a-dimethylbenzyl) peroxide Org. Perox. F, H242; Repr. 1B, H360D; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	0,1-1%

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:



Take care of personal protection for the first aider.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded. Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray. Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures


Keep away from ignition sources.

(Contd. on page 3)




MT

Trade name: **PEROXAN BU**

(Contd. of page 2)

- In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.2 Environmental precautions:**  Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
While using do not eat, drink or smoke.
Avoid shock and friction.
-  Do not smoke.
- **Information about fire - and explosion protection:** Protect from heat.
Prevent impact and friction.
Fumes can combine with air to form an explosive mixture.
-  Wear shoes with conductive soles.
-  Avoid open flames, sparks, direct sunlight and other sources of ignition.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Protect from contamination.
Store in a cool place.
Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** +15 +30 °C
- **Storage class:** 5.2

(Contd. on page 4)

— MT —

Trade name: **PEROXAN BU**

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

98-83-9 2-phenylpropene

IOELV (EU)	Short-term value: 492 mg/m ³ , 100 ppm Long-term value: 246 mg/m ³ , 50 ppm
WEL (Great Britain)	Short-term value: 491 mg/m ³ , 100 ppm Long-term value: 246 mg/m ³ , 50 ppm

· DNELs

98-86-2 acetophenone

Dermal	DNEL Longterm System	0,35 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	1,23 mg/m ³ (Worker)

75-91-2 tert-butyl hydroperoxide

Dermal	DNEL Longterm System	0,21 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	85,2 mg/m ³ (Worker)
	DNEL Acute Local	28,4 mg/m ³ (Worker)
	DNEL Longterm System	2,2 mg/m ³ (Worker)
	DNEL Longterm Local	0,58 mg/m ³ (Worker)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

Oral	DNEL Longterm System	0,4 mg/kg bw/day (General population)
Dermal	DNEL Longterm System	0,8 mg/kg bw/day (Worker) 0,4 mg/kg bw/day (General population)
Inhalative	DNEL Longterm System	5,6 mg/m ³ (Worker) 1,4 mg/m ³ (General population)

· PNECs

98-86-2 acetophenone

PNEC Marinewater sed	0,113 mg/kg sed dw (-)
PNEC Freshwater	0,086 mg/l (AF 1.000)
PNEC Freshwater sed	1,13 mg/kg sed dw (-)
PNEC Soil	0,175 mg/kg soil dw (-)
PNEC STP	34,6 mg/l (AF 10)
PNEC Marinewater	0,009 mg/l (AF 10.000)

75-91-2 tert-butyl hydroperoxide

PNEC Marinewater sed	0,001 mg/kg sed dw
PNEC Freshwater	0,002 mg/l (AF 1.000)
PNEC Seawater	0 mg/l (AF 10.000)
PNEC Freshwater sed	0,006 mg/kg sed dw (-)
PNEC Soil	0,166 mg/kg soil dw (AF 1.000)
PNEC STP	0,17 mg/l (AF 100)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

PNEC Freshwater	0,00234 mg/l (AF 50)
PNEC Freshwater sed	2,24 mg/kg sed dw (-)
PNEC Soil	0,447 mg/kg soil dw (-)
PNEC STP	100 mg/l (AF 10)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**





The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.

(Contd. on page 5)

— MT —

Trade name: **PEROXAN BU**

(Contd. of page 4)

· Respiratory protection:	<p>Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</p>
· Hand protection	<p> Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated. Filter A2 Only use chemical-protective gloves with CE-labelling of category III.  Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</p>
· Material of gloves	<p>Protective gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene</p>
· Penetration time of glove material	<p>The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.</p>
· Eye/face protection	<p> Tightly sealed goggles</p>
· Body protection:	<p> Protective work clothing</p>

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Light yellow
· Odour:	Aromatic
· Odour threshold:	Not determined.
· Melting point/freezing point:	<15 °C
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	Not applicable.
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not determined.
· Decomposition temperature:	ca. +90 °C (SADT)
· pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity	4 mPas
· Dynamic at 20 °C:	Undetermined.
· Solubility	not determined
· water:	Not determined.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	0,94 g/cm³
· Density at 20 °C:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

MT

Trade name: **PEROXAN BU**

(Contd. of page 5)

· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void
· Other safety characteristics	
· Active oxygen	> 6,9 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbon dioxide and -monoxide. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plan in place.

* SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· Acute toxicity	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
3457-61-2 tert-butyl alpha,alpha-dimethylbenzyl peroxide		
Oral	LD50	4.700 mg/kg (rattus)
Dermal	LD50	>2.000 mg/kg (rattus)
Inhalative	LC50	>1,2 mg/l (rattus)
98-83-9 2-phenylpropene		
Oral	LD50	4.900 mg/kg (rattus)
98-86-2 acetophenone		
Oral	LD50	2.081 mg/kg (rattus)
75-91-2 tert-butyl hydroperoxide		
Oral	LD50	805 mg/kg (70%) (rattus)
Dermal	LD50	633 mg/kg (70%) (rabbit)

(Contd. on page 7)

MT

Trade name: **PEROXAN BU**

(Contd. of page 6)

</

SECTION 12: Ecological information

· 12.1 Toxicity

· **Aquatic toxicity:**

75-91-2 tert-butyl hydroperoxide

EC50 / 72h 2,1 mg/l /(70%) (selenastrum capricornutum)

LC50 / 96h 42,3 mg/l /(70%) (pimephales promelas)

EC50 24,3 mg/l /(70%) (activa sludge)

EC50 / 48h 20 mg/l /(70%) (daphnia)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

EC50 / 72h >20 mg/l (algae)

EC50 >1.000 mg/l (activa sludge)

· 12.2 Persistence and degradability

· **Degree of elimination:**

· **Classification:**

3457-61-2 tert-butyl alpha,alpha-dimethylbenzyl peroxide

Degradation (Not readily biodegradable) (OECD 301 F)

98-86-2 acetophenone

Degradation (Readily biodegradable) (OECD 301 C)

75-91-2 tert-butyl hydroperoxide

Degradation (Not readily biodegradable) (OECD 301 D)

80-43-3 bis(a,a-dimethylbenzyl) peroxide

Degradation (Not readily biodegradable) (OECD 301 F)

· 12.3 Bioaccumulative potential

· **Partition coefficient: nOctanol/water: [Log Kow]**

3457-61-2	tert-butyl alpha,alpha-dimethylbenzyl peroxide	4,4 (25°C)
98-86-2	acetophenone	1,65 (20°C)
75-91-2	tert-butyl hydroperoxide	0,85 (30 °C)
80-43-3	bis(a,a-dimethylbenzyl) peroxide	5,6 (25°C)

· **Bioconcentration factor (BCF)**

80-43-3 bis(a,a-dimethylbenzyl) peroxide

BCF 747

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· **PBT:**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

· **vPvB:**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· **Remark:**

Toxic for fish

· **Additional ecological information:**

· **General notes:**

Toxic for aquatic organisms

(Contd. on page 8)


MT

Trade name: **PEROXAN BU**






(Contd. of page 7)

Also poisonous for fish and plankton in water bodies.
Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 - Recommendation  After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- Uncleaned packaging:
 - Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	UN3109
14.2 UN proper shipping name ADR IMDG IATA	UN3109 ORGANIC PEROXIDE TYPE F, LIQUID (tert-BUTYL CUMYL PEROXIDE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE F, LIQUID (tert-BUTYL CUMYL PEROXIDE), MARINE POLLUTANT ORGANIC PEROXIDE TYPE F, LIQUID (tert-BUTYL CUMYL PEROXIDE)
14.3 Transport hazard class(es) ADR   Class Label	5.2 (P1) Organic peroxides. 5.2
IMDG   Class Label	5.2 Organic peroxides. 5.2
IATA  Class Label	5.2 Organic peroxides. 5.2
14.4 Packing group ADR, IMDG	Void
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code Segregation Code	Warning: Organic peroxides. - F-J,S-R D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.

Trade name: **PEROXAN BU**

(Contd. of page 8)

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	125 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· RID / GGVSEB:	like ADR
· IMDG	
· Limited quantities (LQ)	125 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Directive 2012/18/EU	
· Named dangerous substances	
- ANNEX I	Substance is not listed.
· Seveso category	P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES E2 Hazardous to the Aquatic Environment
· Qualifying quantity (tonnes) for the application of lower-tier requirements	50 t
· Qualifying quantity (tonnes) for the application of upper-tier requirements	200 t
· REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3
· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II	
None of the ingredients is listed.	
· REGULATION (EU) 2019/1148	
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))	
None of the ingredients is listed.	
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS	
None of the ingredients is listed.	
· Regulation (EC) No 273/2004 on drug precursors	
None of the ingredients is listed.	
· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	
None of the ingredients is listed.	

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:	Tel: +49 2871 9902-0 E-mail: mail@pergan.com
· Version number of previous version:	11
· Abbreviations and acronyms:	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

(Contd. on page 10)

— MT —

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version: 12 (replaces version 11)

Revision: 14.12.2023

Trade name: **PEROXAN BU**

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. E: Organic peroxides – Type E/F
Org. Perox. F: Organic peroxides – Type E/F
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· * Data compared to the
previous version altered.

— MT —