

Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN CND-50 WN-A IBC

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance /

the mixture

Reaction initiator

 \cdot 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

No further relevant information available.

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from:

Environment protection / Security of labour Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. F H242 Heating may cause a fire. Carc. 1B H350 May cause cancer.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS08

· Signal word Danger

· Hazard-determining

components of labelling:

methanol

1-methyl-1-phenylethyl peroxyneodecanoate

Hazard statements H242 Heating may cause a fire.

H350 May cause cancer.

H370 Causes damage to the central nervous system and the visual organs.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P405 Store locked up. P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding -15°C. Keep cool.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Restricted to professional users.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Determination of endocrine-

disrupting propertiesThe product does not contain substances with endocrine disrupting properties.

— MT -



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 26748-47-0 EINECS: 247-956-7 Reg-No.: 01-2120767069-44	1-methyl-1-phenylethyl peroxyneodecanoate Org. Perox. D, H242	40-50%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg-No.: 01-2119433307-44	methanol Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	10-20%
CAS: 9005-65-6	Polyoxyethylensorbitanmonooleate Aquatic Chronic 3, H412	1-2,5%
CAS: 98-82-8 EINECS: 202-704-5 Index number: 601-024-00-X Reg-No.: 01-2119473983-24	Cumene Flam. Liq. 3, H226; Carc. 1B, H350; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335	0,1-1%
Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 General information:

hours after the accident.

Take care of personal protection for the first aider.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

persist.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

No further relevant information available.

· After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Call for a doctor immediately. 4.2 Most important symptoms

and effects, both acute and

delayed

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from

the substance or mixture Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.

· Additional information Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Dilute with plenty of water.

(Contd. on page 3)



(Contd. of page 2)

Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

X

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight.

Protect from contamination.

Store under lock and key and out of the reach of children.

Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

-25 -15 °C

· Storage class:

5.2

(Contd. on page 4)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

· 7.3 Specific end use(s) No further relevant information available (Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

6.1 Control parame		
· Ingredients with limit values that require monitoring at the workplace:		
67-56-1 methanol		
IOELV (EU)	Long-term value: 260 mg/m³, 200 ppm Skin	
WEL (Great Britain)	Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk	
98-82-8 Cumene		
IOELV (EU) Short-term value: 250 mg/m³, 50 ppm Long-term value: 50 mg/m³, 10 ppm Skin		
WEL (Great Britain)	Short-term value: 250 mg/m³, 50 ppm Long-term value: 125 mg/m³, 25 ppm Sk	
DNELs		
26748-47-0 1-methyl-1-phenylethyl peroxyneodecanoate		
Dermal DNEL Lo	ngterm System 1,4 mg/kg bw/day (Worker)	
Inhalative DNEL Lo	ngterm System 4,93 mg/m3 (Worker)	
67-56-1 methanol		
Dermal DNEL Lo	ngterm System 20 mg/kg bw/day (Worker)	
Inhalative DNEL Longterm System 130 mg/m3 (Worker)		
98-82-8 Cumene		
Dermal DNEL Longterm System 15,4 mg/kg bw/day (Worker)		
Inhalative DNEL Lo	ngterm System 100 mg/m3 (Worker)	
PNECs		
26748-47-0 1-methy	I-1-phenylethyl peroxyneodecanoate	
PNEC Marinewater sed 0,00376 mg/kg sed dw (-)		
PNEC Freshwater	0,0038 mg/l (AF 1.000)	
PNEC Freshwater se	ed 0,0376 mg/kg sed dw (-)	
PNEC Soil	0,00529 mg/kg soil dw (-)	
PNEC STP	1,4 mg/l (AF 10)	
PNEC Marinewater	0,00038 mg/l (AF 10.000)	

98-82-8 Cumene

PNEC Marinewater sed 0,322 mg/kg sed dw (-) **PNEC Freshwater** 0,035 mg/l (AF 10) PNEC Freshwater sed 3,22 mg/kg sed dw (-) PNEC Soil 0,624 mg/kg soil dw (-) PNEC STP 200 mg/l (AF 10) **PNEC Marinewater** 0,004 mg/l (AF 100)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

(Contd. on page 5)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

(Contd. of page 4) · Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

Only use chemical-protective gloves with CE-labelling of category III. · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Whitish · Odour: Characteristic

Odour threshold: Not determined. · Melting point/freezing point: Not applicable. · Boiling point or initial boiling point and boiling range Not applicable. · Flammability Not applicable.

· Lower and upper explosion limit

· Lower: · Upper:

· Flash point: Decomposition temperature:

Ha · Viscosity:

· Kinematic viscosity

Dynamic:

·Solubility · water:

· Form:

Partition coefficient n-octanol/water (log value)

· Vapour pressure:

· Density and/or relative density

 Relative density · Vapour density

Density at 20 °C:

1,00 g/cm³ Not determined Not determined. No further relevant information available.

· 9.2 Other information · Appearance:

emulsion

· Important information on protection of health and environment,

and on safety.

Ignition temperature:

· Explosive properties:

· Change in condition

· Evaporation rate

· Information with regard to physical hazard classes

Explosives

Flammable gases

Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

Not determined.

Not determined.

Not determined.

Not determined.

Not determined.

Emulsifiable.

not determined

Not determined.

Not determined

+5 °C (SADT) Not determined.

Void

Void

(Contd. on page 6)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

(Contd. of page 5)

	(CCI	itu. Oi page
· Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable gases	s in	
contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
Organic peroxides	Heating may cause a fire.	
Corrosive to metals	Void	
Desensitised explosives	Void	
Other safety characteristics		
Active oxygen	2,6 - 2,7 %	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

 Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-

accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT.

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

• Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity
 Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:			
26748-47	26748-47-0 1-methyl-1-phenylethyl peroxyneodecanoate			
Oral	LD50	5.126 mg/kg (rattus)		
Dermal	LD50	>7.940 mg/kg (rabbit)		
67-56-1 m	67-56-1 methanol			
Oral	LD50	1.187 mg/kg (rattus)		
98-82-8 Cumene				
Oral	LD50	2.260 mg/kg (rattus)		
Dermal	LD50	12.300 mg/kg (rabbit)		
Inhalative		24,7 mg/l (mouse)		

• Skin corrosion/irritation Based on available data, the classification criteria are not met.
• Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Germ cell mutagenicity

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

· Carcinogenicity May cause cancer.

Reproductive toxicity
STOT-single exposure
STOT-repeated exposure
STOT-repeated exposure
STOT-repeated exposure
STOT-repeated exposure
STOT-repeated exposure
Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-56-1 methanol

EC50 / 72h | 22.000 mg/l (algae)

- 12.2 Persistence and degradability
- Degree of elimination:
- · Classification:

26748-47-0 1-methyl-1-phenylethyl peroxyneodecanoate

Degradation (Readily biodegradable) (OECD 301 B)

67-56-1 methanol

Degradation (Readily biodegradable)

98-82-8 Cumene

Degradation (Readily biodegradable)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]			
26748-47-0 1-methyl-1-phenylethyl peroxyneodecanoate	3,9 (20°C)		
67-56-1 methanol	-0,77 (20°C)		
98-82-8 Cumene	3,55 (20°C)		
79-20-9 methyl acetate	0,18 (20°C)		

· Bioconcentration factor (BCF)

67-56-1 methanol

BCF <10

· 12.4 Mobility in soil No further relevant information available

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

· Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)number.

· Uncleaned packaging:

Recommendation:

Recommended cleansing

agents:

This material and its container must be disposed of as hazardous waste.

Water, if necessary together with cleansing agents.

MT -

(Contd. on page 8)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN number or ID number · ADR, IMDG	UN3119
· 14.2 UN proper shipping name	
· ADR · IMDG	UN3119 ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLED (CUMYLPEROXYNEODECANOATE) ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLEI
AA 2 Transport harrond along/as)	(CUMYLPEROXYNEODECANOATE)
14.3 Transport hazard class(es)	
· ADR	
· Class	5.2 (P2) Organic peroxides.
· Label	5.2
· IMDG	
· Class	5.2 Organic peroxides.
Label	5.2
·IATA	
· Class	X
Label	X
· 14.4 Packing group · ADR, IMDG	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Organic peroxides.
· Hazard identification number (Kemler code): · Stowage Category	- D
· Stowage Code	SW1 Protected from sources of heat.
-	SW3 Shall be transported under temperature control.
Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instr	
· Transport/Additional information:	типотто постаррновано.
· ADR	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0
· Transport category	Not permitted as Excepted Quantity
Tunnel restriction code	D
· RID / GGVSEB:	no admission
· IMDG	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	Not permitted as Excepted Quantity
· IATA · Remarks:	no admission
· Control temperature:	-15 °C
Emergency temperature:	-13 ℃ -5 °C

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances
- ANNEX I None of the ingredients is listed.

(Contd. on page 9)



Printing date 03.04.2024 Version: 10 (replaces version 9) Revision: 27.11.2023

Trade name: PEROXAN CND-50 WN-A IBC

50 t

(Contd. of page 8)

· Seveso category H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

· Qualifying quantity (tonnes) for the application of lower-tier

requirements

Qualifying quantity (tonnes) for the application of upper-tier requirements

REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 28, 69

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

9

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the · Abbreviations and acronyms:

International Transport of Dangerous Goods by Rail)
ADR: Accord relatif au transport international des marci nandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. D: Organic peroxides – Type C/D
Org. Perox. F: Organic peroxides – Type E/F
Acute Tox. 3: Acute toxicity – Category 3
Carc. 18: Carcinogenicity – Category 1B
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Acg. Tox 1: Aspiration hazard – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

МТ