

Version: 7 (replaces version 6)

Revision: 27.11.2023

• 7

The Peroxide Company

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN CU-40 M

· Trade name:	PEROXAN CU-40 M
· 1.2 Relevant identified uses of the	ne substance or mixture and uses advised against No further relevant information available.
 Application of the substance / the mixture 	Reaction initiator For industrial use
• 1.3 Details of the supplier of the • Manufacturer/Supplier:	safety data sheet PERGAN GmbH Hilfsstoffe für industrielle Prozesse Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50
 Further information obtainable from: 1.4 Emergency telephone number: 	Environment protection / Security of labour Qualified person: E-mail: msds@pergan.com - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

SECTION 2: Hazards	Jentification		
 2.1 Classification of the Classification according 	ubstance or mixture to Regulation (EC) No 1272/2008		
Org. Perox. F H242	leating may cause a fire.		
Acute Tox. 4 H302 Harmful if swallowed.			
Acute Tox. 4 H312 Harmful in contact with skin.			
	Acute Tox. 3 H331 Toxic if inhaled.		
	Causes severe skin burns and eye damage.		
•	Causes serious eye damage.		
Carc. 1B H350	flay cause cancer.		
STOT SE 3 H335	<i>I</i> ay cause respiratory irritation.		
STOT RE 2 H373	<i>I</i> ay cause damage to organs through prolonged or repeated exposure.		
	oxic to aquatic life with long lasting effects.		
· ·			
2.2 Label elements Labelling according to			
Regulation (EC) No 12	/2008 The product is classified and labelled according to the CLP regulation.		
· Hazard pictograms			
nazara pietogranie			
	$ \forall \lor \lor \lor \lor \lor \lor $		
	GHS02 GHS05 GHS06 GHS08 GHS09		
· Signal word	Danger		
 Hazard-determining 			
components of labelli			
	Cumene		
	2-Phenyl-2-propanol		
 Hazard statements 	H242 Heating may cause a fire.		
	H302+H312 Harmful if swallowed or in contact with skin.		
	H331 Toxic if inhaled.		
	H314 Causes severe skin burns and eye damage. H350 May cause cancer.		
	H350 May cause cancer. H335 May cause respiratory irritation.		
	H373 May cause damage to organs through prolonged or repeated exposure.		
	H411 Toxic to aquatic life with long lasting effects.		
· Precautionary stateme			
· · · · · · · · · · · · · · · · · · ·	smoking.		
	P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and		
	accelerators (e. g. heavy metal compounds and amines).		
	P234 Keep only in original packaging.		
	P243 Take action to prevent static discharges.		
	P264 Wash thoroughly after handling.		
	P273 Avoid release to the environment.		
	P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing		
	protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with		
	water [or shower].		
	(Contd. on page 2)		
	(

— MT —

Printing date 03.04.2024

Version: 7 (replaces version 6)

Revision: 27.11.2023

•)

The Peroxide Company

Trade name: PEROXAN CU-40 M

		(Contd. of page	
		IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
	P310	Immediately call a POISON CENTER/doctor.	
	P362+P364	Take off contaminated clothing and wash it before reuse.	
	P405	Store locked up.	
	P410	Protect from sunlight.	
	P411+P235	Store at temperatures not exceeding +30°C. Keep cool.	
	P420	Store separately.	
		Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Additional information:	Restricted to profe	ssional users.	
2.3 Other hazards	•		
· Results of PBT and vPvB asses	sment		
· PBT:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
· Determination of endocrine-		3	
disrupting properties	The product does not contain substances with endocrine disrupting properties.		

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

CAS: 80-15-9	α,α -dimethylbenzyl hydroperoxide	40-50%
	Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 %	-
CAS: 98-82-8 EINECS: 202-704-5 Index number: 601-024-00-X Reg-No.: 01-2119473983-24		2,5-5%
CAS: 617-94-7 EINECS: 210-539-5	2-Phenyl-2-propanol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-2,5%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measured	ures
· General information:	Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Remove breathing equipment only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration. Take care of personal protection for the first aider.
· After inhalation:	Supply fresh air or oxygen; call for doctor. In case of unconsciousness place patient stably in side position for transportation. Take affected persons into fresh air and keep quiet.
After skin contact:	Immediately wash with water and soap and rinse thoroughly. Immediately remove contaminated clothing.
 After eye contact: After swallowing: 	Rinse opened eye for several minutes under running water. Then consult a doctor. Call for a doctor immediately. Drink plenty of water and provide fresh air. Call for a doctor immediately.
 4.2 Most important symptoms and effects, both acute and delayed 4.3 Indication of any immediate medical attention and special 	No further relevant information available.
treatment needed	No further relevant information available.

(Contd. on page 3)

Printing date 03.04.2024

Version: 7 (replaces version 6)

Revision: 27.11.2023

The Peroxide Company

Trade name: PEROXAN CU-40 M

(Contd. of page 2)

SECTION 5: Firefighting measures

 5.1 Extinguishing media 	
· Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· 5.2 Special hazards arising from	
the substance or mixture	Under certain fire conditions, traces of other toxic gases cannot be excluded. Hydrocarbons, carbondioxide and -monoxid.
5.3 Advice for firefighters	
· Protective equipment:	Mouth respiratory protective device.
	Do not inhale explosion gases or combustion gases.
 Additional information 	Cool endangered receptacles with water spray.
	Self-protection first

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures 	Keep away from ignition sources. In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away.
· 6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
¹ 6.3 Methods and material for	
containment and cleaning up:	Dispose contaminated material as waste according to section 13.
	Ensure adequate ventilation.
	Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before disposal.
	Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
· 6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.
	In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe	
handling	Keep away from heat and direct sunlight.
•	Ensure good ventilation/exhaustion at the workplace.
	Open and handle receptacle with care.
	Prevent formation of aerosols.
	Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
	Do not refill residue into storage receptacles.
	Restrict the quantity stored at the work place.
	Use only in well ventilated areas.
	Before break and at the end of work hands should be thoroughly washed.
	Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-
	metal compounds and amines).
	While using do not eat, drink or smoke. Do not generate flames or sparks.
	Keep product and emptied container away from heat and sources of ignition.
	Avoid shock and friction.
	Take precautionary measures against static discharges.
	bo not smoke.
 Information about fire - and 	
explosion protection:	Protect from heat.
	Protect against electrostatic charges.
	Prevent impact and friction.
	Keep respiratory protective device available.
	Use explosion-proof apparatus / fittings and spark-proof tools.
	Fumes can combine with air to form an explosive mixture.

Printing date 03.04.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 Version: 7 (replaces version 6)



Revision: 27.11.2023

Trade name: PEROXAN CU-40 M

	(Contd. of page 3
	Wear shoes with conductive soles.
	Formation of flammable or explosive gas/air-mixtures is possible.
	Avoid open flames, sparks, direct sunlight and other sources of ignition.
	Keep ignition sources away - Do not smoke.
7.2 Conditions for safe storage,	including any incompatibilities
Storage:	Pay attention to the special requirements of your local autorithies for storing dangerous goods.
· Requirements to be met by	
storerooms and receptacles:	Store only in the original receptacle.
	Prevent any seepage into the ground.
	Use only receptacles specifically permitted for this substance/product.
 Information about storage in 	
one common storage facility:	Do not store or park organic peroxide together with heavy metal compounds and amines.
	Store away from foodstuffs, drinks and feeding stuffs.
 Further information about 	
storage conditions:	Keep container tightly sealed.
	Protect from heat and direct sunlight.
	Protect from contamination.
	Store under lock and key and out of the reach of children.
Decomposed of stores	Storage in a collecting room is required.
· Recommended storage	
temperature (To maintain	
quality): • Storage class:	0 +30 °C 5.2
7.3 Specific end use(s)	o.z No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

98-82-8 Cumene	nit values that require monitoring at the workplace:		
	ort-term value: 250 mg/m³, 50 ppm ng-term value: 50 mg/m³, 10 ppm		
	ing-term value. So mg/m , to ppm		
	prt-term value: 250 mg/m³, 50 ppm		
	Long-term value: 125 mg/m ³ , 25 ppm		
:	Sk		
DNELS			
80-15-9 α,α -dimethy	Ibenzyl hydroperoxide		
Inhalative DNEL Lon	gterm System 6 mg/m3 (Worker)		
98-82-8 Cumene			
Dermal DNEL Lon	gterm System 15,4 mg/kg bw/day (Worker)		
Inhalative DNEL Longterm System 100 mg/m3 (Worker)			
· PNECs			
80-15-9 α,α -dimethy	Ibenzyl hydroperoxide		
PNEC Marinewater se	ed 0,002 mg/kg sed dw (-)		
PNEC Freshwater	0,003 mg/l (AF 1.000)		
PNEC Freshwater se	d 0,023 mg/kg sed dw (-)		
PNEC Soil	0,003 mg/kg soil dw (-)		
PNEC STP	0,35 mg/l (-)		
PNEC Marinewater	0 mg/l (AF 10.000)		
98-82-8 Cumene			
PNEC Marinewater se	ed 0,322 mg/kg sed dw (-)		
PNEC Freshwater	0,035 mg/l (AF 10)		
PNEC Freshwater se	d 3,22 mg/kg sed dw (-)		
PNEC Soil	0,624 mg/kg soil dw (-)		
PNEC STP	200 mg/l (AF 10)		
PNEC Marinewater	0,004 mg/l (AF 100)		
· Additional informa	tion: The lists valid during the making were used as basis.		

Printing date 03.04.2024

Version: 7 (replaces version 6)



Revision: 27.11.2023

Trade name: PEROXAN CU-40 M

	(Contd. of page
2 Exposure controls	
Appropriate engineering	
controls	No further data; see section 7.
ndividual protection measure General protective and	es, such as personal protective equipment
hygienic measures:	The usual precautionary measures are to be adhered to when handling chemicals.
	Keep away from foodstuffs, beverages and feed.
	Immediately remove all soiled and contaminated clothing
	Wash hands before breaks and at the end of work.
	Store protective clothing separately.
	Avoid contact with the eyes and skin.
	Do not eat, drink, smoke or sniff while working.
	Use skin protection cream for skin protection.
	Be sure to clean skin thoroughly after work and before breaks.
Respiratory protection:	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer
	exposure use self-contained respiratory protective device.
	Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	Filter A2
Hand protection	Only use chemical-protective gloves with CE-labelling of category III.
	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	Protective gloves
Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of
-	quality and varies from manufacturer to manufacturer.
	Butyl rubber, BR
	Fluorocarbon rubber (Viton)
	Nitrile rubber, NBR
	Neoprene
Penetration time of glove	
material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to b
	observed.
Eye/face protection	
	Tightly sealed goggles
Body protection:	Protective work clothing
	W

9.1 Information on basic physical and chemical properties		
· General Information		
· Colour:	colourless - yellowish	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Not applicable.	
 Boiling point or initial boiling point and boiling range 	Not applicable.	
· Flammability	Not applicable.	
 Lower and upper explosion limit 		
· Lower:	Not determined.	
· Upper:	Not determined.	
· Flash point:	79 °C	
· Decomposition temperature:	> +80 °C (SADT)	
pH	Not determined.	
· Viscosity:		
Kinematic viscosity	Not determined.	
· Dynamic at 20 °C:	5 mPas	
Solubility		
water:	Undetermined.	
 Partition coefficient n-octanol/water (log value) 	not determined	
Vapour pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C:	1,046 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not determined.	
		(Co



Version: 7 (replaces version 6)

PERGAN The Peroxide Company

Revision: 27.11.2023

Trade name: PEROXAN CU-40 M

	(Contd. of page
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment,	
and on safety.	
Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour
	mixtures are possible.
Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
 Self-reactive substances and mixtures 	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in	
contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
Corrosive to metals	Void
· Desensitised explosives	Void
Other safety characteristics	
· Active oxygen	4,5 - 4,7 %

SECTION 10: Stability and reactivity

-	-
 10.1 Reactivity 10.2 Chemical stability Thermal decomposition / 	No further relevant information available.
conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
10.3 Possibility of hazardous	
reactions	Self-accelerating decomposition at SADT.
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g heavy-metal compounds and amines).
10.6 Hazardous decomposition	
products:	Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

 11.1 Information on hazard class Acute toxicity 		on hazard classes as defined in Regulation (EC) No 1272/2008 Harmful if swallowed or in contact with skin. Toxic if inhaled.	Harmful if swallowed or in contact with skin.	
· LD/LC5	0 values	relevant for classification:		
80-15-9 c	α,α -dime	thylbenzyl hydroperoxide		
Oral	LD50	200-2.000 mg/kg (rattus)		
Dermal	LD50	400-2.000 mg/kg (rattus)		
L			(Cor	

Printing date 03.04.2024

Version: 7 (replaces version 6)

The Peroxide Company

Revision: 27.11.2023

Trade name: PEROXAN CU-40 M

		(Contd. of page 6	
Inhalative	LC50 / 4h	0,5-2 mg/l (rattus)	
98-82-8 Ci	umene		
Oral	LD50	2.260 mg/kg (rattus)	
Dermal	LD50	12.300 mg/kg (rabbit)	
Inhalative	LC50 / 4h	24,7 mg/l (mouse)	
617-94-7 2	2-Phenyl-2-	-propanol	
Oral	LD50	1.300 mg/kg (rattus)	
Dermal	LD50	4.300 mg/kg (rabbit)	
• Skin corrosion/irritation Causes severe skin burns and eye damage.			
Serious eye damage/irritation Causes serious eye damage.			
	ory or skin		
sensitisa	tion	Based on available data, the classification criteria are not met.	
· Germ cel	l mutagen	icity Based on available data, the classification criteria are not met.	
· Carcinog	enicity	May cause cancer.	
Reproduc	ctive toxic	ity Based on available data, the classification criteria are not met.	
STOT-sin	gle expos	May cause respiratory irritation.	
STOT-rep	beated exp		
· Aspiratio		Based on available data, the classification criteria are not met.	
		other hazards	
· Endocrin	e disruptiı	ng properties	
None of the	e ingredien	nts is listed.	

SECTION 12: Ecological information

· 12.1 Toxicity			
· Aquatic toxicity:			
80-15-9 α,α -dimethylbenzyl l	nydroperoxide		
LC50 10-100 mg/l (leuciscus i	dus)		
· 12.2 Persistence and degrad	ability		
• Degree of elimination:			
· Classification:			
80-15-9 α,α -dimethylbenzyl l	nydroperoxide		
Degradation (Not readily biod	egradable) (OECD 301 B)		
98-82-8 Cumene			
Degradation (Readily biodegr	adable)		
12.3 Bioaccumulative potent	ial		
· Partition coefficient: nOcta	nol/water: [Log Kow]		
141-97-9 ethyl acetoacetate		0,8 (20°C)	
80-15-9 α,α -dimethylbenzyl	hydroperoxide	1,6 (25°C)	
98-82-8 Cumene			
		1,89 (25°C)	
98-86-2 acetophenone		1,65 (20°C)	
12.4 Mobility in soil	No further relevant information available.	i	
· 12.5 Results of PBT and vPv			
· PBT: · vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to REAC		
· 12.6 Endocrine disrupting	The substances in the mixture do not meet the PBT/vPvB criteria according to REAC	H, annex XIII.	
properties	The product does not contain substances with endocrine disrupting properties.		
12.7 Other adverse effects			
· Remark:	Toxic for fish		
 Additional ecological inform 			
· General notes:	Must not reach sewage water or drainage ditch undiluted or unneutralised.		
	Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms		
	Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water		
	Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small guantities leak into the ground.		
	Danger to uninking water in even small quantities leak into the ground.	MT	

(Contd. on page 8)

Printing date 03.04.2024

Version: 7 (replaces version 6)

Revision: 27.11.2023

The Peroxide Company

Trade name: PEROXAN CU-40 M

(Contd. of page 7)

	(Contd. of page 7)
SECTION 13: Disposal cons	siderations
 13.1 Waste treatment methods Recommendation 	After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.
	Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· Waste disposal key:	Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)- number.
 Uncleaned packaging: Recommendation: 	This material and its container must be disposed of as hazardous waste.
SECTION 14: Transport info	ormation
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3109
 · 14.2 UN proper shipping name · ADR · IMDG 	UN3109 ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE),
	MARINE POLLUTANT ORGANIC PEROXIDE TYPE F, LIQUID (CUMYLHYDROPEROXIDE)
· 14.3 Transport hazard class(es)
· ADR	5.2 (P1) Organic peroxides. 5.2
· IMDG · Class · Label	5.2 Organic peroxides. 5.2
· IATA	5.2 Organic peroxides.
· Label	5.2 Siganic peroxides.
 14.4 Packing group ADR, IMDG, IATA 	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: CUMYLHYDROPEROXIDE
• Marine pollutant:	Yes Symbol (fish and tree)
• Special marking (ADR):	Symbol (fish and tree)
 14.6 Special precautions for us Stowage Category 	er Warning: Organic peroxides. D
Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.
· 14.7 Maritime transport in bulk	according to IMO instruments Not applicable.
Transport/Additional information	
ADR Limited quantities (LQ)	125 ml

Printing date 03.04.2024

Version: 7 (replaces version 6)



Revision: 27.11.2023

Trade name: PEROXAN CU-40 M

	(Contd. of page 8)
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
Tunnel restriction code	D
· RID / GGVSEB:	like ADR
· IMDG	
· Limited quantities (LQ)	125 ml
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU · Named dangerous substances - ANNEX I None of the ingredients is listed. · Seveso category H2 ACUTE TOXIC P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES E2 Hazardous to the Aquatic Environment · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t **REGULATION (EC) No** 1907/2006 ANNEX XVII Conditions of restriction: 3, 28, 75 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex п None of the ingredients is listed. · REGULATION (EU) 2019/1148 · Regulation (EC) No 273/2004 on drug precursors None of the ingredients is listed. · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:	Environment protection / Security of labour
· Contact:	Tel: +49 2871 9902-0
	E-mail: mail@pergan.com
· Version number of previous	
version:	6
• Abbreviations and acronyms:	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
	ICAO: International Civil Aviation Organisation
	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)
	DNEL DERIVED NO-Effect Concentration (REACH)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	Flam. Liq. 3: Flammable liquids – Category 3
	Org. Perox. E: Organic peroxides – Type E/F
	Org. Perox. F: Organic peroxides – Type E/F
	Acute Tox. 4: Acute toxicity – Category 4
	Acute Tox. 3: Acute toxicity – Category 3
	Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2
	(Contd. on page 10)

Printing date 03.04.2024

Version: 7 (replaces version 6)

PERGAN The Peroxide Company

Revision: 27.11.2023

(Contd. of page 9)

Trade name: PEROXAN CU-40 M

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Carc. 1B: Carcinogenicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• * Data compared to the previous version altered.

— MT —