

Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN DB-50 W · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

Environment protection / Security of labour from:

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Org. Perox. F H242 Heating may cause a fire.

H341 Suspected of causing genetic defects. Muta. 2

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



Danger

· Signal word

· Hazard-determining

components of labelling: di-tert-butyl peroxide

**Hazard statements** H225 Highly flammable liquid and vapour.

H242 Heating may cause a fire.

H341 Suspected of causing genetic defects.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e.g. heavy metal compounds and amines).

P234 Keep only in original packaging. P243 Take action to prevent static discharges. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up

P410 Protect from sunlight. P411 Store at temperatures not exceeding +40°C.

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations

· Additional information: Contains tert-butyl hydroperoxide. May produce an allergic reaction.

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

(Contd. on page 2)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

(Contd. of page 1)

Determination of endocrinedisrupting properties

The product does not contain substances with endocrine disrupting properties.

#### **SECTION 3: Composition/information on ingredients**

#### · 3 2 Mixtures

· Dangerous components:		
CAS: 110-05-4 EINECS: 203-733-6 Index number: 617-001-00-2 Reg-No.: 01-2119513335-48	di-tert-butyl peroxide Flam. Liq. 2, H225; Org. Perox. E, H242; Muta. 2, H341; Aquatic Chronic 3, H412	40-50%
CAS: 75-91-2 EINECS: 200-915-7 Reg-No.: 01-2119446670-40	tert-butyl hydroperoxide Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 2, H351; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limits: Eye Dam. 1; H318: C ≥ 1 % Skin Sens. 1; H317: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	≤0,1%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately remove contaminated clothing.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After eye contact:

After swallowing: If symptoms persist consult doctor.

 4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate

medical attention and special

No further relevant information available.

treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

· 5.3 Advice for firefighters

· Protective equipment: · Additional information Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 3)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

(Contd. of page 2)

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections In case of large spillage the environmental authority should be informed.

# **SECTION 7: Handling and storage**

· 7.1 Precautions for safe

handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Use only in well ventilated areas.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

# · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Store in a cool place.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight. Protect from contamination.

Recommended storage temperature (To maintain

max.: +40°C

quality): Storage class: 52

· 7.3 Specific end use(s) No further relevant information available.



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

(Contd. of page 3)

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs				
110-05-4	110-05-4 di-tert-butyl peroxide			
Dermal	DNEL Longterm System	3 mg/kg bw/day (Worker)		
Inhalative	DNEL Longterm System	20 mg/m3 (Worker)		
75-91-2 te	75-91-2 tert-butyl hydroperoxide			
Dermal	DNEL Longterm System	0,21 mg/kg bw/day (Worker)		
Inhalative	DNEL Acute Systemic	85,2 mg/m3 (Worker)		
	DNEL Acute Local	28,4 mg/m3 (Worker)		
	DNEL Longterm System	2,2 mg/m3 (Worker)		
	DNEL Longterm Local	0,58 mg/m3 (Worker)		

#### · PNFCs

#### 110-05-4 di-tert-butyl peroxide

PNEC Marinewater sed | 1,5 mg/kg sed dw (-) 0,144 mg/l (AF 50) **PNEC Freshwater** PNEC Freshwater sed 15 mg/kg sed dw (-) PNEC Soil 2,94 mg/kg soil dw (-) PNEC STP 10 mg/l (AF 100) 0,014 mg/l (AF 500) PNEC Marinewater

# 75-91-2 tert-butyl hydroperoxide

PNEC Marinewater sed 0,001 mg/kg sed dw 0,002 mg/l (AF 1.000) PNEC Freshwater 0 mg/l (AF 10.000) PNEC Seawater 0,006 mg/kg sed dw (-) PNEC Freshwater sed 0,166 mg/kg soil dw (AF 1.000) PNEC Soil 0,17 mg/l (AF 100) PNEC STP

• Additional information:

The lists valid during the making were used as basis.

### 8.2 Exposure controls

Appropriate engineering

controls

No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer · Respiratory protection:

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

(Contd. on page 5)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

(Contd. of page 4)

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

· Eye/face protection



Neoprene

Tightly sealed goggles

· Body protection:

Protective work clothing

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless · Odour: Characteristic · Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range Undetermined. · Flash point: +5 °C

> +80 °C (SADT) · Decomposition temperature:

· Viscosity:

Dynamic at 20 °C:

· Solubility

· Partition coefficient n-octanol/water (log value)

· Density and/or relative density

· Density at 20 °C:

Not miscible or difficult to mix.

not determined

ca. 6 mPas

ca. 0,83 g/cm<sup>3</sup>

9.2 Other information

Appearance:

Fluid · Form: · Important information on protection of health and environment,

and on safety.

· Ignition temperature: Product is not selfigniting. Explosive properties:

Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids

Highly flammable liquid and vapour. · Flammable solids Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in

contact with water Void · Oxidising liquids Void Oxidising solids Void

· Organic peroxides Heating may cause a fire.

 Corrosive to metals Void Desensitised explosives Void

**SECTION 10: Stability and reactivity** 

· 10.1 Reactivity · 10.2 Chemical stability No further relevant information available.

Thermal decomposition /

conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

(Contd. on page 6)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.

(Contd. of page 5)

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e.g. heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

#### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

#### 110-05-4 di-tert-butyl peroxide

Oral	LD50	>25.000 mg/kg (rattus)
Dermal	LD50	>19.000 mg/kg (mus)
Inhalative	LC50 / 4h	>24,5 mg/l (rattus)

#### 75-91-2 tert-butyl hydroperoxide

Oral	LD50	805 mg/kg /(70%) (rattus)
Dermal	LD50	633 mg/kg /(70%) (cuniculosus)
Inhalative	LC50 / 4h	1.2 mg/l /(70%) (rattus)

Skin corrosion/irritation Based on available data, the classification criteria are not met. Low irritant effect

· Serious eye damage/irritation

Respiratory or skin

Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Suspected of causing genetic defects.

· Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

# · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

# · 12.1 Toxicity

sensitisation

. д	quatic	toxicity:	
_	.quuii0	toxioity.	

# 75-91-2 tert-butyl hydroperoxide

EC50 / 72h | 2,1 mg/l /(70%) (selenastrum capricornutum) LC50 / 96h 42,3 mg/l /(70%) (pimephales promelas) 24,3 mg/l /(70%) (activa sludge) EC50 / 48h | 20 mg/l /(70%) (daphnia magna)

# 12.2 Persistence and degradability

· Degree of elimination:

# · Classification:

# 110-05-4 di-tert-butyl peroxide

Degradation (Not readily biodegradable) (OECD 301 D)

### 75-91-2 tert-butyl hydroperoxide

Degradation (Not readily biodegradable) (OECD 301 D)

#### 12.3 Bioaccumulative potential

### · Partition coefficient: nOctanol/water: [Log Kow]

110-05-4 di-tert-butyl peroxide 3,2 (22°C) 8042-47-5 White mineral oil, petroleum > 3,5

(Contd. on page 7)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

# Trade name: PEROXAN DB-50 W

(Contd. of page 6) 75-65-0 2-methylpropan-2-ol 0,32 (20°C) 75-91-2 tert-butyl hydroperoxide 0,85 (30 °C)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number

· Uncleaned packaging:

· Recommendation: This material and its container must be disposed of as hazardous waste.

### **SECTION 14: Transport information**

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3109 · 14.2 UN proper shipping name

· ADR UN3109 ORGANIC PEROXIDE TYPE F, LIQUID (DI-tert-BUTYL

PEROXIDE)

· IMDG, IATA ORGANIC PEROXIDE TYPE F, LIQUID (DI-tert-BUTYL PEROXIDE)

· 14.3 Transport hazard class(es)

· ADR



· Class 5.2 (P1) Organic peroxides.

· Label

· IMDG, IATA



· Class 5.2 Organic peroxides

· Label 5.2

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: Nο

14.6 Special precautions for user Warning: Organic peroxides.

· Hazard identification number (Kemler code):

· Stowage Category D

Stowage Code SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids · Segregation Code

SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable

(Contd. on page 8)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN DB-50 W

(Contd. of page 7)

· Transport/Additional information:

· ADR

 Limited quantities (LQ) Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category Tunnel restriction code

· RID / GGVSEB: like ADR

Limited quantities (LQ) 125 ml Code: E0 Excepted quantities (EQ)

Not permitted as Excepted Quantity

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES Seveso category

· Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

**REGULATION (EC) No** 

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug

None of the ingredients is listed.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the · Abbreviations and acronyms:

IND: Reglement international concernant le transport des marchandises dangereuses par chemin de ter (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDC: International Ministry Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)

(Contd. on page 9)



Printing date 29.12.2023 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN DB-50 W

(Contd. of page 8)

PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. E: Organic peroxides – Type E/F
Org. Perox. F: Organic peroxides – Type E/F
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 PNEC: Predicted No-Effect Concentration (REACH)

· \* Data compared to the previous version altered.

мт —