

Version: 14 (replaces version 13)

•) The Peroxide Company

Revision: 14.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

DEBUXYN DC-40 D

· Trade name:	PERUXAN DC-40 P
· 1.2 Relevant identified uses of the	ne substance or mixture and uses advised against
	No further relevant information available.
 Application of the substance / 	
the mixture	Reaction initiator
	For industrial use
· 1.3 Details of the supplier of the	safety data sheet
Manufacturer/Supplier:	PERGAN GmbH
	Hilfsstoffe für industrielle Prozesse
	Schlavenhorst 71
	D-46395 Bocholt
	Tel: +49 2871 9902-0
	Fax: +49 2871 9902-50
· Further information obtainable	
from:	Environment protection / Security of labour
	Qualified person: E-mail: msds@pergan.com
· 1.4 Emergency telephone	Zeener - Feerer - eener (Steel Steel Steel
number:	- Tel: +49 2871 9902-0
SECTION 2: Hazards identifie	cation

ON 2: Hazards identification

• 2.1 Classification of the substan • Classification according to Reg	
Flam. Sol. 1 H228 Flamm Org. Perox. G	able solid.
Skin Irrit. 2 H315 Cause	s skin irritation.
Eye Irrit. 2 H319 Causes	s serious eye irritation.
Skin Sens. 1 H317 May ca	use an allergic skin reaction.
	mage the unborn child.
Aquatic Chronic 2 H411 Toxic t	o aquatic life with long lasting effects.
2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Hazard pictograms	The product is classified and labelled according to the CLP regulation.
· Signal word	Danger
 Hazard-determining components of labelling: Hazard statements 	 bis(a,a-dimethylbenzyl) peroxide H228 Flammable solid. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H360D May damage the unborn child. H411 Toxic to aquatic life with long lasting effects.
 Precautionary statements 	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P264 Wash thoroughly after handling. P273 Avoid release to the environment. P280 Wear eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 Additional information: 2.3 Other hazards 	Restricted to professional users.
· Results of PBT and vPvB asses	sment
PBT:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. (Contd. on page 2)

Printing date 04.04.2024

Version: 14 (replaces version 13)

PERGAN The Peroxide Company

Revision: 14.12.2023

Trade name: PEROXAN DC-40 P

disrupting properties	- The product does not contain substances with endocrine disrupting properties.
SECTION 3: Composition	/information on ingredients
3.2 Mixtures	
Dangerous components:	
EINECS: 201-279-3	bis(a,a-dimethylbenzyl) peroxide Org. Perox. F, H242; Repr. 1B, H360D; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317
Additional information:	For the wording of the listed hazard phrases refer to section 16.
SECTION 4: First aid mea	SUITAS
4.1 Description of first aid m General information:	Take care of personal protection for the first aider.
After inhalation:	In case of unconsciousness place patient stably in side position for transportation. Take affected persons into fresh air and keep quiet.
After skin contact:	Immediately wash with water and soap and rinse thoroughly. Immediately remove contaminated clothing.
After eye contact: After swallowing:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. If symptoms persist consult doctor.
4.2 Most important symptom	
and effects, both acute and delayed	No further relevant information available.
4.3 Indication of any immedi medical attention and specia	
treatment needed	No further relevant information available.
SECTION 5: Firefighting I	neasures
5.1 Extinguishing media	
5.1 Extinguishing media	nts: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. rom
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture	
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment:	rom Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters	rom Under certain fire conditions, traces of other toxic gases cannot be excluded.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment:	Trom Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment:	Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray. Self-protection first!
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions,	Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray. Self-protection first!
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information	Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray. Self-protection first! elease measures In case of further temperature should be cooled with waterspray from a safe distance.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and emergency procedures	Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray. Self-protection first! Please measures In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and emergency procedures	Under certain fire conditions, traces of other toxic gases cannot be excluded. Do not inhale explosion gases or combustion gases. Cool endangered receptacles with water spray. Self-protection first! Please measures In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and	In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away. In form respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and emergency procedures 6.2 Environmental precautio	Image: construction of the second
5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and emergency procedures 6.2 Environmental precautio 6.3 Methods and material for	In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away. Inform respective authorities in case of seepage into water course or sewage system. Image: Inform respective authorities in case of seepage into water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Do not allow to enter sewers/ surface or ground water. Plexity Plexity Do not allow to enter sewers/ surface or ground water. Plexity Plexity Plexity Plexity Plexity Plexity P
 5.1 Extinguishing media Suitable extinguishing ager 5.2 Special hazards arising f the substance or mixture 5.3 Advice for firefighters Protective equipment: Additional information SECTION 6: Accidental re 6.1 Personal precautions, protective equipment and emergency procedures 6.2 Environmental precaution 6.3 Methods and material for containment and cleaning u 	Image: construction of the second

Printing date 04.04.2024

Version: 14 (replaces version 13)

The Peroxide Company

•)

Revision: 14.12.2023


Trade name: PEROXAN DC-40 P

(Contd. of page 2)

SECTION 7: Handling and st	orage
· 7.1 Precautions for safe	
handling	Open and handle receptacle with care. Prevent formation of dust. Wear suitable respiratory protective device when decanting larger quantities without extractor facilities. Before break and at the end of work hands should be thoroughly washed. Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy- metal compounds and amines). While using do not eat, drink or smoke. Avoid shock and friction.
Information about fire - and	
explosion protection:	Protect from heat.
	Prevent impact and friction. Dust can combine with air to form an explosive mixture.
	Substance/product is oxidising when dry.
	Avoid open flames, sparks, direct sunlight and other sources of ignition.
· 7.2 Conditions for safe storage,	including any incompatibilities
Storage:	Pay attention to the special requirements of your local autorithies for storing dangerous goods.
 Requirements to be met by 	
storerooms and receptacles:	Store only in the original receptacle.
	Prevent any seepage into the ground.
· Information about storage in	Use only receptacles specifically permitted for this substance/product.
one common storage facility:	Store away from foodstuffs, drinks and feeding stuffs.
· Further information about	
storage conditions:	Keep container tightly sealed.
-	Protect from heat and direct sunlight.
	Protect from contamination.
B	Storage in a collecting room is required.
· Recommended storage	
temperature (To maintain quality):	max.: +30 °C
Storage class:	5.2
· 7.3 Specific end use(s)	No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Ingredier	ol parameter nts with limit ire monitori :e:	t values ng at the	The product does not contain any relevant quantities of materials with critical values that monitored at the workplace.	have to be
· DNELs				
80-43-3 bi	s(a,a-dimeth			
Oral	DNEL Longt	erm System	0,4 mg/kg bw/day (General population)	
Dermal	DNEL Longt	erm System	0,8 mg/kg bw/day (Worker)	
			0,4 mg/kg bw/day (General population)	
Inhalative	DNEL Longt	erm System	5,6 mg/m3 (Worker)	
			1,4 mg/m3 (General population)	
· PNECs				
80-43-3 bi	s(a,a-dimeth	nylbenzyl) po	eroxide	
PNEC Fre	shwater	water 0,00234 mg/l (AF 50)		
PNEC Fre	shwater sed	2,24 mg/kg	sed dw (-)	
PNEC Soi	I	0,447 mg/kg	g soil dw (-)	
PNEC ST	>	100 mg/l (A	F 10)	
· Addition	al informati	on:	The lists valid during the making were used as basis.	
 8.2 Exposure controls Appropriate engineering controls Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. 				



Version: 14 (replaces version 13)

Revision: 14.12.2023

•

The Peroxide Company

ſ

Trade name: PEROXAN DC-40 P

Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or snift while working. Use skin protection cream for skin protection. Be sure to clean skin throughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves Protective gloves • Penetration time of glove material The selection of the suitable gloves does not only depend on the material, but also on f quality nubber, NBR Neoprene • Penetration time of glove material The selection of the suitable gloves does not only depend on the material, but also on f quality nubber, NBR Neoprene • Penetration time of glove material The selection of the suitable gloves does not only depend on the material, but also on f quality nubber, NBR Neoprene • Penetration time of glove material The selection quality use all protection (Viton) Nitrile rubber, NBR Neoprene • Selection of the suitable gloggles Tightly sealed goggles	of diffusion and the
Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid cose or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves tobserved. • Eye/face protection: Tightly sealed goggles	of diffusion and the
Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection: Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloses • Eye/face protection Tightly sealed goggles	of diffusion and the
Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. Image: Selection of the gloves Filter P2 Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves Material of gloves Penetration time of glove material Penetration time of glove material Penetration time of glove material Eye/face protection Body protection:	of diffusion and the
Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or shiff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection: Not excessary if room is well-ventilated. • Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Buyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves observed. • Eye/face protection Tightly sealed goggles	of diffusion and the
Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection: Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves observed. • Eye/face protection Tightly sealed goggles	of diffusion and the
Do not eat, drink, smoke or sniff while working. Use skin protection. Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Respiratory protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves • Material of gloves Filter P2 • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves ved. • Eye/face protection Tightly sealed goggles	of diffusion and the
• Respiratory protection: Be sure to clean skin thoroughly after work and before breaks. Not necessary if room is well-ventilated. • Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. • Material of gloves Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves rubber velocetion • Eye/face protection Tightly sealed goggles	of diffusion and the
• Respiratory protection: Not necessary if room is well-ventilated. • Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. • Material of gloves Selection of the glove material on consideration of the penetration times, rates degradation • Protective gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves rubber ved. • Eye/face protection Tightly sealed goggles	of diffusion and the
• Hand protection Filter P2 • Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. • Material of gloves Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, NBR Filorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective globes rod. • Eye/face protection Tightly sealed goggles	of diffusion and the
• Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. • Material of gloves Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves observed. • Eye/face protection Tightly sealed goggles	of diffusion and the
• Hand protection Filter P2 • Hand protection Only use chemical-protective gloves with CE-labelling of category III. • Material of gloves Selection of the glove material on consideration of the penetration times, rates degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloses observed. • Eye/face protection Tightly sealed goggles	of diffusion and the
 Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	
 Hand protection Only use chemical-protective gloves with CE-labelling of category III. Selection of the glove material on consideration of the penetration times, rates degradation Protective gloves Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	
 Material of gloves Material of gloves Material of gloves Material of gloves Selection of the gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	
 Material of gloves Material of gloves Material of gloves Material of gloves Selection of the gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	
 Material of gloves Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	
 Material of gloves Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	urther marks of
 Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Body protection: 	urther marks of
• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on f quality and varies from manufacturer to manufacturer. Butyl rubber, BR • Penetration time of glove material Fluorocarbon rubber (Viton) • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective globserved. • Eye/face protection Tightly sealed goggles	urther marks of
quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene The exact break trough time has to be found out by the manufacturer of the protective observed. Eye/face protection Body protection:	
Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene Penetration time of glove material Eye/face protection Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene The exact break trough time has to be found out by the manufacturer of the protective observed. Eye/face protection Tightly sealed goggles	
 Penetration time of glove material Eye/face protection Body protection: 	
 Penetration time of glove material Eye/face protection Body protection: 	
• Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective globserved. • Eye/face protection Tightly sealed goggles	
Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective observed. Eye/face protection Tightly sealed goggles	
material The exact break trough time has to be found out by the manufacturer of the protective observed. • Eye/face protection Tightly sealed goggles • Body protection: Image: Comparison of the protective observed.	
• Eye/face protection • Body protection:	loves and has to be
Body protection:	,
Body protection:	
· Body protection:	
· Body protection:	
Urotootivo work alathing	
Protective work clothing	
SECTION 9: Physical and chemical properties	
• 9.1 Information on basic physical and chemical properties	
· General Information	
· Colour: white - yellowish	
· Odour: Characteristic	
Odour threshold: Not determined.	
• Melting point/freezing point: Not applicable.	
· Boiling point or initial boiling point and boiling range Not applicable.	
· Flammability May cause fire.	
· Lower and upper explosion limit	
· Lower: Not determined.	
· Upper: Not determined.	
· Flash point: Not determined:	
· Decomposition temperature: +80 °C (SADT)	
· pH Not applicable.	
· Viscosity:	
• Kinematic viscosity Not applicable.	
• Dynamic: Not applicable.	
· Solubility	
· water: Undetermined.	
· Partition coefficient n-octanol/water (log value) not determined	
· Vapour pressure: Not applicable.	
· Density and/or relative density	
· Density: Not determined.	
• Relative density Not determined.	
Bulk density at 20 °C: 410 - 480 kg/m ³	
Vapour density Not applicable.	
· Particle characteristics	
See section 3.	
	(Contd. on page 5

Printing date 04.04.2024

Version: 14 (replaces version 13)

Revision: 14.12.2023

Trade name: PEROXAN DC-40 P

		(Contd. of page
9.2 Other information	No further relevant information available.	
· Appearance:		
· Form:	Solid	
	Powder	
· Important information on protection of health and envir	ronment,	
and on safety.		
· Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Not determined.	
Change in condition		
· Evaporation rate	Not applicable.	
· Information with regard to physical hazard classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Flammable solid.	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable gases	sin	
contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	
· Other safety characteristics		
· Active oxygen	2,3 - 2,4 %	

SECTION 10: Stability and reactivity

 10.1 Reactivity 10.2 Chemical stability Thermal decomposition / 	No further relevant information available.
conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications.
 10.3 Possibility of hazardous 	·····
reactions	Self-accelerating decomposition at SADT.
 10.4 Conditions to avoid 	No further relevant information available.
 10.5 Incompatible materials: 	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
 10.6 Hazardous decomposition 	
products:	Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

11.1 Inf Acute 1			ses as defined in Regulation (EC) No 1272/2008 Based on available data, the classification criteria are not met.	
· LD/LC	50 val	ues relevant for cla	assification:	
80-43-3	bis(a,a	a-dimethylbenzyl)	peroxide	
Oral	LD50	>2.000 mg/kg (rattu	us)	
Dermal	LD50	>2.000 mg/kg (rattu	us)	
		on/irritation lamage/irritation	Causes skin irritation. Causes serious eye irritation.	
Conou	o oyo t			(Contd. on page 6) ——— MT —



Printing date 04.04.2024

Version: 14 (replaces version 13)

Revision: 14.12.2023

Trade name: PEROXAN DC-40 P

		(Contd. of page 5)
Respiratory or skin		
sensitisation	May cause an allergic skin reaction.	
 Germ cell mutagenicity 	Based on available data, the classification criteria are not met.	
 Carcinogenicity 	Based on available data, the classification criteria are not met.	
Reproductive toxicity	May damage the unborn child.	
STOT-single exposure	Based on available data, the classification criteria are not met.	
STOT-repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
11.2 Information on other haz	ards	
· Endocrine disrupting proper	ties	
None of the ingredients is listed		

SECTION 12: Ecological information

· 12.1 Toxici	ty		
· Aquatic to	xicity:		
80-43-3 bis	(a,a-dimethylbenzy	yl) peroxide	
EC50 / 72h	>20 mg/l (algae)		
EC50	>1.000 mg/l (activa	a sludge)	
	tence and degrada elimination:	ability	
Classifica	tion:		
80-43-3 bis	(a,a-dimethylbenzy	yl) peroxide	
Degradatior	Not readily biode	egradable) (OECD 301 F)	
· 12.3 Bioaco	cumulative potentia	al	
· Partition	coefficient: nOctan	nol/water: [Log Kow]	
80-43-3 bis	(a,a-dimethylbenzyl	I) peroxide	5,6 (25°C)
Bioconcer	tration factor (BCI	F)	
80-43-3 bis	(a,a-dimethylbenzy	yl) peroxide	
BCF 747			
12.4 Mobili	ty in soil	No further relevant information available.	
	s of PBT and vPvE		
· PBT:		The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex	
· vPvB:		The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, anne	CXIII.
	rine disrupting	The second set of a second stress whether a second stress with a second s	
properties	adverse effects	The product does not contain substances with endocrine disrupting properties. No further relevant information available	
Remark:	auverse effects	Toxic for fish	
	ecological information		
· General n	otes:	Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small qu Danger to drinking water if even extremely small quantities leak into the ground.	

SECTION 13: Disposal considerations

 13.1 Waste treatment methods Recommendation 	Must not be disposed together with household garbage. Do not allow product to reach sewage system.	
· Waste disposal key:	Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)- number.	
Uncleaned packaging:		
· Recommendation:	This material and its container must be disposed of as hazardous waste.	
SECTION 14: Transport information		

•	14.1	UN	num	ber	or	ID	number	'
	ADF	R, IN	IDG,	IAT	Α			

UN1325



Printing date 04.04.2024

Version: 14 (replaces version 13)

Revision: 14.12.2023

Trade name: PEROXAN DC-40 P

	(Contd. of page 6
 14.2 UN proper shipping name ADR 	UN1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (DICUMYL PEROXIDE),
·IMDG	ENVIRONMENTALLY HAZARDOUS FLAMMABLE SOLID, ORGANIC, N.O.S. (DICUMYL PEROXIDE), MARINE POLLUTANT
· IATA	FLAMMABLE SOLID, ORGANIC, N.O.S. (DICUMYL PEROXIDE)
· 14.3 Transport hazard class(es)	
ADR	
Class	4.1 (F1) Flammable solids, self-reactive substances, polymerizing substances and solid desensitized explosives
·Label	4.1
· Class	4.1 Flammable solids, self-reactive substances, polymerizing substances and solid desensitized explosives
· Label	4.1
· Class	 4.1 Flammable solids, self-reactive substances, polymerizing substances and solid desensitized explosives 4.1
• 14.4 Packing group	4.1
ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: DICUMYL PEROXIDE
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable solids, self-reactive substances, polymerizing substances and solid desensitized explosives
· EMS Number: · Stowage Category	F-A,S-G B
· 14.7 Maritime transport in bulk according to IM	O instruments Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1 kg Code: E2 Maximum net quantity per inner packaging: 30 g
 Transport category Tunnel restriction code 	Maximum net quantity per outer packaging: 500 g 2 E
· RID / GGVSEB:	like ADR
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1 kg Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
	······································

(Contd. on page 8)



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 Version: 14 (replaces version 13)

Printing date 04.04.2024

PERGAN The Peroxide Company

Revision: 14.12.2023

Trade name: PEROXAN DC-40 P

(Contd. of page 7)

SECTION 15: Regulatory information

 15.1 Safety, health and environ 	mental regulations/legislation specific for the substance or mixture				
· Directive 2012/18/EU					
• Named dangerous substance	ns and a second s				
- ANNEX I	None of the ingredients is listed.				
· Seveso category	E2 Hazardous to the Aquatic Environment				
Qualifying quantity (tonnes) for					
the application of lower-tier	200.4				
requirements 200 t					
· Qualifying quantity (tonnes) for the application of upper-tier					
requirements	500 t				
· REGULATION (EC) No					
1907/2006 ANNEX XVII	Conditions of restriction: 30, 75				
• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II					
None of the ingredients is listed.					
· REGULATION (EU) 2019/1148					
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))					
None of the ingredients is listed.					
Annex II - REPORTABLE EXPLOSIVES PRECURSORS					
None of the ingredients is listed.					
· Regulation (EC) No 273/2004 on drug precursors					
None of the ingredients is listed.					
 Regulation (EC) No 111/2005 precursors 	laying down rules for the monitoring of trade between the Community and third countries in drug				
None of the ingredients is listed.					

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Department issuing SDS: 	Environment protection / Security of labour
Contact:	Tel: +49 2871 9902-0
	E-mail: mail@pergan.com
 Version number of previous 	
version:	13
 Abbreviations and acronyms: 	International Transport of Dangerous Goods by Rail)
	ICAO: International Civil Aviation Organisation
	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International
	Carriage of Dangerous Goods by Road
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	DNEL: Derived No-Effect Level (REACH)
	PNEC: Predicted No-Effect Concentration (REACH)
	LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
	LDSU: Letrai dose, su percent PBT: Persistent. Bioaccumulative and Toxic
	VPUB: very Persistent and very Bioaccumulative
	Flam. Sol. 1: Flammable solids – Category 1
	Org. Perox. F: Organic peroxides – Type E/F
	Org. Perox. G: Organic peroxides – Type G
	Skin Irrit. 2: Skin corrosion/irritation – Category 2
	Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1
	Skin Sens. 18: Skin sensitisation – Category 1 Skin Sens. 18: Skin sensitisation – Category 1B
	Rep: 1B: Reproductive toxicity – Category 1B
	Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
* * Data compared to the	
previous version altered.	
pressour reference attended	мт —
	101