

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN M64 AX
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:** Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Org. Perox. D	H242	Heating may cause a fire.
Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS05 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane
4-hydroxy-4-methylpentan-2-one
2,4-Pentanedione, peroxide
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate
- **Hazard statements**

H242 Heating may cause a fire.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +30°C. Keep cool.
P420	Store separately.

Trade name: PEROXAN M64 AX

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Determination of endocrine-disrupting properties

78-93-3	butanone	List II
---------	----------	---------

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Dangerous components:

CAS: 6846-50-0 EINECS: 229-934-9 Reg-No.: 01-2119451093-47	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2, H361d; Aquatic Chronic 3, H412	30-40%
CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Repr. 2, H361d; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	25-40%
CAS: 1338-23-4 EC number: 700-954-4 Reg-No.: 01-2119514691-43	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane Org. Perox. D, H242; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	20-25%
CAS: 37187-22-7 EINECS: 253-384-9 Reg-No.: 01-2119965139-28	2,4-Pentanedione, peroxide Alternative CAS number: 13784-51-5 Org. Perox. D, H242; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg-No.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	1-5%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 % Skin Corr. 1B; H314: 50 % ≤ C < 70 % Skin Irrit. 2; H315: 35 % ≤ C < 50 % Eye Dam. 1; H318: C ≥ 8 % Eye Irrit. 2; H319: 5 % ≤ C < 8 % STOT SE 3; C ≥ 35 % Ox. Liq. 1; H271: C ≥ 70 % Ox. Liq. 2; H272: 50 % ≤ C < 70 %	1-5%
CAS: 123-54-6 EINECS: 204-634-0 Index number: 606-029-00-0 Reg-No.: 01-2119458968-15	pentane-2,4-dione Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302	0,1-1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)

MT

Trade name: **PEROXAN M64 AX**


(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.


SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded. Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray. Self-protection first!

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
Avoid contact with skin and eyes.
While using do not eat, drink or smoke.
Avoid shock and friction.
 Do not smoke.
- **Information about fire - and explosion protection:** Protect from heat.
Prevent impact and friction.

(Contd. on page 4)

— MT —

Trade name: **PEROXAN M64 AX**

(Contd. of page 3)

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:**
 - Store only in the original receptacle.
 - Prevent any seepage into the ground.
 - Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:**
 - Do not store or park organic peroxide together with heavy metal compounds and amines.
 - Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.
 - Protect from contamination.
 - Store under lock and key and out of the reach of children.
- **Recommended storage temperature (To maintain quality):** 0 +30 °C
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL (Great Britain)	Short-term value: 362 mg/m ³ , 75 ppm Long-term value: 241 mg/m ³ , 50 ppm
---------------------	---

78-93-3 butanone

IOELV (EU)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV

7722-84-1 hydrogen peroxide solution

WEL (Great Britain)	Short-term value: 2,8 mg/m ³ , 2 ppm Long-term value: 1,4 mg/m ³ , 1 ppm
---------------------	---

· **DNELs**

6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	17,62 mg/m ³ (Worker)

123-42-2 4-hydroxy-4-methylpentan-2-one

Dermal	DNEL Longterm System	467 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	32,6 mg/m ³ (Worker)

1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

Dermal	DNEL Longterm System	1,43 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	7,55 mg/m ³
	DNEL Longterm System	2,52 mg/m ³ (Worker)

37187-22-7 2,4-Pentanedione, peroxide

Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	4,41 mg/m ³ (Worker)

78-93-3 butanone

Dermal	DNEL Longterm System	1.161 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	600 mg/m ³ (Worker)

7722-84-1 hydrogen peroxide solution

Inhalative	DNEL Longterm Local	1,4 mg/m ³ (Worker)
------------	---------------------	--------------------------------

(Contd. on page 5)

MT

Trade name: PEROXAN M64 AX

(Contd. of page 4)

Continued on page 3

123-54-6 pentane-2,4-dione		
Dermal	DNEL Longterm System	12 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	84 mg/m3 (Worker)
· PNECs		
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
PNEC Marinewater sed	0,529 mg/kg sed dw (-)	
PNEC Freshwater	0,014 mg/l (AF 50)	
PNEC Freshwater sed	5,29 mg/kg sed dw	
PNEC Soil	1,05 mg/kg soil dw	
PNEC STP	3 mg/l (AF 10)	
PNEC Marinewater	0,001 mg/l (AF 500)	
123-42-2 4-hydroxy-4-methylpentan-2-one		
PNEC Marinewater sed	0,74 mg/kg sed dw	
PNEC Freshwater	2 mg/l (AF 50)	
PNEC Freshwater sed	7,4 mg/kg sed dw	
PNEC Soil	0,31 mg/kg soil dw	
PNEC STP	100 mg/l (AF 10)	
PNEC Marinewater	0,2 mg/l (AF 500)	
1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane		
PNEC Marinewater sed	0,009 mg/kg sed dw	
PNEC Freshwater	0,006 mg/l (AF 1.000)	
PNEC Freshwater sed	0,088 mg/kg sed dw	
PNEC Soil	0,014 mg/kg soil dw	
PNEC STP	1,2 mg/l (AF 10)	
PNEC Marinewater	0,001 mg/l (AF 10.000)	
37187-22-7 2,4-Pentanedione, peroxide		
PNEC Marinewater sed	0,153 mg/kg sed dw (-)	
PNEC Freshwater	0,17 mg/l (AF 10)	
PNEC Freshwater sed	1,53 mg/kg sed dw (-)	
PNEC Soil	0,2 mg/kg soil dw (-)	
PNEC STP	6,2 mg/l (AF 10)	
PNEC Marinewater	0,017 mg/l (AF 100)	
7722-84-1 hydrogen peroxide solution		
PNEC Marinewater sed	0,047 mg/kg sed dw	
PNEC Freshwater	0,013 mg/l (AF 50)	
PNEC Freshwater sed	0,047 mg/kg sed dw	
PNEC Soil	0,002 mg/kg soil dw	
PNEC STP	4,66 mg/l (AF 100)	
PNEC Marinewater	0,013 mg/l (AF 50)	
123-54-6 pentane-2,4-dione		
PNEC Marinewater sed	0,191 mg/kg sed dw	
PNEC Freshwater	0,2 mg/l (AF 50)	
PNEC Freshwater sed	1,909 mg/kg sed dw	
PNEC Soil	0,193 mg/kg soil dw (-)	
PNEC STP	1,32 mg/l (AF 10)	
PNEC Marinewater	0,02 mg/l (AF 500)	
· Ingredients with biological limit values:		
78-93-3 butanone		
BMGV (Great Britain)	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

(Contd. on page 6)

— MT —

Trade name: **PEROXAN M64 AX**

(Contd. of page 5)

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Neoprene

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Fluid

· Colour:

Colourless

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Not applicable.

· Boiling point or initial boiling point and boiling range

Not applicable.

· Flammability

May cause fire.

· Lower and upper explosion limit

· Lower:

Not determined.

· Upper:

Not determined.

· Flash point:

> SADT

· Decomposition temperature:

+50 °C (SADT)

· pH

Not determined.

· Viscosity:

· Kinematic viscosity

Not determined.

· Dynamic at 20 °C:

17 mPas

· Solubility

· water:

Undetermined.

· Partition coefficient n-octanol/water (log value)

not determined

Not determined.

· Vapour pressure:

Not determined.

· Density and/or relative density

· Density at 20 °C:

1,01 g/cm³

· Relative density

Not determined.

· Vapour density

Not determined.

(Contd. on page 7)

— MT —

Trade name: **PEROXAN M64 AX**

(Contd. of page 6)

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void
· Other safety characteristics	
· Active oxygen	7,3 - 7,7 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.
· Additional information:	Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· Acute toxicity	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
Oral	LD50	3.200 mg/kg (rattus)
Dermal	LD50	18.900 mg/kg (caviinae)

(Contd. on page 8)

MT

Trade name: **PEROXAN M64 AX**

(Contd. of page 7)

123-42-2 4-hydroxy-4-methylpentan-2-one		
Oral	LD50	3.002 mg/kg (rattus)
1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane		
Oral	LD50	1.017 mg/kg (rattus)
37187-22-7 2,4-Pentanedione, peroxide		
Oral	LD50	>2.000 mg/kg (rattus)
Dermal	LD0	>2.000 mg/kg (rattus)
123-54-6 pentane-2,4-dione		
Oral	LD50	575 mg/kg (rattus)
Dermal	LD50	790 mg/kg (rattus)
Inhalative	LC50 / 4h	5,1 mg/l (rattus)
<ul style="list-style-type: none"> · Skin corrosion/irritation Causes severe skin burns and eye damage. · Serious eye damage/irritation Causes serious eye damage. · Respiratory or skin sensitisation May cause an allergic skin reaction. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Suspected of damaging the unborn child. · STOT-single exposure May cause respiratory irritation. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. 		
11.2 Information on other hazards		
<ul style="list-style-type: none"> · Endocrine disrupting properties 		
78-93-3	butanone	List II

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

LC50 / 96h 44,2 mg/l (-)

78-93-3 butanone

LC50 / 96h 3.220 mg/l (pimephales promelas)

EC50 / 48h 5.091 mg/l (daphnia magna)

123-54-6 pentane-2,4-dione

LC50 / 96h 72 mg/l (oncorhynchus mykiss)

EC50 / 48h 75 mg/l (daphnia magna)

12.2 Persistence and degradability

Degree of elimination:

Classification:

6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Degradation (Readily biodegradable, failing 10-d wind) (OECD 301 B)

123-42-2 4-hydroxy-4-methylpentan-2-one

Degradation (Readily biodegradable) (OECD 301 A)

1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

Degradation (Readily biodegradable) (OECD 301 B)

78-93-3 butanone

Degradation (Readily biodegradable) (OECD 301 D)

7722-84-1 hydrogen peroxide solution

Degradation (Readily biodegradable)

123-54-6 pentane-2,4-dione

Degradation (Readily biodegradable) (OECD 301 C)

12.3 Bioaccumulative potential

Partition coefficient: nOctanol/water: [Log Kow]

123-42-2	4-hydroxy-4-methylpentan-2-one	-0,09 (20°C)
1338-23-4	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane	2,04 (25°C)
78-93-3	butanone	0,3 (40°C)
7722-84-1	hydrogen peroxide solution	-1,57 (20°C)

(Contd. on page 9)

MT

Trade name: PEROXAN M64 AX

(Contd. of page 8)

123-54-6	pentane-2,4-dione	0,68 (20 °C)
102-82-9	tributylamine	3,34 (25 °C)
· Bioconcentration factor (BCF)		
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
BCF	183-194 (piscis)	
· 12.4 Mobility in soil	No further relevant information available.	
· 12.5 Results of PBT and vPvB assessment		
· PBT:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.	
· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.	
· 12.6 Endocrine disrupting properties	For information on endocrine disrupting properties see section 11.	
· 12.7 Other adverse effects		
· Remark:	Harmful to fish	
· Additional ecological information:		
· General notes:	Must not reach sewage water or drainage ditch undiluted or unneutralised. Harmful to aquatic organisms Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.	

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

· Uncleaned packaging:

· Recommendation:

This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number	UN3105
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S), ACETYL ACETONE PEROXIDE)
· ADR	
· IMDG, IATA	ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S), ACETYL ACETONE PEROXIDE)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	5.2 (P1) Organic peroxides.
· Label	5.2
· IMDG, IATA	
· Class	5.2 Organic peroxides.
· Label	5.2
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Organic peroxides.
· Hazard identification number (Kemler code):	-

(Contd. on page 10)

MT

Trade name: **PEROXAN M64 AX**

(Contd. of page 9)

· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	125 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· RID / GGVSEB:	like ADR
· IMDG	
· Limited quantities (LQ)	125 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances**
- **- ANNEX I** None of the ingredients is listed.
- **Seveso category** P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Regulation (EC) No 273/2004 on drug precursors**

78-93-3	butanone	3
---------	----------	---

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

78-93-3	butanone	3
---------	----------	---

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:** Tel: +49 2871 9902-0
E-mail: mail@pergan.com
- **Version number of previous version:** 8
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

— MT —

Trade name: **PEROXAN M64 AX**

(Contd. of page 10)

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Ox. Liq. 1: Oxidizing liquids – Category 1
Org. Perox. D: Organic peroxides – Type C/D
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the
previous version altered.

— MT —