

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**  

**PEROXAN ME-50 LM4 X**
- **Trade name:**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  

No further relevant information available.
- **Application of the substance / the mixture**  

Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  

PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:**  


Competent person:  
\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com  
Security of labour
- **1.4 Emergency telephone number:**  

- Tel: +49 2871 9902-0

## \* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Org. Perox. D	H242	Heating may cause a fire.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Muta. 2	H341	Suspected of causing genetic defects.
Carc. 2	H351	Suspected of causing cancer.
Repr. 2	H361d	Suspected of damaging the unborn child.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
- **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08
- **Signal word**  

Danger
- **Hazard-determining components of labelling:**  

Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane  
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate  
tert-butyl hydroperoxide  
4-hydroxy-4-methylpentan-2-one
- **Hazard statements**

H242 Heating may cause a fire.  
H332 Harmful if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H341 Suspected of causing genetic defects.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).  
P234 Keep only in original packaging.  
P264 Wash thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

MT —

**Trade name: PEROXAN ME-50 LM4 X**

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER/doctor.  
P310 Store locked up.  
P405 Protect from sunlight.  
P410 Store at temperatures not exceeding +30°C. Keep cool.  
P411+P235 Store separately.  
P420 Dispose of contents/container in accordance with local/regional/national/international regulations.  
P501

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.  
· **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· **Determination of endocrine-disrupting properties**

78-93-3	butanone	List II
---------	----------	---------

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

· **Dangerous components:**

CAS: 6846-50-0 EINECS: 229-934-9 Reg-No.: 01-2119451093-47	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2, H361d; Aquatic Chronic 3, H412	30-50%
CAS: 1338-23-4 EC number: 700-954-4 Reg-No.: 01-2119514691-43	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane Org. Perox. D, H242; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	25-40%
CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Repr. 2, H361d; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	2,5-20%
CAS: 75-91-2 EINECS: 200-915-7 Reg-No.: 01-2119446670-40	tert-butyl hydroperoxide Flam. Liq. 3, H226; Org. Perox. F, H242; Acute Tox. 3, H311; Acute Tox. 2, H330; Muta. 2, H341; Carc. 2, H351; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limits: Eye Dam. 1; H318: C ≥ 1 % Skin Sens. 1; H317: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	2,5-5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg-No.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	0,1-5%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 % Skin Corr. 1B; H314: 50 % ≤ C < 70 % Skin Irrit. 2; H315: 35 % ≤ C < 50 % Eye Dam. 1; H318: C ≥ 8 % Eye Irrit. 2; H319: 5 % ≤ C < 8 % STOT SE 3; C ≥ 35 % Ox. Liq. 1; H271: C ≥ 70 % Ox. Liq. 2; H272: 50 % ≤ C < 70 %	0,1-5%
CAS: 102-82-9 EINECS: 203-058-7 Reg-No.: 01-2119474898-14	tributylamine Acute Tox. 3, H311; Acute Tox. 1, H330; Acute Tox. 4, H302; Skin Irrit. 2, H315	0-1%

- **Additional information:** tert-butyl hydroperoxide 70%ig in water  
For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)  
MT

**Trade name: PEROXAN ME-50 LM4 X**

(Contd. of page 2)

Remove breathing equipment only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.




Take care of personal protection for the first aider.

- **After inhalation:** Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.  
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbon dioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.  
Self-protection first!

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal.  
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.  
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
Do not refill residue into storage receptacles.  
Restrict the quantity stored at the work place.  
Use only in well ventilated areas.

(Contd. on page 4)

MT

Trade name: **PEROXAN ME-50 LM4 X**

(Contd. of page 3)

Before break and at the end of work hands should be thoroughly washed.  
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
Avoid contact with skin and eyes.  
While using do not eat, drink or smoke.  
Avoid shock and friction.



Do not smoke.

**Information about fire - and explosion protection:**

Protect from heat.  
Prevent impact and friction.  
Keep respiratory protective device available.  
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.

**Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
Prevent any seepage into the ground.  
Use only receptacles specifically permitted for this substance/product.

**Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
Store away from foodstuffs, drinks and feeding stuffs.

**Further information about storage conditions:** Keep container tightly sealed.  
Protect from heat and direct sunlight.  
Protect from contamination.  
Store under lock and key and out of the reach of children.  
Storage in a collecting room is required.

**Recommended storage temperature (To maintain quality):** 0 .... +30 °C

**Storage class:** 5.2

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

#### 123-42-2 4-hydroxy-4-methylpentan-2-one

WEL (Great Britain)	Short-term value: 362 mg/m <sup>3</sup> , 75 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
---------------------	---

#### 78-93-3 butanone

IOELV (EU)	Short-term value: 900 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm
WEL (Great Britain)	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV

#### 7722-84-1 hydrogen peroxide solution

WEL (Great Britain)	Short-term value: 2,8 mg/m <sup>3</sup> , 2 ppm Long-term value: 1,4 mg/m <sup>3</sup> , 1 ppm
---------------------	---

### DNELs

#### 6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	17,62 mg/m <sup>3</sup> (Worker)

#### 1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane

Dermal	DNEL Longterm System	1,43 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Systemic	7,55 mg/m <sup>3</sup>

(Contd. on page 5)

MT



## Trade name: PEROXAN ME-50 LM4 X

(Contd. of page 5)

PNEC Freshwater	0,008 mg/l (AF 1.000)
PNEC Freshwater sed	35,85 mg/kg sed dw
PNEC Soil	7,17 mg/kg soil dw
PNEC STP	100 mg/l (AF 1)
PNEC Marinewater	0,0008 mg/l (AF 10.000)

### · Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV (Great Britain)	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Appropriate engineering controls

No further data; see section 7.

#### · Individual protection measures, such as personal protective equipment

#### · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid close or long term contact with the skin.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Use skin protection cream for skin protection.  
Be sure to clean skin thoroughly after work and before breaks.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

#### · Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.  
Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
Nitrile rubber, NBR  
Neoprene

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection



Tightly sealed goggles

#### · Body protection:



Protective work clothing

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

#### · Physical state

Fluid

#### · Colour:

Colourless

#### · Odour:

Characteristic

#### · Odour threshold:

Not determined.

#### · Melting point/freezing point:

Not applicable.

#### · Boiling point or initial boiling point and boiling range

Not applicable.

#### · Flammability

May cause fire.

(Contd. on page 7)

MT

Trade name: **PEROXAN ME-50 LM4 X**

(Contd. of page 6)

<ul style="list-style-type: none"> <li>· Lower and upper explosion limit</li> <li>· Lower:</li> <li>· Upper:</li> <li>· Flash point:</li> <li>· Decomposition temperature:</li> <li>· pH</li> <li>· Viscosity:</li> <li>· Kinematic viscosity</li> <li>· Dynamic at 20 °C:</li> <li>· Solubility</li> <li>· water:</li> <li>· Partition coefficient n-octanol/water (log value)</li> <li>· Vapour pressure:</li> <li>· Density and/or relative density</li> <li>· Density at 20 °C:</li> <li>· Relative density</li> <li>· Vapour density</li> </ul>	<ul style="list-style-type: none"> <li>Not determined.</li> <li>Not determined.</li> <li>&gt; SADT</li> <li>+60 °C (SADT)</li> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>17 mPas</li> <li>Undetermined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>1,011 g/cm<sup>3</sup></li> <li>Not determined.</li> <li>Not determined.</li> </ul>
<ul style="list-style-type: none"> <li>· 9.2 Other information</li> <li>· Appearance:</li> <li>· Form:</li> <li>· Important information on protection of health and environment, and on safety.</li> <li>· Ignition temperature:</li> <li>· Explosive properties:</li> <li>· Change in condition</li> <li>· Evaporation rate</li> </ul>	<ul style="list-style-type: none"> <li>Fluid</li> <li>Product is not selfigniting.</li> <li>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</li> <li>Not determined.</li> </ul>
<ul style="list-style-type: none"> <li>· Information with regard to physical hazard classes</li> <li>· Explosives</li> <li>· Flammable gases</li> <li>· Aerosols</li> <li>· Oxidising gases</li> <li>· Gases under pressure</li> <li>· Flammable liquids</li> <li>· Flammable solids</li> <li>· Self-reactive substances and mixtures</li> <li>· Pyrophoric liquids</li> <li>· Pyrophoric solids</li> <li>· Self-heating substances and mixtures</li> <li>· Substances and mixtures, which emit flammable gases in contact with water</li> <li>· Oxidising liquids</li> <li>· Oxidising solids</li> <li>· Organic peroxides</li> <li>· Corrosive to metals</li> <li>· Desensitised explosives</li> <li>· Other safety characteristics</li> <li>· Active oxygen</li> </ul>	<ul style="list-style-type: none"> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>8,9 - 9,4 %</li> </ul>

## SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> <li>· 10.1 Reactivity</li> <li>· 10.2 Chemical stability</li> <li>· Thermal decomposition / conditions to be avoided:</li> <li>· 10.3 Possibility of hazardous reactions</li> <li>· 10.4 Conditions to avoid</li> </ul>	<ul style="list-style-type: none"> <li>No further relevant information available.</li> <li>SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.</li> <li>No decomposition if used and stored according to specifications.</li> <li>To avoid thermal decomposition do not overheat.</li> <li>Self-accelerating decomposition at SADT.</li> <li>No further relevant information available.</li> </ul>
--	---

(Contd. on page 8)

MT



**Trade name: PEROXAN ME-50 LM4 X**

(Contd. of page 7)

- **10.5 Incompatible materials:** Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
- **10.6 Hazardous decomposition products:** Hydrocarbons, carbondioxide and -monoxid.  
No hazardous decomposition products if used and stored according to specifications.
- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

**\* SECTION 11: Toxicological information**

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate**

Oral	LD50	3.200 mg/kg (rattus)
Dermal	LD50	18.900 mg/kg (caviinae)

**1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

Oral	LD50	1.017 mg/kg (rattus)
------	------	----------------------

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	LD50	3.002 mg/kg (rattus)
------	------	----------------------

**75-91-2 tert-butyl hydroperoxide**

Oral	LD50	805 mg/kg /(70%) (rattus)
Dermal	LD50	633 mg/kg /(70%) (cuniculosus)
Inhalative	LC50 / 4h	1,2 mg/l /(70%) (rattus)

**102-82-9 tributylamine**

Oral	LD50	540 mg/kg (rattus)
Dermal	LD50	250 mg/kg (cuniculosus)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Suspected of causing genetic defects.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3	butanone	List II
---------	----------	---------

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane**

LC50 / 96h	44,2 mg/l (-)
------------	---------------

**75-91-2 tert-butyl hydroperoxide**

EC50 / 72h	2,1 mg/l /(70%) (selenastrum capricornutum)
LC50 / 96h	42,3 mg/l /(70%) (pimephales promelas)
EC50	24,3 mg/l /(70%) (activa sludge)
EC50 / 48h	20 mg/l /(70%) (daphnia magna)

**78-93-3 butanone**

LC50 / 96h	3.220 mg/l (pimephales promelas)
EC50 / 48h	5.091 mg/l (daphnia magna)

· **12.2 Persistence and degradability**

· **Degree of elimination:**

· **Classification:**

**6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate**

Degradation	(Readily biodegradable, failing 10-d wind) (OECD 301 B)
-------------	---

(Contd. on page 9)

MT



**Trade name: PEROXAN ME-50 LM4 X**

(Contd. of page 8)

1338-23-4 Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane		
Degradation	(Readily biodegradable) (OECD 301 B)	
123-42-2 4-hydroxy-4-methylpentan-2-one		
Degradation	(Readily biodegradable) (OECD 301 A)	
75-91-2 tert-butyl hydroperoxide		
Degradation	(Not readily biodegradable) (OECD 301 D)	
78-93-3 butanone		
Degradation	(Readily biodegradable) (OECD 301 D)	
7722-84-1 hydrogen peroxide solution		
Degradation	(Readily biodegradable)	
102-82-9 tributylamine		
Degradation	(Readily biodegradable) (OECD 301 B)	
12.3 Bioaccumulative potential		
Partition coefficient: nOctanol/water: [Log Kow]		
1338-23-4	Reaction mass of butane-2,2-diyl dihydroperoxide and di-sec-butylhexaoxidane	2,04 (25°C)
123-42-2	4-hydroxy-4-methylpentan-2-one	-0,09 (20°C)
75-91-2	tert-butyl hydroperoxide	0,85 (30 °C)
78-93-3	butanone	0,3 (40°C)
7722-84-1	hydrogen peroxide solution	-1,57 (20°C)
102-82-9	tributylamine	3,34 (25 °C)
110-05-4	di-tert-butyl peroxide	3,2 (22°C)
Bioconcentration factor (BCF)		
6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate		
BCF	183-194 (piscis)	
102-82-9 tributylamine		
BCF	7,3	
12.4 Mobility in soil		
No further relevant information available.		
12.5 Results of PBT and vPvB assessment		
PBT:		
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
vPvB:		
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
12.6 Endocrine disrupting properties		
For information on endocrine disrupting properties see section 11.		
12.7 Other adverse effects		
Remark:		
Harmful to fish		
Additional ecological information:		
General notes:		
Must not reach sewage water or drainage ditch undiluted or unneutralised.		
Harmful to aquatic organisms		
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water		
Do not allow product to reach ground water, water course or sewage system.		
Danger to drinking water if even small quantities leak into the ground.		

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Recommendation



After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

##### Uncleaned packaging:

##### Recommendation:

This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

##### ADR, IMDG, IATA



UN3105

(Contd. on page 10)

MT

Trade name: **PEROXAN ME-50 LM4 X**

(Contd. of page 9)

· 14.2 UN proper shipping name · ADR · IMDG, IATA		UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S)) ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ETHYL KETONE PEROXIDE(S))
· 14.3 Transport hazard class(es) · ADR  · Class · Label		5.2 (P1) Organic peroxides. 5.2
· IMDG, IATA  · Class · Label		5.2 Organic peroxides. 5.2
· 14.4 Packing group · ADR, IMDG, IATA		Void
· 14.5 Environmental hazards:		Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · Stowage Category · Stowage Code · Segregation Code		Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.
· 14.7 Maritime transport in bulk according to IMO instruments		Not applicable.
· Transport/Additional information:		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)		125 ml Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code		2 D
· RID / GGVSEB:		like ADR
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)		125 ml Code: E0 Not permitted as Excepted Quantity

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances
  - ANNEX I None of the ingredients is listed.
- Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)

— MT —

**Trade name: PEROXAN ME-50 LM4 X**

(Contd. of page 10)

· <b>DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II</b>		
None of the ingredients is listed.		
· <b>REGULATION (EU) 2019/1148</b>		
· <b>Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))</b>		
None of the ingredients is listed.		
· <b>Annex II - REPORTABLE EXPLOSIVES PRECURSORS</b>		
None of the ingredients is listed.		
· <b>Regulation (EC) No 273/2004 on drug precursors</b>		
78-93-3	butanone	3
· <b>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</b>		
78-93-3	butanone	3

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· <b>Contact:</b>	Tel: +49 2871 9902-0 E-mail: mail@pergan.com
· <b>Version number of previous version:</b>	6
· <b>Abbreviations and acronyms:</b>	<p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</p> <p>IMDG: International Maritime Code for Dangerous Goods</p> <p>IATA: International Air Transport Association</p> <p>GHS: Globally Harmonised System of Classification and Labelling of Chemicals</p> <p>EINECS: European Inventory of Existing Commercial Chemical Substances</p> <p>ELINCS: European List of Notified Chemical Substances</p> <p>CAS: Chemical Abstracts Service (division of the American Chemical Society)</p> <p>DNEL: Derived No-Effect Level (REACH)</p> <p>PNEC: Predicted No-Effect Concentration (REACH)</p> <p>LC50: Lethal concentration, 50 percent</p> <p>LD50: Lethal dose, 50 percent</p> <p>PBT: Persistent, Bioaccumulative and Toxic</p> <p>vPvB: very Persistent and very Bioaccumulative</p> <p>Flam. Liq. 2: Flammable liquids – Category 2</p> <p>Flam. Liq. 3: Flammable liquids – Category 3</p> <p>Ox. Liq. 1: Oxidizing liquids – Category 1</p> <p>Org. Perox. D: Organic peroxides – Type C/D</p> <p>Org. Perox. F: Organic peroxides – Type E/F</p> <p>Acute Tox. 4: Acute toxicity – Category 4</p> <p>Acute Tox. 3: Acute toxicity – Category 3</p> <p>Acute Tox. 1: Acute toxicity – Category 1</p> <p>Acute Tox. 2: Acute toxicity – Category 2</p> <p>Skin Corr. 1A: Skin corrosion/irritation – Category 1A</p> <p>Skin Corr. 1B: Skin corrosion/irritation – Category 1B</p> <p>Skin Corr. 1C: Skin corrosion/irritation – Category 1C</p> <p>Skin Irrit. 2: Skin corrosion/irritation – Category 2</p> <p>Eye Dam. 1: Serious eye damage/eye irritation – Category 1</p> <p>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</p> <p>Skin Sens. 1: Skin sensitisation – Category 1</p> <p>Muta. 2: Germ cell mutagenicity – Category 2</p> <p>Carc. 2: Carcinogenicity – Category 2</p> <p>Repr. 2: Reproductive toxicity – Category 2</p> <p>STOT SE 3: Specific target organ toxicity (single exposure) – Category 3</p> <p>Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2</p> <p>Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>

· \* Data compared to the previous version altered.