

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN NPO-50

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from: Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Org. Perox. F H242 Heating may cause a fire.
Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.



· Signal word Warning

· Hazard-determining

components of labelling: Hazard statements

Di-(3,5,5-trimethylhexanoyl)-peroxide H226 Flammable liquid and vapour. H242 Heating may cause a fire. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P234 Keep only in original packaging.
P243 Take action to prevent static discharges.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding 0°C. Keep cool.

P420 Store separately

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrine-

disrupting propertiesThe product does not contain substances with endocrine disrupting properties.

— мт -



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 3851-87-4	Di-(3,5,5-trimethylhexanoyl)-peroxide	50-60%
EINECS: 223-356-0	Org. Perox. D, H242; Skin Irrit. 2, H315; Skin Sens. 1B, H317	
Reg-No.: 01-2119966134-37		
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	40-50%
EINECS: 297-629-8	Alternative CAS number: 13475-82-6	
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

· After eye contact:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

After swallowing:

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available.

If symptoms persist consult doctor.

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters · Protective equipment:

· Additional information

Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

After exceeding the emergency temperature must be diluted with a suitable desentisation agent to < 10 %.

In case of further temperature should be cooled with waterspray from a safe distance.

Take precautionary measures against static discharges.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections In case of large spillage the environmental authority should be informed.

MT



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

(Contd. of page 2)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed. Keep away from heat and direct sunlight. Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

The product must be preserved, stored and transported continously cool. Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage: Requirements to be met by Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in

one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about

storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight.

Protect from contamination.

Recommended storage temperature (To maintain

quality):

-8 5°C +10°C

Control temperature: Emergency temperature: · Storage class:

+15°C 5.2

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

· DNELs

3851-87-4 Di-(3,5,5-trimethylhexanoyl)-peroxide

Dermal DNEL Longterm System | 0,67 mg/kg bw/day (Worker)

(Contd. on page 4)



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

(Contd. of page 3)

Inhalative DNEL Longterm System 1,18 mg/m3 (Worker)

· PNECs

3851-87-4 Di-(3,5,5-trimethylhexanoyl)-peroxide

PNEC Marinewater sed PNEC Freshwater 0,073 mg/l (AF 100)
PNEC Freshwater sed PNEC Soil 0,054 mg/kg sed dw (-)
PNEC STP 75 mg/l (AF 10)
PNEC Marinewater 0,0073 mg/l (AF 1.000)

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-pro

Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Filter A2

Protective gloves

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour:

· Melting point/freezing point:

Boiling point or initial boiling point and boiling range

Flash point:

Decomposition temperature:

Viscosity:

Odour:

Dynamic at 20 °C:

Solubility

· water:
· Partition coefficient n-octanol/water (log value)

Colourless

Characteristic Undetermined. Undetermined.

> 53 °C 25 °C (SADT)

77 mPas

Not miscible or difficult to mix.

not determined

(Contd. on page 5)



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

(Contd. of page 4)

· Density and/or relative density

 Density at 20 °C: 0,825 g/cm3

· 9.2 Other information

· Appearance:

Fluid Form:

· Important information on protection of health and environment, and on safety.

Product is not selfigniting. Ignition temperature:

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void **Aerosols** Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in Void

contact with water · Oxidising liquids Void Oxidising solids Void

· Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions · 10.4 Conditions to avoid

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

3851-87-4 Di-(3,5,5-trimethylhexanoyl)-peroxide

LD50 >5.000 mg/kg (rattus) Dermal LD50 >2.000 mg/kg (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

LD50 >5.000 mg/kg (rattus)

 Skin corrosion/irritation Causes skin irritation.

(Contd. on page 6)



(Contd. of page 5)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

Serious eye damage/irritation Low irritant effect Respiratory or skin

May cause an allergic skin reaction.

sensitisation Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h >0,04 mg/l (daphnia) IC50 / 72h >0,04 mg/l (algae)

12.2 Persistence and degradability

· Degree of elimination:

Classification:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

· 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · PBT: · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-· Waste disposal key:

number.

· Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG UN3119 · 14.2 UN proper shipping name · ADR UN3119 ORGANIC PEROXIDE TYPE F. LIQUID. TEMPERATURE CONTROLLED (DI-(3,5,5-TRIMETHYLHEXANOYL) PEROXIDE) ·IMDG ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLED

(DI-(3,5,5-TRIMETHYLHEXANOYL) PEROXIDE)

(Contd. on page 7)



Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR 5.2 (P2) Organic peroxides. Label · IMDG Class 5.2 Organic peroxides. · Label 5.2 · IATA · Class Χ · Label Χ · 14.4 Packing group · ADR, IMDG Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Organic peroxides. · Hazard identification number (Kemler code): Stowage Category Stowage Code SW1 Protected from sources of heat. SW3 Shall be transported under temperature control. · Segregation Code SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D · RID / GGVSEB: no admission · Limited quantities (LQ) 0 · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · IATA · Remarks: no admission · Control temperature: +10°C Emergency temperature: +15°C

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances

- ANNEX I None of the ingredients is listed.

• Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

(Contd. on page 8)



(Contd. of page 7)

Printing date 04.04.2024 Version: 9 (replaces version 8) Revision: 25.10.2023

Trade name: PEROXAN NPO-50

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Environment protection / Security of labour Department issuing SDS:

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Version number of previous

version:

· Abbreviations and acronyms:

8 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. D: Organic peroxides – Type C/D
Org. Perox. F: Organic peroxides – Type E/F
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

·* Data compared to the previous version altered.

MT