

Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PA-50 · Trade name:

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from:

Environment protection / Security of labour Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

- Tel: +49 2871 9902-0 number:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Org. Perox. C H242 Heating may cause a fire.

Acute Tox. 3 H331 Toxic if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.







GHS02 GHS06 GHS08 GHS09

· Signal word Danger

· Hazard-determining

components of labelling:

tert-butyl peracetate

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

· Hazard statements H226 Flammable liquid and vapour. H242 Heating may cause a fire.

H331 Toxic if inhaled.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines).

P234 Keep only in original packaging. P243 Take action to prevent static discharges.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up. P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +10°C. Keep cool.

(Contd. on page 2)



(Contd. of page 1)

Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvR· The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrinedisrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:		
CAS: 107-71-1	tert-butyl peracetate	50-60%
EINECS: 203-514-5	Flam. Lig. 3, H226; Org. Perox. C, H242; Acute Tox. 3, H331; Aquatic Chronic 2, H411; Eye Irrit. 2,	
Reg-No.: 01-2120759514-49	H319; Skin Sens. 1, H317	
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	40-50%
EINECS: 297-629-8	Alternative CAS number: 13475-82-6	
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
Additional informations	For the wording of the listed beyond phrones refer to continue 16	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate

medical attention and special

treatment needed

No further relevant information available.

No further relevant information available

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents:

Water with full iet

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

· 5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases. Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

(Contd. of page 2)

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel). Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines).

While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage: Requirements to be met by Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination

Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

-15 +10 °C

Storage class:

5.2

(Contd. on page 4)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

•	u	N	ᆮ	LS

107-71-1 tert-butyl peracetate

Dermal	DNEL Longterm System	1 mg/kg bw/day (Worker)
Inhalative	DNEL Acute Local	13,4 mg/m3 (Worker)
	DNEL Longterm System	4,46 mg/m3 (Worker)

PNECs

107-71-1 tert-butyl peracetate

PNEC Freshwater	0,004 mg/l (AF 1.000)
PNEC Freshwater sed	0,03 mg/kg sed dw (-)
PNEC Soil	0,0035 mg/kg soil dw (-)
PNEC STP	0,07 mg/l (AF 10)
PNEC Marinewater	0,0004 mg/l (AF 10.000)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: Not necessary if room is well-ventilated.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

Only use chemical-protective gloves with CE-labelling of category III. · Hand protection



Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Protective gloves

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

MT -



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· General Information

· Colour: Colourless Characteristic · Odour: Odour threshold: Not determined. · Melting point/freezing point: Not applicable. Boiling point or initial boiling point and boiling range Not applicable.

Not applicable. Flammability

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. 35 °C Flash point: Decomposition temperature: > +70 °C (SADT)

Not determined. · pH

Viscosity:

Kinematic viscosity Not determined Dynamic: Not determined.

Solubility · water:

Undetermined. Partition coefficient n-octanol/water (log value) not determined · Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C: 0,835 q/cm³ Relative density Not determined · Vapour density Not determined.

· 9.2 Other information No further relevant information available.

· Appearance:

· Form: Fluid · Important information on protection of health and environment,

and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Change in condition Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in

contact with water Void Oxidising liquids Void · Oxidising solids Void

Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

(Contd. on page 6)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

No decomposition if used and stored according to specifications.

(Contd. of page 5)

· 10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid

To avoid thermal decomposition do not overheat.

· 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Toxic if inhaled.

			_		-
· LD/LC50	values	relevant	for c	lassifica	tion:

Oral	LD50	3.843 mg/kg (rattus)
Dermal	LD50	7.136 mg/kg (rabbit)
Inhalative	LC50 / 4h	9,2 mg/l (rattus)

107-71-1 tert-butyl peracetate

Oral	LD50	2.562 mg/kg (rattus)
Dermal	LD50	4.757 mg/kg (rabbit)
Inhalative	LC50 / 4h	6,1 mg/l (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

LD50 >5.000 mg/kg (rattus)

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

· Respiratory or skin

Causes serious eye irritation.

sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

107-71-1 tert-butyl peracetate

EC50 / 72h 6,4 mg/l (pseudokirchneriella subcapitata)

LC50 / 96h 39,6 mg/l (brachydanio rerio)

EC50 / 48h 4,31 mg/l (daphnia)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h >0,04 mg/l (daphnia) IC50 / 72h >0,04 mg/l (algae)

12.2 Persistence and degradability

· Degree of elimination:

· Classification:

107-71-1 tert-butyl peracetate

Degradation (Not readily biodegradable)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

(Contd. on page 7)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

· 12.3 Bioaccumulative potential

(Contd. of page 6)

· Partition coefficient: nOctanol/water: [Log Kow] 107-71-1 tert-butyl peracetate

No further relevant information available. 12.4 Mobility in soil

1,6 (25°C)

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

No further relevant information available. 12.7 Other adverse effects

· Additional ecological information:

· General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e.g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

· Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA UN3103

· 14.2 UN proper shipping name

UN3103 ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL · ADR PEROXYACETAT), ENVIRONMENTALLY HAZARDOUS

·IMDG ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETAT),

MARINE POLLUTANT

· IATA ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETAT)

· 14.3 Transport hazard class(es)

· ADR





· Class 5.2 (P1) Organic peroxides. Label

· IMDG





Class 5.2 Organic peroxides. Label 5.2

· IATA



Class 5.2 Organic peroxides. · Label 5.2

14.4 Packing group

· ADR, IMDG, IATA Void

(Contd. on page 8)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

(Contd. of page 7)

· 14.5 Environmental hazards:

Marine pollutant: Symbol (fish and tree)
 Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

Stowage Code S

Stowage Code
SW1 Protected from sources of heat.
Segregation Code
SG35 Stow "separated from" SGG1-acids
SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ) 25 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Transport category 1
Tunnel restriction code D

· RID / GGVSEB: like ADR

·IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I None of the ingredients is listed.

• Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

5

Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Version number of previous

version:

(Contd. on page 9)



Printing date 04.04.2024 Version: 6 (replaces version 5) Revision: 14.02.2023

Trade name: PEROXAN PA-50

(Contd. of page 8)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

(Contd. of page RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
DBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. C: Organic peroxides – Type C/D
Acute Tox. 3: Acute toxicity – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

·* Data compared to the previous version altered.

MT —