

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**

Trade name:

PEROXAN PB-50 A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
- **Application of the substance / the mixture**

Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:**

Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:**





- Tel: +49 2871 9902-0

* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Org. Perox. C	H242	Heating may cause a fire.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS08 GHS09
- **Signal word**

Danger
- **Hazard-determining components of labelling:**

4-hydroxy-4-methylpentan-2-one
tert-butyl perbenzoate
2,4-Pentadione, peroxide
- **Hazard statements**

H242 Heating may cause a fire.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +30°C. Keep cool.
P420	Store separately.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Trade name: PEROXAN PB-50 A

(Contd. of page 1)

- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Dangerous components:

CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Repr. 2, H361d; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	30-40%
CAS: 614-45-9 EINECS: 210-382-2 Reg-No.: 01-2119513317-46	tert-butyl perbenzoate Org. Perox. C, H242; Aquatic Acute 1, H400; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-30%
CAS: 13784-51-5 EINECS: 237-438-9 Reg-No.: 01-2119965139-28	2,4-Pentadione, peroxide Alternative CAS number: 37187-22-7 Org. Perox. D, H242; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
CAS: 123-54-6 EINECS: 204-634-0 Index number: 606-029-00-0 Reg-No.: 01-2119458968-15	pentane-2,4-dione Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Acute Tox. 4, H302	5-10%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 70 % Skin Corr. 1B; H314: 50 % ≤ C < 70 % Skin Irrit. 2; H315: 35 % ≤ C < 50 % Eye Dam. 1; H318: C ≥ 8 % Eye Irrit. 2; H319: 5 % ≤ C < 8 % STOT SE 3; C ≥ 35 % Ox. Liq. 1; H271: C ≥ 70 % Ox. Liq. 2; H272: 50 % ≤ C < 70 %	0,1-2,5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:



Take care of personal protection for the first aider.

· After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.

· 5.3 Advice for firefighters

- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

(Contd. on page 3)

MT —

Trade name: **PEROXAN PB-50 A**

(Contd. of page 2)

Self-protection first!

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.
Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal.
Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Do not refill residue into storage receptacles.
Restrict the quantity stored at the work place.
Use only in well ventilated areas.
Before break and at the end of work hands should be thoroughly washed.
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
Avoid contact with skin and eyes.
While using do not eat, drink or smoke.
Avoid shock and friction.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.
Prevent impact and friction.
Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Pay attention to the special requirements of your local authorities for storing dangerous goods.

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.
Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.
Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed.
Protect from heat and direct sunlight.
Protect from contamination.

(Contd. on page 4)

— MT —

Trade name: **PEROXAN PB-50 A**

(Contd. of page 3)

Storage in a collecting room is required.

- **Recommended storage temperature (To maintain quality):** 0 +30 °C
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL (Great Britain) Short-term value: 362 mg/m³, 75 ppm
Long-term value: 241 mg/m³, 50 ppm

7722-84-1 hydrogen peroxide solution

WEL (Great Britain) Short-term value: 2,8 mg/m³, 2 ppm
Long-term value: 1,4 mg/m³, 1 ppm

· **DNELs**

123-42-2 4-hydroxy-4-methylpentan-2-one

Dermal	DNEL Longterm System	467 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	32,6 mg/m ³ (Worker)

614-45-9 tert-butyl perbenzoate

Dermal	DNEL Longterm System	17,5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	24,7 mg/m ³ (Worker)

13784-51-5 2,4-Pentadione, peroxide

Dermal	DNEL Longterm System	5 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	4,41 mg/m ³ (Worker)

123-54-6 pentane-2,4-dione

Dermal	DNEL Longterm System	12 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	84 mg/m ³ (Worker)

7722-84-1 hydrogen peroxide solution

Inhalative	DNEL Longterm Local	1,4 mg/m ³ (Worker)
------------	---------------------	--------------------------------

· **PNECs**

123-42-2 4-hydroxy-4-methylpentan-2-one

PNEC Marinewater sed	0,74 mg/kg sed dw
PNEC Freshwater	2 mg/l (AF 50)
PNEC Freshwater sed	7,4 mg/kg sed dw
PNEC Soil	0,31 mg/kg soil dw
PNEC STP	100 mg/l (AF 10)
PNEC Marinewater	0,2 mg/l (AF 500)

614-45-9 tert-butyl perbenzoate

PNEC Marinewater sed	0,028 mg/kg sed dw
PNEC Freshwater	0,01 mg/l (AF 10)
PNEC Freshwater sed	0,28 mg/kg sed dw
PNEC Soil	0,049 mg/kg soil dw
PNEC STP	0,6 mg/l (AF 10)
PNEC Marinewater	0,00101 mg/l (AF 100)

13784-51-5 2,4-Pentadione, peroxide

PNEC Marinewater sed	0,153 mg/kg sed dw (-)
PNEC Freshwater	0,17 mg/l (AF 10)
PNEC Freshwater sed	1,53 mg/kg sed dw (-)
PNEC Soil	0,2 mg/kg soil dw (-)
PNEC STP	6,2 mg/l (AF 10)
PNEC Marinewater	0,017 mg/l (AF 100)

123-54-6 pentane-2,4-dione

PNEC Marinewater sed	0,191 mg/kg sed dw
PNEC Freshwater	0,2 mg/l (AF 50)
PNEC Freshwater sed	1,909 mg/kg sed dw

(Contd. on page 5)

MT

Trade name: PEROXAN PB-50 A

(Contd. of page 4)

PNEC Soil	0,193 mg/kg soil dw (-)
PNEC STP	1,32 mg/l (AF 10)
PNEC Marinewater	0,02 mg/l (AF 500)
7722-84-1 hydrogen peroxide solution	
PNEC Marinewater sed	0,047 mg/kg sed dw
PNEC Freshwater	0,013 mg/l (AF 50)
PNEC Freshwater sed	0,047 mg/kg sed dw
PNEC Soil	0,002 mg/kg soil dw
PNEC STP	4,66 mg/l (AF 100)
PNEC Marinewater	0,013 mg/l (AF 50)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· **Hand protection**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Butyl rubber, BR
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

colourless - yellowish

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not applicable.

· **Boiling point or initial boiling point and boiling range**

Not applicable.

· **Flammability**

May cause fire.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

(Contd. on page 6)

MT

Trade name: **PEROXAN PB-50 A**

(Contd. of page 5)

· Upper:	Not determined.
· Flash point:	> SADT
· Decomposition temperature:	> +60 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	15 mPas
· Solubility	
· water:	Undetermined.
· Partition coefficient n-octanol/water (log value)	not determined.
	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1,05 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void
· Other safety characteristics	
· Active oxygen	4,7 - 5,0 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

(Contd. on page 7)

— MT —

Trade name: **PEROXAN PB-50 A**

(Contd. of page 6)

· **10.6 Hazardous decomposition products:**

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· **Additional information:**

Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

123-42-2 4-hydroxy-4-methylpentan-2-one

Oral	LD50	3.002 mg/kg (rattus)
------	------	----------------------

614-45-9 tert-butyl perbenzoate

Oral	LD50	4.838 mg/kg (rattus)
------	------	----------------------

Dermal	LD50	3.817 mg/kg (rattus)
--------	------	----------------------

Inhalative	LC100 4h	4,9 mg/l (rattus)
------------	----------	-------------------

	LC0 / 4h	1,01 mg/l (rattus)
--	----------	--------------------

13784-51-5 2,4-Pentadione, peroxide

Oral	LD50	>2.000 mg/kg (rattus)
------	------	-----------------------

123-54-6 pentane-2,4-dione

Oral	LD50	575 mg/kg (rattus)
------	------	--------------------

Dermal	LD50	790 mg/kg (rattus)
--------	------	--------------------

Inhalative	LC50 / 4h	5,1 mg/l (rattus)
------------	-----------	-------------------

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

· **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

· **Carcinogenicity**

Based on available data, the classification criteria are not met.

· **Reproductive toxicity**

Suspected of damaging the unborn child.

· **STOT-single exposure**

May cause respiratory irritation.

· **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

· **Aspiration hazard**

Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

13784-51-5 2,4-Pentadione, peroxide

EC50 / 72h	5,4 mg/l (alga (Süßwasser))
------------	-----------------------------

LC50 / 96h	67,7 mg/l (piscis)
------------	--------------------

EC50 / 48h	7,1 mg/l (daphnia magna)
------------	--------------------------

123-54-6 pentane-2,4-dione

LC50 / 96h	72 mg/l (oncorhynchus mykiss)
------------	-------------------------------

EC50 / 48h	75 mg/l (daphnia magna)
------------	-------------------------

· **12.2 Persistence and degradability**

· **Degree of elimination:**

· **Classification:**

123-42-2 4-hydroxy-4-methylpentan-2-one

Degradation	(Readily biodegradable) (OECD 301 A)
-------------	--------------------------------------

614-45-9 tert-butyl perbenzoate

Degradation	(Readily biodegradable) (OECD 301 D)
-------------	--------------------------------------

13784-51-5 2,4-Pentadione, peroxide

Degradation	(Readily biodegradable) (OECD 301 D)
-------------	--------------------------------------

(Contd. on page 8)

MT

Trade name: **PEROXAN PB-50 A**

(Contd. of page 8)

· Label	5.2
· IMDG	
· Class	5.2 Organic peroxides.
· Label	5.2
· IATA	
· Class	5.2 Organic peroxides.
· Label	5.2
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: tert-BUTYL PEROXYBENZOATE
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Organic peroxides.
· Hazard identification number (Kemler code):	-
· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	25 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· RID / GGVSEB:	like ADR
· IMDG	
· Limited quantities (LQ)	25 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I

None of the ingredients is listed.

· Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements

50 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

— MT —

Trade name: **PEROXAN PB-50 A**

(Contd. of page 9)

· **REGULATION (EU) 2019/1148**

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:** Tel: +49 2871 9902-0
E-mail: mail@pergan.com

· **Version number of previous version:**

8

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Ox. Liq. 1: Oxidizing liquids – Category 1
Org. Perox. C: Organic peroxides – Type C/D
Org. Perox. D: Organic peroxides – Type C/D
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

— MT —