

Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PEROXAN PIN · Trade name:

· CAS Number: 13122-18-4 236-050-7 · EC number:

Registration number: 01-2119498308-25

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from: Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Org. Perox. D H242 Heating may cause a fire.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining

components of labelling:

tert-Butylperoxy-3,5,5-trimethylhexanoate **Hazard statements**

H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators

(e. g. heavy metal compounds and amines).

P234 Keep only in original packaging. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

Protect from sunlight. P410

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

P420 Store separately.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII. · vPvR· This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Determination of endocrine-

The product does not contain substances with endocrine disrupting properties. disrupting properties

MT



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.1 Substances

CAS No. Description

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

· Identification number(s)

· EC number: 236-050-7

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

Rinse opened eye for several minutes under running water. After eye contact: If symptoms persist consult doctor.

After swallowing:

· 4.2 Most important symptoms and effects, both acute and

delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

· Protective equipment: Additional information

Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away. Inform respective authorities in case of seepage into water course or sewage system.

· 6.2 Environmental precautions:



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

7.1 Precautions for safe

handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight. Open and handle receptacle with care.

(Contd. on page 3)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 2)

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles.

Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by

storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Information about storage in

one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about

storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from contamination. Store in a cool place.

Store in a cool place.

Storage in a collecting room is required.

· Recommended storage temperature (To maintain

quality):

max.: +30°C

Storage class:

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace: Not required.

•	υ	N	E	LS

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

Dermal DNEL Longterm System 3,2 mg/kg bw/day (Worker)
Inhalative DNEL Longterm System 5,6 mg/m3 (Worker)

· PNECs

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

PNEC Marinewater sed | 0,05 mg/kg sed dw (-) PNEC Freshwater | 0,003 mg/l (AF 50)

(Contd. on page 4)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

PNEC Freshwater sed | 0,497 mg/kg sed dw (-)

(Contd. of page 3)

PNEC Soil 0,098 mg/kg soil dw (-) PNEC STP 2,6 mg/l (AF 10) **PNEC Marinewater** 0 mg/l (AF 500)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data: see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

The usual precautionary measures are to be adhered to when handling chemicals. hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: Not necessary if room is well-ventilated.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

<10 mPas

Undetermined.

not determined

degradation

Filter A2

Protective gloves · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

· Penetration time of glove

material

· Hand protection

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed

· Eye/face protection

Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless Odour: Characteristic · Melting point/freezing point: Not applicable. · Boiling point or initial boiling point and boiling range Not applicable. Flash point: > SADT Decomposition temperature: +60 °C (SADT)

· Viscosity:

Dynamic at 20 °C:

Solubility

· water:

· Partition coefficient n-octanol/water (log value)

· Density and/or relative density

Density at 20 °C: 0,89 g/cm³

· 9.2 Other information

Appearance:

· Form: Fluid

(Contd. on page 5)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 4)

Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in	
contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
Desensitised explosives	Void
Other safety characteristics	
· Active oxygen	> 6.8 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause

decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

10.4 Conditions to avoid

· 10.5 Incompatible materials:

No further relevant information available.

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

Self-accelerating decomposition at SADT.

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. · Acute toxicity

· LD/LC50 values relevant for classification:

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

LD50 >5.000 mg/kg (rattus) Oral LD50 >2.000 mg/kg (rattus) Dermal Inhalative LC50 / 4h >0,8 mg/l (rattus)

Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 5)

· STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

Substance is not listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

EC50 / 72h | 0,33 mg/l (algae)

LC50 / 96h | 7 mg/l (oncorhynchus mykiss)

EC50 / 48h > 100 mg/l (daphnia)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

13122-18-4 tert-Butylperoxy-3,5,5-trimethylhexanoate

Degradation (Readily biodegradable) (OECD 301 D)

12.3 Bioaccumulative potential

Partition coefficient: nOctanol/water: [Log Kow]

4,4 (25°C)

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII. · vPvR· This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Endocrine disrupting

properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects · Remark: Very toxic for fish

Additional ecological information:

General notes:

Very toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· ADR, IMDG, IATA UN3105

· 14.2 UN proper shipping name

· 14.1 UN number or ID number

· ADR

UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (tert-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE), ENVIRONMENTALLY HAZARDOUS · IMDG ORGANIC PEROXIDE TYPE D, LIQUID (tert-BUTYL PEROXY-3,5,5-

TRIMETHYLHEXANOATE), MARINE POLLUTANT

·IATA ORGANIC PEROXIDE TYPE D, LIQUID (tert-BUTYL PEROXY-3,5,5-TRIMETHYLHEXANOATE)

(Contd. on page 7)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR





Class 5.2 (P1) Organic peroxides. · Label

· IMDG





Class 5.2 Organic peroxides. · Label 5.2

· IATA



Class 5.2 Organic peroxides.

Label 5.2

· 14.4 Packing group · ADR, IMDG, IATA

Void

· 14.5 Environmental hazards: Product contains environmentally hazardous substances: tert-BUTYL

PEROXY-3,5,5-TRIMETHYLHEXANOATE · Marine pollutant:

Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code):

· Stowage Category

· Stowage Code SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. · Segregation Code

SG72 See 7.2.6.3.2.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 125 ml Code: E0 Excepted quantities (EQ)

Not permitted as Excepted Quantity Transport category D

Tunnel restriction code

· RID / GGVSEB: like ADR

· IMDG

· Limited quantities (LQ) 125 ml Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

· Named dangerous substances

- ANNEX I Substance is not listed.

Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier

requirements

50 t

(Contd. on page 8)



Printing date 04.04.2024 Version: 8 (replaces version 7) Revision: 16.02.2023

Trade name: PEROXAN PIN

(Contd. of page 7)

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex ш

Substance is not listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

Substance is not listed

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

Substance is not listed.

· Regulation (EC) No 273/2004 on drug precursors

Substance is not listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

Substance is not listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Version number of previous

version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the Abbreviations and acronyms:

International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent Bioaccumulative and Toxic

PB1. Persistent, Bloaccumulative and Toxic
VPVB: very Persistent and very Bioaccumulative
Org. Perox. D: Organic peroxides – Type C/D
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· * Data compared to the previous version altered.

МТ