

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN PO-50 P
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour  
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Org. Perox. E	H242	Heating may cause a fire.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 1B	H360F	May damage fertility.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
- **Hazard pictograms**

GHS02 GHS07 GHS08 GHS09
- **Signal word**  
Danger
- **Hazard-determining components of labelling:** tert-butyl 2-ethylperoxyhexanoate
- **Hazard statements**

H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.
H360F	May damage fertility.
H410	Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378	In case of fire: Use CO <sub>2</sub> , powder or water spray to extinguish.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +20°C. Keep cool.
P420	Store separately.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:** Restricted to professional users.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties**  
The product does not contain substances with endocrine disrupting properties.

Trade name: **PEROXAN PO-50 P**

(Contd. of page 1)

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Dangerous components:

CAS: 3006-82-4	tert-butyl 2-ethylperoxyhexanoate	40-50%
EINECS: 221-110-7	Org. Perox. C, H242; Repr. 1B, H360F; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Sens. 1,	
Reg-No.: 01-2119498310-40	H317	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information:



Take care of personal protection for the first aider.

##### After inhalation:

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.

##### After skin contact:

Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.

##### After eye contact:

Rinse opened eye for several minutes under running water.

##### After swallowing:

If symptoms persist consult doctor.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbondioxide and -monoxid.

#### 5.3 Advice for firefighters

##### Protective equipment:

Do not inhale explosion gases or combustion gases.

##### Additional information

Cool endangered receptacles with water spray.  
Self-protection first!

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.



Do not allow to enter sewers/ surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.  
Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.  
Pick up mechanically, collect in a suitable receptacle and dispose in accordance with government regulations.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.  
In case of large spillage the environmental authority should be informed.

Trade name: **PEROXAN PO-50 P**

(Contd. of page 2)

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.  
Open and handle receptacle with care.  
Prevent formation of dust.  
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
Do not refill residue into storage receptacles.  
Restrict the quantity stored at the work place.  
Before break and at the end of work hands should be thoroughly washed.  
Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
While using do not eat, drink or smoke.  
Do not generate flames or sparks.  
Keep product and emptied container away from heat and sources of ignition.  
Avoid shock and friction.  
Take precautionary measures against static discharges.



Do not smoke.

### Information about fire - and explosion protection:

Protect from heat.  
Protect against electrostatic charges.  
Prevent impact and friction.  
Use explosion-proof apparatus / fittings and spark-proof tools.  
Dust can combine with air to form an explosive mixture.  
Substance/product is oxidising when dry.  
Product is not explosive. However, formation of explosive air/dust mixtures are possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.

**Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
Prevent any seepage into the ground.  
Use only receptacles specifically permitted for this substance/product.

**Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
Store away from foodstuffs, drinks and feeding stuffs.

**Further information about storage conditions:** Protect from heat and direct sunlight.  
Protect from contamination.  
Storage in a collecting room is required.

**Recommended storage temperature (To maintain quality):**

max.: +15 °C

**Control temperature:** +20 °C

**Emergency temperature:** +25 °C

**Storage class:** 5.2

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### DNELs

#### 3006-82-4 tert-butyl 2-ethylperoxyhexanoate






Dermal	DNEL Longterm System	5,6 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	9,8 mg/m3 (Worker)

(Contd. on page 4)

MT —

Trade name: **PEROXAN PO-50 P**

(Contd. of page 3)

· <b>PNECs</b>	
<b>3006-82-4 tert-butyl 2-ethylperoxyhexanoate</b>	
PNEC Marinewater sed	0,0622 mg/kg sed dw
PNEC Freshwater	0,002 mg/l (AF 50)
PNEC Freshwater sed	0,622 mg/kg sed dw
PNEC STP	0,64 mg/l (AF 100)
PNEC Marinewater	0 mg/l (AF 500)
· <b>Additional information:</b>	The lists valid during the making were used as basis.
· <b>8.2 Exposure controls</b>	
· <b>Appropriate engineering controls</b>	No further data; see section 7.
· <b>Individual protection measures, such as personal protective equipment</b>	
· <b>General protective and hygienic measures:</b>	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid close or long term contact with the skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Be sure to clean skin thoroughly after work and before breaks.
· <b>Respiratory protection:</b>	Not necessary if room is well-ventilated.
	 Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.
	 Filter P2
· <b>Hand protection</b>	Only use chemical-protective gloves with CE-labelling of category III.
	 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· <b>Material of gloves</b>	Protective gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Neoprene
· <b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· <b>Eye/face protection</b>	 Tightly sealed goggles
· <b>Body protection:</b>	 Protective work clothing

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

· Colour:	Whitish
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	May cause fire.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Decomposition temperature:	+35 °C (SADT)
· pH	Not applicable.

(Contd. on page 5)

MT

Trade name: **PEROXAN PO-50 P**

(Contd. of page 4)

<ul style="list-style-type: none"> <li>· Viscosity:</li> <li>· Kinematic viscosity</li> <li>· Dynamic:</li> <li>· Solubility</li> <li>· water:</li> <li>· Partition coefficient n-octanol/water (log value)</li> <li>· Vapour pressure:</li> <li>· Density and/or relative density</li> <li>· Density at 20 °C:</li> <li>· Relative density</li> <li>· Bulk density at 20 °C:</li> <li>· Vapour density</li> <li>· Particle characteristics</li> </ul>	<p>Not applicable.</p> <p>Not applicable.</p> <p>Undetermined.</p> <p>not determined</p> <p>Not applicable.</p> <p>1,3 g/cm<sup>3</sup></p> <p>Not determined.</p> <p>310 kg/m<sup>3</sup></p> <p>Not applicable.</p>
See section 3.	
<ul style="list-style-type: none"> <li>· 9.2 Other information</li> <li>· Appearance:</li> <li>· Form:</li> <li>· Important information on protection of health and environment, and on safety.</li> <li>· Ignition temperature:</li> <li>· Explosive properties:</li> <li>· Change in condition</li> <li>· Evaporation rate</li> </ul>	<p>No further relevant information available.</p> <p>Powder</p> <p>Product is not selfigniting.</p> <p>Product is not explosive. However, formation of explosive air/dust mixtures are possible.</p> <p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· Information with regard to physical hazard classes</li> <li>· Explosives</li> <li>· Flammable gases</li> <li>· Aerosols</li> <li>· Oxidising gases</li> <li>· Gases under pressure</li> <li>· Flammable liquids</li> <li>· Flammable solids</li> <li>· Self-reactive substances and mixtures</li> <li>· Pyrophoric liquids</li> <li>· Pyrophoric solids</li> <li>· Self-heating substances and mixtures</li> <li>· Substances and mixtures, which emit flammable gases in contact with water</li> <li>· Oxidising liquids</li> <li>· Oxidising solids</li> <li>· Organic peroxides</li> <li>· Corrosive to metals</li> <li>· Desensitised explosives</li> <li>· Other safety characteristics</li> <li>· Active oxygen</li> </ul>	<p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Heating may cause a fire.</p> <p>Void</p> <p>Void</p> <p>3,6 - 3,8 %</p>

## SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> <li>· 10.1 Reactivity</li> <li>· 10.2 Chemical stability</li> <li>· Thermal decomposition / conditions to be avoided:</li> </ul>	<p>No further relevant information available.</p> <p>SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.</p> <p>No decomposition if used and stored according to specifications.</p> <p>To avoid thermal decomposition do not overheat.</p>
<ul style="list-style-type: none"> <li>· 10.3 Possibility of hazardous reactions</li> <li>· 10.4 Conditions to avoid</li> <li>· 10.5 Incompatible materials:</li> <li>· 10.6 Hazardous decomposition products:</li> </ul>	<p>Self-accelerating decomposition at SADT.</p> <p>No further relevant information available.</p> <p>Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).</p> <p>Hydrocarbons, carbon dioxide and -monoxid.</p> <p>No hazardous decomposition products if used and stored according to specifications.</p>

(Contd. on page 6)

MT

Trade name: **PEROXAN PO-50 P**

(Contd. of page 5)

- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

### SECTION 11: Toxicological information

#### · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Oral	LD50	>10.000 mg/kg (rattus)
Dermal	LD50	14.142-20.000 mg/kg (rabbit)
Inhalative	LC50 / 4h	42,2 mg/l (rattus)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.  
 · **Serious eye damage/irritation** Based on available data, the classification criteria are not met.  
 · **Respiratory or skin sensitisation** May cause an allergic skin reaction.  
 · **Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
 · **Carcinogenicity** Based on available data, the classification criteria are not met.  
 · **Reproductive toxicity** May damage fertility.  
 · **STOT-single exposure** Based on available data, the classification criteria are not met.  
 · **STOT-repeated exposure** Based on available data, the classification criteria are not met.  
 · **Aspiration hazard** Based on available data, the classification criteria are not met.

#### · 11.2 Information on other hazards

##### · Endocrine disrupting properties

None of the ingredients is listed.

### \* SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 3006-82-4 tert-butyl 2-ethylperoxyhexanoate

EC50 / 72h	0,44 mg/l (alga (Süßwasser))
LC50 / 96h	8,66 mg/l (poecilia reticulata)
EC50 / 48h	7,5 mg/l (daphnia)

#### · 12.2 Persistence and degradability

##### · Degree of elimination:

##### · Classification:

##### 3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Degradation (Readily biodegradable) (OECD 301 D)

#### · 12.3 Bioaccumulative potential

##### · Partition coefficient: nOctanol/water: [Log Kow]

3006-82-4	tert-butyl 2-ethylperoxyhexanoate	4,79 (20°C)
-----------	-----------------------------------	-------------

#### · 12.4 Mobility in soil

No further relevant information available.

#### · 12.5 Results of PBT and vPvB assessment

· **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

#### · 12.7 Other adverse effects

No further relevant information available.

##### · Remark:

Toxic for fish

##### · Additional ecological information:

##### · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

MT —  
(Contd. on page 7)

Trade name: **PEROXAN PO-50 P**

(Contd. of page 6)

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Recommendation



After diluting with a suitable inert solid material to 10 %, the product must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### Waste disposal key:

Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.

##### Uncleaned packaging:

##### Recommendation:

This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

##### ADR, IMDG

UN3118

#### 14.2 UN proper shipping name

##### ADR

UN3118 ORGANIC PEROXIDE TYPE E, SOLID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), ENVIRONMENTALLY HAZARDOUS

##### IMDG

ORGANIC PEROXIDE TYPE E, SOLID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), MARINE POLLUTANT

#### 14.3 Transport hazard class(es)

##### ADR



##### Class

5.2 (P2) Organic peroxides.

##### Label

5.2

##### IMDG



##### Class

5.2 Organic peroxides.

##### Label

5.2

##### IATA

##### Class

X

##### Label

X

#### 14.4 Packing group

##### ADR, IMDG

Void

#### 14.5 Environmental hazards:

##### Marine pollutant:

##### Special marking (ADR):

Product contains environmentally hazardous substances: tert-BUTYLPEROXY-2-ETHYLHEXANOATE  
Symbol (fish and tree)  
Symbol (fish and tree)

#### 14.6 Special precautions for user

##### Hazard identification number (Kemler code):

##### Stowage Category

##### Stowage Code

##### Segregation Code

Warning: Organic peroxides.

-

D

SW1 Protected from sources of heat.

SW3 Shall be transported under temperature control.

SG35 Stow "separated from" SGG1-acids

SG36 Stow "separated from" SGG18-alkalis.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

##### Transport/Additional information:

##### ADR

##### Limited quantities (LQ)

0

##### Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

##### Transport category

1

##### Tunnel restriction code

D

(Contd. on page 8)

MT

Trade name: **PEROXAN PO-50 P**

(Contd. of page 7)

· RID / GGVSEB:	no admission
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IATA	
· Remarks:	no admission
· Control temperature:	+20 °C
· Emergency temperature:	+25 °C

## \* SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### · Directive 2012/18/EU

##### · Named dangerous substances

###### - ANNEX I

None of the ingredients is listed.

##### · Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES  
E1 Hazardous to the Aquatic Environment

#### · Qualifying quantity (tonnes) for the application of lower-tier requirements

50 t

#### · Qualifying quantity (tonnes) for the application of upper-tier requirements

200 t

#### · REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 30, 75

#### · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### · REGULATION (EU) 2019/1148

##### · Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

##### · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

##### · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

##### · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Department issuing SDS:

Environment protection / Security of labour

#### · Contact:

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

#### · Version number of previous version:

13

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Org. Perox. C: Organic peroxides – Type C/D

(Contd. on page 9)

MT

Trade name: **PEROXAN PO-50 P**

(Contd. of page 8)

Org. Perox. E: Organic peroxides – Type E/F  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 1B: Reproductive toxicity – Category 1B  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· \* Data compared to the  
previous version altered.

— MT —