

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**

PEROXAN PO-70
- **Trade name:**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
- **Application of the substance / the mixture**

Reaction initiator
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

PERGAN GmbH
Hilfsstoffe für industrielle Prozesse
Schlavenhorst 71
D-46395 Bocholt
Tel: +49 2871 9902-0
Fax: +49 2871 9902-50
- **Further information obtainable from:**

Environment protection / Security of labour
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:**





- Tel: +49 2871 9902-0

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Org. Perox. C	H242	Heating may cause a fire.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 1B	H360F	May damage fertility.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS08 GHS09
- **Signal word**

Danger
- **Hazard-determining components of labelling:**

tert-butyl 2-ethylperoxyhexanoate
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
- **Hazard statements**

H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H360F May damage fertility.
H304 May be fatal if swallowed and enters airways.
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
P234	Keep only in original packaging.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding +20°C. Keep cool.
P420	Store separately.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Trade name: **PEROXAN PO-70**

(Contd. of page 1)


- **Additional information:** Restricted to professional users.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
 - **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 - **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture: consisting of the following components.

· Dangerous components:		
CAS: 3006-82-4 EINECS: 221-110-7 Reg-No.: 01-2119498310-40	tert-butyl 2-ethylperoxyhexanoate Org. Perox. C, H242; Repr. 1B, H360F; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Sens. 1, H317	60-70%
CAS: 93685-81-5 EINECS: 297-629-8 Reg-No.: 01-2119490725-29	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Alternative CAS number: 13475-82-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	25-30%
· Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  Take care of personal protection for the first aider.
- **After inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Immediately remove contaminated clothing.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded.
Hydrocarbons, carbondioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.
Self-protection first!

SECTION 6: Accidental release measures


- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.
In case of further temperature should be cooled with waterspray from a safe distance.
Wear breathing apparatus with filter A during decomposition of materials.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)




— MT —

Trade name: **PEROXAN PO-70**

(Contd. of page 2)

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.
 Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.
 Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
 In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Keep away from heat and direct sunlight.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
 Do not refill residue into storage receptacles.
 Restrict the quantity stored at the work place.
 Before break and at the end of work hands should be thoroughly washed.
 Only use tools made of suitable materials (e. g. polyethylene or stainless steel).
 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
 While using do not eat, drink or smoke.
 Do not generate flames or sparks.
 Keep product and emptied container away from heat and sources of ignition.
 Avoid shock and friction.
 Take precautionary measures against static discharges.
 Do not smoke.
- **Information about fire - and explosion protection:**
 Protect from heat.
 Protect against electrostatic charges.
 Prevent impact and friction.
 Use explosion-proof apparatus / fittings and spark-proof tools.
 Fumes can combine with air to form an explosive mixture.
 Wear shoes with conductive soles.
 Formation of flammable or explosive gas/air-mixtures is possible.
 Avoid open flames, sparks, direct sunlight and other sources of ignition.
 Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
 Prevent any seepage into the ground.
 Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.
 Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
 Protect from heat and direct sunlight.
 Protect from contamination.
 Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** max.: +15 °C
- **Control temperature:** +20 °C
- **Emergency temperature:** +25 °C
- **Storage class:** 5.2

(Contd. on page 4)

— MT —

Trade name: **PEROXAN PO-70**

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Dermal	DNEL Longterm System	5,6 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	9,8 mg/m3 (Worker)

· PNECs

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

PNEC Marinewater sed	0,0622 mg/kg sed dw
PNEC Freshwater	0,002 mg/l (AF 50)
PNEC Freshwater sed	0,622 mg/kg sed dw
PNEC STP	0,64 mg/l (AF 100)
PNEC Marinewater	0 mg/l (AF 500)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid close or long term contact with the skin.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Be sure to clean skin thoroughly after work and before breaks.
Not necessary if room is well-ventilated.

· Respiratory protection:



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Neoprene

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

Trade name: **PEROXAN PO-70**

(Contd. of page 4)

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information**

· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	> SADT
· Decomposition temperature:	+35 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Undetermined.
· Partition coefficient n-octanol/water (log value)	not determined
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0,85 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

No further relevant information available.

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.**· Ignition temperature:**

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Change in condition**· Evaporation rate**

Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity**· 10.1 Reactivity**

No further relevant information available.

· 10.2 Chemical stability**· Thermal decomposition / conditions to be avoided:**

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

(Contd. on page 6)

MT

Trade name: PEROXAN PO-70

(Contd. of page 5)

10.3 Possibility of hazardous reactions

No decomposition if used and stored according to specifications.
To avoid thermal decomposition do not overheat.

10.4 Conditions to avoid

Self-accelerating decomposition at SADT.

10.5 Incompatible materials:

No further relevant information available.

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).

10.6 Hazardous decomposition products:

Hydrocarbons, carbon dioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

Additional information:

Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Oral	LD50	>10.000 mg/kg (rattus)
Dermal	LD50	14.142-20.000 mg/kg (rabbit)
Inhalative	LC50 / 4h	42,2 mg/l (rattus)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Oral	LD50	>5.000 mg/kg (rattus)
------	------	-----------------------

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

EC50 / 72h	0,44 mg/l (alga (Süßwasser))
LC50 / 96h	8,66 mg/l (poecilia reticulata)
EC50 / 48h	7,5 mg/l (daphnia)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h	>0,04 mg/l (daphnia)
IC50 / 72h	>0,04 mg/l (algae)

12.2 Persistence and degradability

Degree of elimination:

Classification:

3006-82-4 tert-butyl 2-ethylperoxyhexanoate

Degradation (Readily biodegradable) (OECD 301 D)

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

12.3 Bioaccumulative potential

Partition coefficient: nOctanol/water: [Log Kow]

3006-82-4	tert-butyl 2-ethylperoxyhexanoate	4,79 (20°C)
-----------	-----------------------------------	-------------

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

(Contd. on page 7)


— MT —

Trade name: **PEROXAN PO-70**





(Contd. of page 6)

· vPvB:	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
· 12.6 Endocrine disrupting properties	The product does not contain substances with endocrine disrupting properties.
· 12.7 Other adverse effects	No further relevant information available.
· Remark:	Toxic for fish
· Additional ecological information:	
· General notes:	Toxic for aquatic organisms Also poisonous for fish and plankton in water bodies. Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods	
· Recommendation	 After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations. Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· Waste disposal key:	Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
· Uncleaned packaging:	
· Recommendation:	This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG	UN3113
· 14.2 UN proper shipping name	
· ADR	UN3113 ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), ENVIRONMENTALLY HAZARDOUS
· IMDG	ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYLPEROXY-2-ETHYLHEXANOATE), MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
 	
· Class	5.2 (P2) Organic peroxides.
· Label	5.2
· IMDG	
 	
· Class	5.2 Organic peroxides.
· Label	5.2
· IATA	
· Class	X
· Label	X
· 14.4 Packing group	
· ADR, IMDG	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: tert-BUTYLPEROXY-2-ETHYLHEXANOATE
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Organic peroxides.
· Hazard identification number (Kemler code):	-
· Stowage Category	D

(Contd. on page 8)

MT —

Trade name: **PEROXAN PO-70**

(Contd. of page 7)

· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SW3 Shall be transported under temperature control. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· RID / GGVSEB:	no admission
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IATA	
· Remarks:	no admission
· Control temperature:	+20 °C
· Emergency temperature:	+25 °C

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances

- ANNEX I

None of the ingredients is listed.

· Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements

50 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 30, 40, 75

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0
E-mail: mail@pergan.com

· Version number of previous version: 15

(Contd. on page 9)

MT

Trade name: **PEROXAN PO-70**

(Contd. of page 8)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. C: Organic peroxides – Type C/D
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

*** Data compared to the previous version altered.**

MT