

Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: PEROXAN PPV-25

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

· Further information obtainable

from: Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

**number:** - Tel: +49 2871 9902-0

#### SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Org. Perox. F H242 Heating may cause a fire.
Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.



· Signal word Danger

Hazard-determining

components of labelling: Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

tert-butyl peroxypivalate

Hazard statements H226 Flammable liquid and vapour. H242 Heating may cause a fire.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines).

P234 Keep only in original packaging.
P243 Take action to prevent static discharges.
P264 Wash thoroughly after handling.

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.
P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding +30°C. Keep cool.

(Contd. on page 2)



(Contd. of page 1)

Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

Trade name: PEROXAN PPV-25

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvR· The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrinedisrupting properties

The product does not contain substances with endocrine disrupting properties.

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

Dangerous components:		
CAS: 93685-81-5	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	70-80%
EINECS: 297-629-8	Alternative CAS number: 13475-82-6	
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
CAS: 927-07-1	tert-butyl peroxypivalate	20-25%
EINECS: 213-147-2	Org. Perox. C, H242; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3,	
Reg-No.: 01-2119961356-32	H335	
Additional informations	For the conding of the listed beyond abuses a refer to continue 10	

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed

4.3 Indication of any immediate medical attention and special

treatment needed

No further relevant information available.

No further relevant information available

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

5.2 Special hazards arising from

the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

· 5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases. Additional information Cool endangered receptacles with water spray.

Self-protection first!

Water with full jet

#### **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

## Trade name: PEROXAN PPV-25

Inform respective authorities in case of seepage into water course or sewage system. · 6.2 Environmental precautions:

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up: Do not allow to enter sewers/ surface or ground water.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke. Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities · Storage:

Requirements to be met by

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed. Protect from heat and direct sunlight. Protect from contamination.

Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

max.: -5 °C +30 °C +35 °C

Control temperature: · Emergency temperature: · Storage class: 52

(Contd. on page 4)



Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

## Trade name: PEROXAN PPV-25

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available

#### **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

·DNELs

927-07-1 tert-butyl peroxypivalate

DNEL Longterm System 1,6 mg/kg bw/day (Worker) Dermal Inhalative DNEL Longterm System 2,8 mg/m3 (Worker)

· PNECs

927-07-1 tert-butyl peroxypivalate

PNEC Marinewater sed | 0,011 mg/kg sed dw (-) 0,014 mg/l (AF 100) PNFC Freshwater PNEC Freshwater sed 0,106 mg/kg sed dw (-) PNEC Soil 0,013 mg/kg soil dw PNEC STP 10.000 mg/l (-) **PNEC Marinewater** 0,001 mg/l (AF 1.000)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butyl rubber, BR

Fluorocarbon rubber (Viton) Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

· Body protection:



Protective work clothing

МТ



Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

Trade name: PEROXAN PPV-25

(Contd. of page 4)

#### **SECTION 9: Physical and chemical properties**

· 9.1	Information	on bas	ic phys	ical and	chemi	cal properties
-------	-------------	--------	---------	----------	-------	----------------

· General Information

· Colour: Colourless Characteristic · Odour: Odour threshold: Not determined. Melting point/freezing point: Not applicable. Boiling point or initial boiling point and boiling range Not applicable. Not applicable.

Flammability

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. > SADT · Flash point:

Decomposition temperature: +40 °C (SADT) Not determined. · pH

Viscosity:

Kinematic viscosity Not determined Dynamic: Not determined.

Solubility

· water: Undetermined. Partition coefficient n-octanol/water (log value) not determined · Vapour pressure: Not determined.

· Density and/or relative density

Density at 0 °C: 0,81 g/cm<sup>3</sup> Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid · Important information on protection of health and environment,

and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour

Void

mixtures are possible.

· Change in condition Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void

· Oxidising solids Void Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity

· Oxidising liquids

· 10.2 Chemical stability

· Thermal decomposition /

conditions to be avoided:

No further relevant information available.

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous selfaccelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT.

(Contd. on page 6)



(Contd. of page 5)

Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

Trade name: PEROXAN PPV-25

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous

reactions

· 10.4 Conditions to avoid

· 10.5 Incompatible materials:

· 10.6 Hazardous decomposition

products:

Self-accelerating decomposition at SADT.

No further relevant information available.

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e.g.

heavy-metal compounds and amines).

Hydrocarbons, carbondioxide and -monoxid.

No hazardous decomposition products if used and stored according to specifications.

· Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

#### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Oral LD50 >5.000 mg/kg (rattus) 927-07-1 tert-butyl peroxypivalate LD50 Oral 4.169 mg/kg (rattus) LD50 2.500 mg/kg (rabbit) Dermal Inhalative LC50 / 4h 7,79 mg/l (rattus)

Skin corrosion/irritation

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation

May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure May cause respiratory irritation.

Causes skin irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

 Aspiration hazard May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

12.1 Toxicity

· Aquatic toxicity:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h | >0,04 mg/l (daphnia) IC50 / 72h >0,04 mg/l (algae)

927-07-1 tert-butyl peroxypivalate

LC50 / 96h | 29 mg/l (brachydanio rerio)

12.2 Persistence and degradability

· Degree of elimination:

Classification:

93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Degradation (Not readily biodegradable)

927-07-1 tert-butyl peroxypivalate

Degradation (Evidence for inherent biodegradability.) (OECD 301 D)

12.3 Bioaccumulative potential

· Partition coefficient: nOctanol/water: [Log Kow]

927-07-1 tert-butyl peroxypivalate

3,17 (25°C)

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

(Contd. on page 7)



(Contd. of page 6)

Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

Trade name: PEROXAN PPV-25

• 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

· Uncleaned packaging:

Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG	UN3119
· 14.2 UN proper shipping name · ADR	UN3119 ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE F, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
** Y	
· Class	5.2 (P2) Organic peroxides.
· Label	5.2
· IMDG	

\*\*\*



· Class	5.2 Organic peroxides.
· Label	5.2
·IATA	
· Class	Χ
· Label	X
14.4 Packing group	
· ADR, IMDG	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: tert-BUTYL PEROXYPIVALATE
· Marine pollutant:	Symbol (fish and tree)

D

Marine pollutant:
Symbol (fish and tree)
Special marking (ADR):
Special precautions for user
Hazard identification number (Kemler code):

- Marine pollutant:
Symbol (fish and tree)
Warning: Organic peroxides.
- -

· Stowage Category

• Stowage Code SW1 Protected from sources of heat.

SW3 Shall be transported under temperature control.

(Contd. on page 8)



(Contd. of page 7)

Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

0

Trade name: PEROXAN PPV-25

 Segregation Code SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity Transport category Tunnel restriction code D

· RID / GGVSEB: no admission

·IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· IATA

Remarks: no admission

· Control temperature: +30 °C · Emergency temperature: +35 °C

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

Named dangerous substances

- ANNEX I None of the ingredients is listed.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES · Seveso category

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier

50 t requirements Qualifying quantity (tonnes) for the application of upper-tier

200 t requirements

**REGULATION (EC) No** 

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug

precursors

None of the ingredients is listed.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· Version number of previous

6 version:

(Contd. on page 9)



Printing date 03.04.2024 Version: 7 (replaces version 6) Revision: 16.02.2023

Trade name: PEROXAN PPV-25

(Contd. of page 8)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

AD: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Org. Perox. C: Organic peroxides – Type C/D
Org. Perox. F: Organic peroxides – Type E/F
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

·\* Data compared to the previous version altered.

MT —