


## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PEROXAN PPV-65
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:** Environment protection / Security of labour  
Qualified person: E-mail: msds@pergan.com
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## \* SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- Flam. Liq. 3      H226 Flammable liquid and vapour.
- Org. Perox. D    H242 Heating may cause a fire.
- Skin Irrit. 2      H315 Causes skin irritation.
- Skin Sens. 1      H317 May cause an allergic skin reaction.
- STOT SE 3        H335 May cause respiratory irritation.
- Asp. Tox. 1       H304 May be fatal if swallowed and enters airways.
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**   
GHS02 GHS07 GHS08 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:** tert-butyl peroxyvalate  
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H242 Heating may cause a fire.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H304 May be fatal if swallowed and enters airways.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
- P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220      Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).
- P234      Keep only in original packaging.
- P243      Take action to prevent static discharges.
- P264      Wash thoroughly after handling.
- P273      Avoid release to the environment.
- P280      Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P310      IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331      Do NOT induce vomiting.
- P303+P361+P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P362+P364      Take off contaminated clothing and wash it before reuse.
- P405      Store locked up.
- P410      Protect from sunlight.
- P411+P235      Store at temperatures not exceeding 0°C. Keep cool.

Trade name: **PEROXAN PPV-65**

(Contd. of page 1)

P420 Store separately.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **Determination of endocrine-disrupting properties** The product does not contain substances with endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

##### · Dangerous components:

CAS: 927-07-1 EINECS: 213-147-2 Reg-No.: 01-2119961356-32	tert-butyl peroxy-pivalate Org. Perox. C, H242; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	60-70%
CAS: 93685-81-5 EINECS: 297-629-8 Reg-No.: 01-2119490725-29	Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Alternative CAS number: 13475-82-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	30-40%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · General information:



Take care of personal protection for the first aider.

##### · After inhalation:

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.

##### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.

##### · After eye contact:

Rinse opened eye for several minutes under running water.

##### · After swallowing:

If symptoms persist consult doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · For safety reasons unsuitable extinguishing agents:

Water with full jet

#### · 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded.  
Hydrocarbons, carbondioxide and -monoxid.

#### · 5.3 Advice for firefighters

##### · Protective equipment:

Do not inhale explosion gases or combustion gases.

##### · Additional information

Cool endangered receptacles with water spray.  
Self-protection first!

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures


Keep away from ignition sources.  
In case of further temperature should be cooled with waterspray from a safe distance.  
Wear breathing apparatus with filter A during decomposition of materials.  
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)




— MT —

Trade name: **PEROXAN PPV-65**

(Contd. of page 2)

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.  
 Ensure adequate ventilation.  
 Large quantities should be diluted with suitable desensitisation agent to a concentration below 10 % before disposal.  
 Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.  
 In case of large spillage the environmental authority should be informed.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
 Keep away from heat and direct sunlight.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.  
 Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.  
 Do not refill residue into storage receptacles.  
 Restrict the quantity stored at the work place.  
 Before break and at the end of work hands should be thoroughly washed.  
 Only use tools made of suitable materials (e. g. polyethylene or stainless steel).  
 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).  
 While using do not eat, drink or smoke.  
 Do not generate flames or sparks.  
 Keep product and emptied container away from heat and sources of ignition.  
 Avoid shock and friction.  
 Take precautionary measures against static discharges.  
 Do not smoke.
- **Information about fire - and explosion protection:**  
 Protect from heat.  
 Protect against electrostatic charges.  
 Prevent impact and friction.  
 Use explosion-proof apparatus / fittings and spark-proof tools.  
 Fumes can combine with air to form an explosive mixture.  
 Wear shoes with conductive soles.  
 Formation of flammable or explosive gas/air-mixtures is possible.  
 Avoid open flames, sparks, direct sunlight and other sources of ignition.  
 Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
 Prevent any seepage into the ground.  
 Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
 Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.  
 Protect from heat and direct sunlight.  
 Protect from contamination.  
 Storage in a collecting room is required.
- **Recommended storage temperature (To maintain quality):** max.: -5 °C
- **Control temperature:** 0 °C
- **Emergency temperature:** +10 °C
- **Storage class:** 5.2

(Contd. on page 4)

Trade name: **PEROXAN PPV-65**

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

**927-07-1 tert-butyl peroxyvalate**

Dermal	DNEL Longterm System	1,4 mg/kg bw/day (Worker)
Inhalative	DNEL Longterm System	2,5 mg/m3 (Worker)

· **PNECs**

**927-07-1 tert-butyl peroxyvalate**

PNEC Marinewater sediment	0,004 mg/kg sed dw (-)
PNEC Freshwater	0,006 mg/l (AF 50)
PNEC Freshwater sediment	0,044 mg/kg sed dw (-)
PNEC Soil	0,005 mg/kg soil dw
PNEC Marinewater	0,001 mg/l (AF 500)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid close or long term contact with the skin.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Use skin protection cream for skin protection.  
Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· **Hand protection**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
Nitrile rubber, NBR  
Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

Trade name: **PEROXAN PPV-65**

(Contd. of page 4)

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

<b>General Information</b>	
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not applicable.
· Boiling point or initial boiling point and boiling range	Not applicable.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	> SADT
· Decomposition temperature:	+20 °C (SADT)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Undetermined.
· Partition coefficient n-octanol/water (log value)	not determined
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 0 °C:	0,86 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

**9.2 Other information**

No further relevant information available.

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.

**Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Heating may cause a fire.
· Corrosive to metals	Void
· Desensitised explosives	Void
· Other safety characteristics	
· Active oxygen	5,9 - 6,1 %

**SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability  
· Thermal decomposition / conditions to be avoided:

SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

(Contd. on page 6)

Trade name: **PEROXAN PPV-65**

(Contd. of page 5)

<ul style="list-style-type: none"> <li>· <b>10.3 Possibility of hazardous reactions</b></li> <li>· <b>10.4 Conditions to avoid</b></li> <li>· <b>10.5 Incompatible materials:</b></li> <li>· <b>10.6 Hazardous decomposition products:</b></li> <li>· <b>Additional information:</b></li> </ul>	<p>decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.</p> <p>Self-accelerating decomposition at SADT. No further relevant information available.</p> <p>Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).</p> <p>Hydrocarbons, carbon dioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.</p> <p>Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.</p>
---	---

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**927-07-1 tert-butyl peroxyvalate**

Oral	LD50	4.169 mg/kg (Rat)
Dermal	LD50	2.500 mg/kg (rabbit)
Inhalative	LC50 / 4h	7,79 mg/l (Rat)

**93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated**

Oral	LD50	>5.000 mg/kg (Rat)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**927-07-1 tert-butyl peroxyvalate**

LC50 / 96h	29 mg/l (brachydanio rerio)
------------	-----------------------------

**93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated**

EC50 / 48h	>0,04 mg/l (Daphnia)
IC50 / 72h	>0,04 mg/l (algae)

- **12.2 Persistence and degradability**

- **Degree of elimination:**

- **Classification:**

**927-07-1 tert-butyl peroxyvalate**

Degradation (Evidence for inherent biodegradability.) (OECD 301 D)

**93685-81-5 Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated**

Degradation (Not readily biodegradable)

- **12.3 Bioaccumulative potential**

- **Partition coefficient: nOctanol/water: [Log Kow]**

927-07-1 tert-butyl peroxyvalate	3,17 (25°C)
----------------------------------	-------------

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.


(Contd. on page 7)

Trade name: **PEROXAN PPV-65**



(Contd. of page 6)

- **vPvB:** The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects** No further relevant information available.
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:** Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.
- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

### SECTION 14: Transport information

· <b>14.1 UN number or ID number</b> · <b>ADR, IMDG</b>	UN3115
· <b>14.2 UN proper shipping name</b> · <b>ADR</b>	UN3115 ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), ENVIRONMENTALLY HAZARDOUS
· <b>IMDG</b>	ORGANIC PEROXIDE TYPE D, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), MARINE POLLUTANT
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b> · <b>Label</b>	5.2 (P2) Organic peroxides. 5.2
· <b>IMDG</b>	
	
· <b>Class</b> · <b>Label</b>	5.2 Organic peroxides. 5.2
· <b>IATA</b> · <b>Class</b> · <b>Label</b>	X X
· <b>14.4 Packing group</b> · <b>ADR, IMDG</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SW3 Shall be transported under temperature control.

(Contd. on page 8)

Trade name: **PEROXAN PPV-65**

(Contd. of page 7)

· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· RID / GGVSEB:	
	no admission
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IATA	
· Remarks:	no admission
· Control temperature:	0 °C
· Emergency temperature:	+10 °C

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances
  - ANNEX I None of the ingredients is listed.
- Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES  
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

#### · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### · REGULATION (EU) 2019/1148

##### · Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

##### · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

##### · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

##### · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

#### · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection / Security of labour
- Contact: Tel: +49 2871 9902-0  
E-mail: mail@pergan.com
- Version number of previous version: 4

(Contd. on page 9)



**Safety data sheet**  
 according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version: 5 (replaces version 4)

Revision: 16.02.2023

Trade name: **PEROXAN PPV-65**

(Contd. of page 8)

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Org. Perox. C: Organic peroxides – Type C/D  
 Org. Perox. D: Organic peroxides – Type C/D  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

\* **Data compared to the previous version altered.**

— MT —