

Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PEROXAN PPV

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance /

the mixture

Reaction initiator For industrial use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: PERGAN GmbH

Hilfsstoffe für industrielle Prozesse

Schlavenhorst 71 D-46395 Bocholt Tel: +49 2871 9902-0 Fax: +49 2871 9902-50

Further information obtainable

from: Environment protection / Security of labour

Qualified person: E-mail: msds@pergan.com

1.4 Emergency telephone

number: - Tel: +49 2871 9902-0

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Org. Perox. C H242 Heating may cause a fire.
Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

Hazard-determining

· Hazard statements

components of labelling: tert-butyl peroxypivalate

2,2,4,6,6-pentamethylheptane H226 Flammable liquid and vapour. H242 Heating may cause a fire.

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

• **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and

accelerators (e. g. heavy metal compounds and amines).

P234 Keep only in original packaging.
P243 Take action to prevent static discharges.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.
P410 Protect from sunlight.

P411+P235 Store at temperatures not exceeding 0°C. Keep cool.

(Contd. on page 2)



(Contd. of page 1)

Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

P420 Store separately.

P501 Dispose of contents/container in accordance with local/regional/national/international

2.3 Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. · vPvR· The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· Determination of endocrinedisrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Dangerous components:				
CAS: 927-07-1	tert-butyl peroxypivalate	70-80%		
EINECS: 213-147-2	Org. Perox. C, H242; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3,			
Reg-No.: 01-2119961356-32				
CAS: 13475-82-6	2,2,4,6,6-pentamethylheptane	20-25%		
EINECS: 236-757-0	Alternative CAS number: 93685-81-5			
Reg-No.: 01-2119490725-29	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413			
. Additional information:	For the wording of the listed hezard phrases refer to section 16			

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take care of personal protection for the first aider.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

· After eye contact: Rinse opened eye for several minutes under running water. After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed

4.3 Indication of any immediate medical attention and special

No further relevant information available.

No further relevant information available

SECTION 5: Firefighting measures

5.1 Extinguishing media

treatment needed

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture Under certain fire conditions, traces of other toxic gases cannot be excluded.

Hydrocarbons, carbondioxide and -monoxid.

5.3 Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases. Additional information Cool endangered receptacles with water spray.

Self-protection first!

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area. Keep away from ignition sources.

In case of further temperature should be cooled with waterspray from a safe distance.

Wear breathing apparatus with filter A during decomposition of materials.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)



Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

(Contd. of page 2)



Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation

Large quantities should be diluted with suitable desensitation agent to a concentration below 10 % before

disposal.

Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government

regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

In case of large spillage the environmental authority should be informed.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Open and handle receptacle with care.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Handle with care. Avoid jolting, friction and impact. Do not refill residue into storage receptacles. Restrict the quantity stored at the work place.

Before break and at the end of work hands should be thoroughly washed.

Only use tools made of suitable materials (e. g. polyethylene or stainless steel).

Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-

metal compounds and amines). While using do not eat, drink or smoke.

Do not generate flames or sparks.

Keep product and emptied container away from heat and sources of ignition.

Avoid shock and friction.

Take precautionary measures against static discharges.



Do not smoke.

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

Prevent impact and friction.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.



Wear shoes with conductive soles.

Formation of flammable or explosive gas/air-mixtures is possible.



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Pay attention to the special requirements of your local autorithies for storing dangerous goods.

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle. Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Do not store or park organic peroxide together with heavy metal compounds and amines.

Store away from foodstuffs, drinks and feeding stuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from contamination.

Store under lock and key and with access restricted to technical experts or their assistants only.

Storage in a collecting room is required.

Recommended storage temperature (To maintain quality):

-15 -5 °C

Control temperature:

0°C

(Contd. on page 4)



(Contd. of page 3)

Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

+10 °C **Emergency temperature:** · Storage class: 5.2

· 7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical values that have to be

monitored at the workplace.

DNELs

927-07-1 tert-butyl peroxypivalate

Dermal DNEL Longterm System 1,6 mg/kg bw/day (Worker) Inhalative DNEL Longterm System 2,8 mg/m3 (Worker)

·PNECs

927-07-1 tert-butyl peroxypivalate

PNEC Marinewater sed 0,011 mg/kg sed dw (-) **PNEC Freshwater** 0,014 mg/l (AF 100) PNEC Freshwater sed 0,106 mg/kg sed dw (-) PNEC Soil 0,013 mg/kg soil dw PNEC STP 10.000 mg/l (-) **PNEC Marinewater** 0,001 mg/l (AF 1.000)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering

controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

The usual precautionary measures are to be adhered to when handling chemicals. hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid close or long term contact with the skin. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer

exposure use self-contained respiratory protective device.

Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.

Filter A2

· Hand protection Only use chemical-protective gloves with CE-labelling of category III.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

Butvl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Neoprene

Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

observed.

· Eye/face protection



Tightly sealed goggles

(Contd. on page 5)



Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

· Body protection:

(Contd. of page 4) Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chemical propertie 	al properties	chemical	and	hvsical	asic	on	Information	· 9.1
--	---------------	----------	-----	---------	------	----	-------------	-------

· General Information

colourless - yellowish · Colour: · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: < -25 °C

Boiling point or initial boiling point and boiling range Not applicable. Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: > SADT Decomposition temperature: +20 °C (SADT) · pH Not determined.

· Viscosity:

Kinematic viscosity Dynamic at 20 °C:

2 mPas · Solubility water: Undetermined. · Partition coefficient n-octanol/water (log value) not determined · Vapour pressure: Not determined.

Density and/or relative density · Density at 20 °C: 0,88 g/cm³ Relative density Not determined.

Vapour density Not determined.

· 9.2 Other information No further relevant information available.

Appearance: · Form:

Fluid · Important information on protection of health and environment,

and on safety.

Ignition temperature:

Product is not selfigniting. Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Void

Not determined.

Change in condition

Not determined. · Evaporation rate

· Information with regard to physical hazard classes

· Explosives Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in

contact with water Void Oxidising liquids Void Oxidising solids Void

· Organic peroxides Heating may cause a fire.

Corrosive to metals Void · Desensitised explosives Void Other safety characteristics

Active oxygen 6,8 - 7,0 %

SECTION 10: Stability and reactivity

No further relevant information available. · 10.1 Reactivity

(Contd. on page 6)



(Contd. of page 5)

Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating

decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause

decomposition at or below the SADT.

No decomposition if used and stored according to specifications.

To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous

reactions

Self-accelerating decomposition at SADT. No further relevant information available.

· 10.4 Conditions to avoid · 10.5 Incompatible materials:

Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g.

heavy-metal compounds and amines).

· 10.6 Hazardous decomposition

products:

Hydrocarbons, carbondioxide and -monoxid.

 $\dot{\text{No}}$ hazardous decomposition products if used and stored according to specifications.

Additional information: Emergency procedures will vary depending on conditions. The customer should have an emergency

response plane in place.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

927-07-1 tert-butyl peroxypivalate

 Oral
 LD50
 4.169 mg/kg (rattus)

 Dermal
 LD50
 2.500 mg/kg (rabbit)

 Inhalative
 LC50 / 4h
 7,79 mg/l (rattus)

13475-82-6 2,2,4,6,6-pentamethylheptaneOral | LD50 | >5.000 mg/kg (rattus)

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard May be fatal if swallowed and enters airways.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

927-07-1 tert-butyl peroxypivalate

LC50 / 96h 29 mg/l (brachydanio rerio)

13475-82-6 2,2,4,6,6-pentamethylheptane

EC50 / 48h | >0,04 mg/l (daphnia)

IC50 / 72h |>0,04 mg/l (algae)

12.2 Persistence and degradability

Degree of elimination:

· Classification:

927-07-1 tert-butyl peroxypivalate

Degradation (Evidence for inherent biodegradability.) (OECD 301 D)

13475-82-6 2,2,4,6,6-pentamethylheptane

Degradation

(Not readily biodegradable)

(Contd. on page 7)



Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

· 12.3 Bioaccumulative potential

(Contd. of page 6)

Partition coefficient: nOctanol/water: [Log Kow]

927-07-1 tert-butyl peroxypivalate 3,17 (25°C)

13475-82-6 2,2,4,6,6-pentamethylheptane 5,94 - 6,16

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

▶ PBT: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 ▶ vPvB: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

· 12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



After diluting with a suitable desentisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage

• Waste disposal key: Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-

number.

Uncleaned packaging:

• Recommendation: This material and its container must be disposed of as hazardous waste.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG	UN3113
· 14.2 UN proper shipping name · ADR	UN3113 ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), ENVIRONMENTALLY HAZARDOUS
· IMDG	ORGANIC PEROXIDE TYPE C, LIQUID, TEMPERATURE CONTROLLED (tert-BUTYL PEROXYPIVALATE), MARINE POLLUTANT

· 14.3 Transport hazard class(es)

· ADR





· Class 5.2 (P2) Organic peroxides · Label 5.2

· IMDG





Class 5.2 Organic peroxides.
Label 5.2

· 14.4 Packing group

· ADR, IMDG Void

(Contd. on page 8)



(Contd. of page 7)

Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

· 14.5 Environmental hazards: Product contains environmentally hazardous substances: tert-BUTYL

PEROXYPIVALATE

· Marine pollutant:

Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Organic peroxides.

Hazard identification number (Kemler code): D

Stowage Category

SW1 Protected from sources of heat. · Stowage Code

SW3 Shall be transported under temperature control.

SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. · Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity · Transport category

· Tunnel restriction code D

· RID / GGVSEB: no admission

· IMDG

Limited quantities (LQ)

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· IATA

Remarks: no admission

· Control temperature: 0°C +10 °C · Emergency temperature:

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances

- ANNEX I None of the ingredients is listed.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES · Seveso category

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex

None of the ingredients is listed.

REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 9)



Printing date 03.04.2024 Version: 13 (replaces version 12) Revision: 16.02.2023

Trade name: PEROXAN PPV

(Contd. of page 8)

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection / Security of labour

· Contact: Tel: +49 2871 9902-0 E-mail: mail@pergan.com

· Version number of previous

version:

12
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

PNEC: Predicted No-Effect Concentration (REAL LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative VPUS: Very Persistent and very bloaccumulature
Flam. Lig. 3: Flammable liquids – Category 3
Org. Perox. C: Organic peroxides – Type C/D
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

·* Data compared to the previous version altered.

МТ