

## SECTION 1: Identification of the substance/mixture and of the company/undertaking


- **1.1 Product identifier**
- Trade name:** PEROXAN MI-60 KX
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Reaction initiator  
For industrial use
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** PERGAN GmbH  
Hilfsstoffe für industrielle Prozesse  
Schlavenhorst 71  
D-46395 Bocholt  
Tel: +49 2871 9902-0  
Fax: +49 2871 9902-50
- **Further information obtainable from:**  
Environment protection / Security of labour  
Competent person:  
\* Sales Manager Germany: Mr. Ansgar Pappenheim, e-mail: a.pappenheim@pergan.com  
\* Export Sales Manager: Mr. Dr. Thomas Philipps, e-mail: dr.philipps@pergan.com  
\* Environment protection / : Mr. Christoph Wilting, e-mail: c.wilting@pergan.com  
Security of labour
- **1.4 Emergency telephone number:** - Tel: +49 2871 9902-0

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Org. Perox. D	H242	Heating may cause a fire.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Corr. 1C	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
- **Hazard pictograms**



The product is classified and labelled according to the CLP regulation.

GHS02 GHS05 GHS07 GHS08 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:** Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide  
4-methylpentan-2-one  
hydrogen peroxide solution
- **Hazard statements**

H226 Flammable liquid and vapour.  
H242 Heating may cause a fire.  
H332 Harmful if inhaled.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H361d Suspected of damaging the unborn child.  
H304 May be fatal if swallowed and enters airways.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P220 Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy metal compounds and amines).  
P234 Keep only in original container.  
P243 Take precautionary measures against static discharge.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Trade name: **PEROXAN MI-60 KX**

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P405 Store locked up.  
 P410 Protect from sunlight.  
 P411+P235 Store at temperatures not exceeding +25°C. Keep cool.  
 P420 Do not mix with peroxide-accelerators or reducing agents.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Dangerous components:**

EC number: 942-932-9 Reg-No.: 01-2120103792-63	Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide Alternative CAS number: 37206-20-5 Flam. Liq. 3, H226; Org. Perox. D, H242; Asp. Tox. 1, H304; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	30-40%
CAS: 6846-50-0 EINECS: 229-934-9 Reg-No.: 01-2119451093-47	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2, H361d; Aquatic Chronic 3, H412	30-40%
CAS: 123-42-2 EINECS: 204-626-7 Index number: 603-016-00-1 Reg-No.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Eye Irrit. 2, H319; STOT SE 3, H335	10-20%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4	4-methylpentan-2-one Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	5-10%
CAS: 7722-84-1 EINECS: 231-765-0 Index number: 008-003-00-9 Reg-No.: 01-2119485845-22	hydrogen peroxide solution Ox. Liq. 1, H271; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412	1-2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Take care of personal protection for the first aider.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
Immediately remove contaminated clothing.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.


(Contd. on page 3)

Trade name: **PEROXAN MI-60 KX**



(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Under certain fire conditions, traces of other toxic gases cannot be excluded. Hydrocarbons, carbon dioxide and -monoxid.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device. Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray. Self-protection first!

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources. In case of further temperature should be cooled with waterspray from a safe distance. Wear breathing apparatus with filter A during decomposition of materials. Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Large quantities should be diluted with suitable desensitization agent to a concentration below 10 % before disposal. Soak up with absorbant material (e. g. Vermiculit) and dispose of in accordance with government regulations.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. In case of large spillage the environmental authority should be informed.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols. Wear suitable respiratory protective device when decanting larger quantities without extractor facilities. Do not refill residue into storage receptacles. Restrict the quantity stored at the work place. Use only in well ventilated areas. Before break and at the end of work hands should be thoroughly washed. Only use tools made of suitable materials (e. g. polyethylene or stainless steel). Keep away from dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines). Oxidizing because of releasing oxygene. While using do not eat, drink or smoke. Do not generate flames or sparks. Keep product and emptied container away from heat and sources of ignition. Avoid shock and friction. Take precautionary measures against static discharges.  Do not smoke.
- **Information about fire - and explosion protection:** Protect from heat. Protect against electrostatic charges. Prevent impact and friction. Use explosion-proof apparatus / fittings and spark-proof tools. Fumes can combine with air to form an explosive mixture.  Wear shoes with conductive soles. Formation of flammable or explosive gas/air-mixtures is possible.

(Contd. on page 4)

Trade name: **PEROXAN MI-60 KX**

(Contd. of page 3)



Avoid open flames, sparks, direct sunlight and other sources of ignition.

Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:** Pay attention to the special requirements of your local authorities for storing dangerous goods.
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.  
Prevent any seepage into the ground.  
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:** Do not store or park organic peroxide together with heavy metal compounds and amines.  
Store away from foodstuffs, drinks and feeding stuffs.
- **Further information about storage conditions:** Keep container tightly sealed.  
Protect from heat and direct sunlight.  
Protect from contamination.
- **Recommended storage temperature (To maintain quality):** +5 .... +25 °C
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

WEL (Great Britain) Short-term value: 362 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**108-10-1 4-methylpentan-2-one**

WEL (Great Britain) Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Sk, BMGV

IOELV (EU) Short-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 83 mg/m<sup>3</sup>, 20 ppm

**7722-84-1 hydrogen peroxide solution**

WEL (Great Britain) Short-term value: 2.8 mg/m<sup>3</sup>, 2 ppm  
Long-term value: 1.4 mg/m<sup>3</sup>, 1 ppm

**DNELs**

**Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide**

Dermal DNEL Longterm System 1.5 mg/kg bw/day (Worker)  
Inhalative DNEL Longterm System 2.64 mg/m<sup>3</sup> (Worker)

**6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate**

Dermal DNEL Longterm System 5 mg/kg bw/day (Worker)  
Inhalative DNEL Longterm System 17.62 mg/m<sup>3</sup> (Worker)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Dermal DNEL Longterm System 840 mg/kg bw/day (Worker)  
Inhalative DNEL Longterm System 59.2 mg/m<sup>3</sup> (Worker)

**7722-84-1 hydrogen peroxide solution**

Inhalative DNEL Longterm Local 1.4 mg/m<sup>3</sup> (Worker)

**PNECs**

**Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide**

PNEC Marinewater sed 0.06 mg/kg sed dw (-)  
PNEC Freshwater 0.00133 mg/l (AF 1.000)  
PNEC Freshwater sed 0.59 mg/kg sed dw (-)  
PNEC Soil 0.118 mg/kg soil dw (-)  
PNEC STP 1.28 mg/l (AF 10)

(Contd. on page 5)

**Trade name: PEROXAN MI-60 KX**

(Contd. of page 4)

PNEC Marinewater	0.000133 mg/l (AF 10.000)
<b>6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate</b>	
PNEC Marinewater sed	0.529 mg/kg sed dw (-)
PNEC Freshwater	0.014 mg/l (AF 50)
PNEC Freshwater sed	5.29 mg/kg sed dw
PNEC Soil	1.05 mg/kg soil dw
PNEC STP	3 mg/l (AF 10)
PNEC Marinewater	0.001 mg/l (AF 500)
<b>123-42-2 4-hydroxy-4-methylpentan-2-one</b>	
PNEC Marinewater sed	0.91 mg/kg sed dw
PNEC Freshwater	2 mg/l (AF 50)
PNEC Freshwater sed	9.06 mg/kg sed dw
PNEC Soil	0.63 mg/kg soil dw
PNEC STP	10 mg/l (AF 100)
PNEC Marinewater	0.2 mg/l (AF 500)
<b>7722-84-1 hydrogen peroxide solution</b>	
PNEC Marinewater sed	0.047 mg/kg sed dw
PNEC Freshwater	0.013 mg/l (AF 50)
PNEC Freshwater sed	0.047 mg/kg sed dw
PNEC Soil	0.002 mg/kg soil dw
PNEC STP	mg/l (AF 100)
PNEC Marinewater	0.013 mg/l (AF 50)
<b>Ingredients with biological limit values:</b>	
<b>108-10-1 4-methylpentan-2-one</b>	
BMGV (Great Britain)	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid close or long term contact with the skin.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Use skin protection cream for skin protection.  
Be sure to clean skin thoroughly after work and before breaks.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Use suitable respiratory device when it exceed exposure limit and when insufficiently ventilated.



Filter A2

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.  
Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
Nitrile rubber, NBR  
Neoprene

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 6)

Trade name: **PEROXAN MI-60 KX**

(Contd. of page 5)

· Body protection:



Protective work clothing

### SECTION 9: Physical and chemical properties

<b>9.1 Information on basic physical and chemical properties</b>	
· General Information	
· Appearance:	
· Form:	Fluid
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/freezing point:	Not applicable.
· Initial boiling point and boiling range:	Not applicable.
· Flash point:	50 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	> +50 °C (SADT)
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.98 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· water:	Undetermined.
· Partition coefficient: n-octanol/water: not determined	
· Viscosity:	
· Dynamic at 20 °C:	13 mPas
· Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.
· Active oxygen	ca. 8.9 %

### SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	SADT (Self Accelerating Decomposition Temperature) is the lowest temperature at which self accelerating decomposition may occur with substance in the packaging as used in transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be cause decomposition at and above the temperature. Contact with incompatible substances can cause decomposition at or below the SADT. No decomposition if used and stored according to specifications. To avoid thermal decomposition do not overheat.
· 10.3 Possibility of hazardous reactions	Self-accelerating decomposition at SADT.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	Rapid decomposition by dirt, rust, chemicals in particular concentrated acids, alkalis and accelerators (e. g. heavy-metal compounds and amines).
· 10.6 Hazardous decomposition products:	Hydrocarbons, carbondioxide and -monoxid. No hazardous decomposition products if used and stored according to specifications.

(Contd. on page 7)



Trade name: **PEROXAN MI-60 KX**

(Contd. of page 6)

- **Additional information:** Emergency procedures will vary depending on conditions. The customer should have an emergency response plane in place.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**  
· **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**Reaction mass of 4-methylpentane-2,2-diyl dihydroperoxide and 4-methylpentane-2-one and peroxybis-4-methylpentane-2,2-diyl dihydroperoxide**

Oral	LD50	1,575 mg/kg (rattus)
Dermal	LD50	>2,000 mg/kg (rattus)
Inhalative	LC50 / 4h	1.5 mg/l (rattus)

**6846-50-0 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate**

Oral	LD50	3,200 mg/kg (rattus)
Dermal	LD50	18,900 mg/kg (caviinae)

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	LD50	2,520 mg/kg (rattus)
Dermal	LD50	13,630 mg/kg (cuniculosus)

**108-10-1 4-methylpentan-2-one**


Oral	LD50	>2,080 mg/kg (rattus)
Dermal	LD50	>16,000 mg/kg (cuniculosus)

- **Primary irritant effect:**  
· **Skin corrosion/irritation** Causes severe skin burns and eye damage.  
· **Serious eye damage/irritation** Causes serious eye damage.  
· **Respiratory or skin sensitisation** May cause an allergic skin reaction.  
· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
· **Carcinogenicity** Based on available data, the classification criteria are not met.  
· **Reproductive toxicity** Suspected of damaging the unborn child.  
· **STOT-single exposure** Based on available data, the classification criteria are not met.  
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.  
· **Aspiration hazard** May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**

- **12.1 Toxicity**  
· **Aquatic toxicity:** No further relevant information available.  
· **12.2 Persistence and degradability** No further relevant information available.  
· **12.3 Bioaccumulative potential** No further relevant information available.  
· **12.4 Mobility in soil** No further relevant information available.  
· **Additional ecological information:**  
· **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
· **12.5 Results of PBT and vPvB assessment**  
· **PBT:** Not applicable.  
· **vPvB:** Not applicable.  
· **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**  
· **Recommendation**  After diluting with a suitable desensitisation agent to 10 %, the solution must be supplied to a special treatment (e. g. thermal utilization) under observance of all official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
· **Waste disposal key:** Please contact your hazardous waste disposers to assign the right EWC-(European waste catalog)-number.




(Contd. on page 8)

Trade name: **PEROXAN MI-60 KX**

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:** This material and its container must be disposed of as hazardous waste.

#### SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	UN3105	
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	UN3105 ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ISOBUTYL KETONE PEROXIDE(S)), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ISOBUTYL KETONE PEROXIDE(S)), MARINE POLLUTANT ORGANIC PEROXIDE TYPE D, LIQUID (METHYL ISOBUTYL KETONE PEROXIDE(S))	
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>	<div style="display: flex; align-items: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	5.2 (P1) Organic peroxides. 5.2
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> </ul>	<div style="display: flex; align-items: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> <li>· <b>IATA</b></li> </ul>	<div style="display: flex; align-items: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	5.2 Organic peroxides. 5.2
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	Void	
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> <li>· <b>Special marking (ADR):</b></li> </ul>	Symbol (fish and tree) Symbol (fish and tree)	
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>Stowage Category</b></li> <li>· <b>Stowage Code</b></li> <li>· <b>Segregation Code</b></li> </ul>	Warning: Organic peroxides. - D SW1 Protected from sources of heat. SG35 Stow "separated from" acids. SG36 Stow "separated from" alkalis. SG72 See 7.2.6.3.2.	
<ul style="list-style-type: none"> <li>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	Not applicable.	
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> <li>· <b>RID / GGVSEB:</b></li> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> </ul>	125 ml Code: E0 Not permitted as Excepted Quantity 2 D like ADR 125 ml	

(Contd. on page 9)  
GB



Trade name: **PEROXAN MI-60 KX**

(Contd. of page 8)

· **Exempted quantities (EQ)**

Code: E0

Not permitted as Exempted Quantity

**SECTION 15: Regulatory information**· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances**- **ANNEX I**

None of the ingredients is listed.

· **Seveso category**

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements**

50 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements**

200 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3

· **National regulations:**· **Other regulations, limitations and prohibitive regulations**· **Please note:**

Take care of the respective local regulations.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H242 Heating may cause a fire.  
H271 May cause fire or explosion; strong oxidiser.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:**

Environment protection / Security of labour

· **Contact:**

Tel: +49 2871 9902-0

E-mail: mail@pergan.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Ox. Liq. 1: Oxidizing liquids – Category 1  
Org. Perox. D: Organic peroxides – Type C/D  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

GB

---

Trade name: **PEROXAN MI-60 KX**

---

(Contd. of page 9)

Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the  
previous version altered.**